

Specifications-Sheathing

Plytanium® plywood sheathing is ideal for residential and light commercial construction, and provides outstanding performance for walls and roofs. It adds proven performance and durability to new homes, room additions and renovations.

Available Sizes (Sized for 4' x 8')

Square Edge 3'-11%" (1.216 m) x 7'-11%" (2.435 m)

Building Code Performance Categories, Panel Thickness

• 3/8 CAT, 0.354" (8.99 mm)

• 15/32 CAT (3-ply), 0.451" (11.45 mm)

• 15/32 CAT (4-ply), 0.451" (11.45 mm)

• 19/32 CAT, 0.578" (14.68 mm)

• 23/32 CAT, 0.703" (17.85 mm)

Specifications

Length/Width Tolerance +0, $-\frac{1}{16}$ " (+0, -1.6 mm)

Testing Agency APA®-The Engineered Wood Association

Classifications Exposure 1 – OSB suitable for uses not permanently exposed to the weather. Panels classified

as Exposure 1 are intended to resist the effects of mositure on structural performance as may

occur due to construction delays, or other conditions of similar severity.

Exterior - Plywood suitable for repeated wetting and redrying or long-term exposure to

weather and other conditions of similar severity.

Code Fire Classification Class III or C

Flame Spread Rating 76-200, smoke-developed index <450

Building Code Compliance PS 1-09 or PS 2-10

Other Information

Forestry Certification Plytanium plywood panels are made from wood sourced through

a system that is third-party certified to the Sustainable Forestry

Initiative® procurement standard.

Green Building Programs See our Plytanium plywood Sustainability Fact Sheet available at

www.builditbetter.com for more information on potential point contributions towards specific green building programs.

NAHB Green Approved Plytanium plywood has been "Green Approved" by the NAHB

Research Center, which means you can be assured that Plytanium

plywood complies with specific green practice criteria in the National Green Building Standard. See our product listing on www.GreenApprovedProducts.com for more information.



Good for you. Good for our forests.™





Specifications-Sheathing

Product Warranty

Plytanium® plywood is covered by a Lifetime Limited Warranty. For terms and conditions, please refer to our Lifetime Limited Warranty available at www.builditbetter.com.

International Shipping

To prevent the introduction and spread of plant pests, *ISPM 15: International Standards for Phytosanitary Measures*, requires that internationally shipped solid wood pallets be debarked, treated with heat or fumigated with methyl bromide, and marked with a seal of compliance. **Pallets made with engineered wood, including Plytanium plywood, are exempt from ISPM 15 regulations.** This is because the process of manufacturing engineered wood destroys any live organisms in the wood. (Source: "Boxes, Crate and Reel Manufacturing," *www.PerformancePanels.com*)

Formaldehyde Emissions

Plytanium plywood contains no added urea formaldehyde resins. PS 1 and PS 2 structural panels are exempt from testing by the California Air Resources Board (CARB) in the *Composite Wood Air Toxic Control Measure (ATCM)* and phenolic bonded structural panels are exempt from testing or monitoring by HUD in the *Manufactured Home Construction and Safety Standards*.

Manufacturing Locations

| Location | APA Mill Number | Zip Code | Harvest Radius |
|------------------|--------------------|-------------|-------------------|
| Camden, TX | 515 | 75934 | 90 miles |
| Corrigan, TX | 516 | 75939 | 90 miles |
| Dudley, NC | 348 | 28333 | 80 miles |
| Emporia, VA | 230 | 23847 | 40 miles |
| Gurdon, AR | 517 | 71743 | 60 miles |
| Madison, GA | 404 | 30650 | 100 miles |
| Prosperity, SC | 329 | 29127 | 80 miles |
| Taylorsville, MS | 282 | 39168 | 50 miles |
| Warm Springs, GA | 324 | 31830 | 450 miles |

