



## ZGXJ.R25826 Wind-resistant Building Components

Page Bottom

### Wind-resistant Building Components

See General Information for Wind-resistant Building Components

**INGERSOLL RAND SECURITY TECHNOLOGIES**

R25826

6810 HILLSDALE CT  
INDIANAPOLIS, IN 46250 USA

Flush Door and Frame Assemblies tested to ASTM E330-02:

Door Model	Max Opening Size (Singles or Pairs)	Frame Model	Hardware Options	Gasketing	Design Pressure
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Schlage AL, ND, A, S; Falcon T, B, Z, X, S, H; Ives FB51P, FB31P; Ives 3CB1 4.5 X 4.5 hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+/- 50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Schlage L9000, L9400; Falcon M Series, Locknetics CM5500 Series; Ives SB453, SB543/454, 360, SB361, SB 1630, and 3CB1 4.5 X 4.5 hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+/- 50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 33/3527A, 33/3527A-F, 2227, 2227-F, 8827, 98/9927, 98/9927-F, 98/9957, 98/9957-F, 299 Strike; Ives 3CB1 4.5 X 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+50/-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 9447 with 338 Strike, 94/9547, 94/9547-F, 33/3547A, 33/3547A-F, 98/9947, 98/9947-F, Ives 3CB1 4.5 x 4.5	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/- 50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 22 Rim with 4954 Mullion and 299 Strike, 22 Rim with 4954 Mullion/KR4954, 22-F x 9954/KR9954; Ives 5BB91 4.5 x 4.5	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50/-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Monarch 19-R with 4023 Mullion	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/- 50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 99 Rim with KR4954 Mullion and 299 Strike, 98/99 Rim with 4954/KR4954 Mullion, 98/99-F x 9954/KR9954 Mullion; Ives 5BB91 4.5 x 4.5 hinges	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50/-40 PSF

L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 33A Rim with 4954 Mullion and 299 Strike, 33/35A Rim with 4954/KR4954 Mullion; Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/- 50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 88 Rim with 4954 Mullion and 299 Strike, 88 Rim with 4954/KR4954 Mullion, 88-F with 9954/KR9954 Mullion and 299 Strike; Ives 5BB91 4.5 x 4.5	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/- 50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Schlage AL, ND, A, S, L9000, L9400; Falcon T, B, Z, X, S, H, M' Locknetics CM5500; Von Duprin Model 6211, 6200 Series w/wo AL/WF suffixes and 6210 Series electric strikes; Ives 5BB91 4.5 x 4.5 hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+ 50/-45 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 9475 with 575 Strike, 94/9575 with 575 Strike, 94/9575-F with 575 Strike, 8875 with 575 Strike, 8875-F with 575 Strike, 5575 with 575 Strike, 5575-F with 575 Strike, 98/9975 with 575 Strike, 98/9975-F with 575 Strike, 7500 Series; Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50/-45 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Monarch 18-M with 1279 Strike, Monarch 17-M with 1279 Strike, Monarch XX-M with 1279 Strike, Monarch F18-M with 1279 Strike, Monarch F17-M with 1279 Strike, Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/-50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Falcon 24-M with 1279 Strike, Falcon 25-M with 1279 Strike, Falcon F-24-M with 1279 Strike, Falcon F-25-M with 1279 Strike, with Ives 5BB91 4.5 x 4.5 Hinges	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/-50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 2670 Guard with 267 Strike, Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+55/-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Monarch 17-V, Monarch 18-V, Monarch 19-V, Monarch XX-V, Monarch 18-TPL, Monarch XX-TPL, Monarch F17-V, Monarch F18-V, Monarch F-19-V, Monarch F18-TPL, Monarch FXX-TPL with Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/-50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Falcon 24-V, Falcon 25-V, Falcon F-24-V, Falcon F-25-V, with Ives 5BB91 4.5 x 4.5 Hinges	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/-50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Von Duprin 55 Rim with 1408 Strike and 5754 Mullion	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/-50 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Monarch 18-C, Monarch 17-C, Monarch XX-C, Monarch F18-C, Monarch F17-C, Monarch FXX-C with Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50/-60 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Falcon 24-C, Falcon 25-C, Falcon F-24-C, Falcon F-25-C, with Ives 5BB91 4.5 x 4.5 Hinges	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50/-60 PSF
L18, L16, L14,	8 ft. x 8 ft.	F16, MU16, F14,	Von Duprin 5547	Steelcraft PS-	+/-60

B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16		MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth		074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	PCF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Schlage B100, Schlage B400, Schlage B600/700/800, Schlage L400, Falcon D400, Falcon D800 with Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+60/-45 PCF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft with 1/4 in. Glazing materials.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 33-Series exit devices Von Duprin 3327x8827 Surface Vertical Rod Exit devices	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50/-40 PCF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. jamb depth or Minimum 4-3/4 in. Jamb Depth	Monarch 17-R-2923, Monarch 18-Rx2923, Monarch 19- Rx2923, Monarch XX-Rx2923, Monarch F17-R, Monarch F18-R, Monarch FXX-R, with additional with 4203, F4023, CR4023, CR-F4023 and 4423 Mullions and Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+/-50 PCF

Full Glass Door and Frame with 1/4 in. glazing materials , Assemblies tested to ASTM E330-02:

Door Model	Max Opening Size (Singles or Pairs)	Frame Model	Hardware Options	Gasketing	Design Pressure
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Schlage AL, ND, A, S; Falcon T, B, Z, X, S, H; Ives FB51P, FB31P; Ives 3CB1 4.5 X 4.5 hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Schlage L9000, L9400; Falcon M Series, Locknetics CM5500 Series; Ives SB453, SB543/454, 360, SB361, SB 1630, and 3CB1 4.5 X 4.5 hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 33/3527A, 33/3527A-F, 2227, 2227-F, 8827, 98/9927, 98/9927-F, 98/9957, 98/9957-F, 299 Strike; Ives 3CB1 4.5 X 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 9447 with 338 Strike, 94/9547, 94/9547-F, 33/3547A, 33/3547A-F, 98/9947, 98/9947-F, Ives 3CB1 4.5 x 4.5	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 22 Rim with 4954 Mullion and 299 Strike, 22 Rim with 4954 Mullion/KR4954, 22-F x 9954/KR9954; Ives 5BB91 4.5 x 4.5	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Monarch 19-R with 4023 Mullion	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 99 Rim with KR4954 Mullion and 299 Strike, 98/99 Rim with 4954/KR4954 Mullion, 98/99-F x 9954/KR9954 Mullion; Ives 5BB91 4.5 x 4.5 hinges	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split	+50-40 PSF

CE 18, CE16				Astragal	
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 33A Rim with 4954 Mullion and 299 Strike, 33/35A Rim with 4954/KR4954 Mullion; Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 88 Rim with 4954 Mullion and 299 Strike, 88 Rim with 4954/KR4954 Mullion, 88-F with 9954/KR9954 Mullion and 299 Strike; Ives 5BB91 4.5 x 4.5	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Schlage AL, ND, A, S, L9000, L9400; Falcon T, B, Z, X, S, H, M' Locknetics CM5500; Von Duprin Model 6211, 6200 Series w/wo AL/WF suffixes and 6210 Series electric strikes; Ives 5BB91 4.5 x 4.5 hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.)	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 9475 with 575 Strike, 94/9575 with 575 Strike, 94/9575-F with 575 Strike, 8875 with 575 Strike, 8875-F with 575 Strike, 5575 with 575 Strike, 5575-F with 575 Strike, 98/9975 with 575 Strike, 98/9975-F with 575 Strike, 7500 Series; Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Monarch 18-M with 1279 Strike, Monarch 17-M with 1279 Strike, Monarch XX-M with 1279 Strike, Monarch F18-M with 1279 Strike, Monarch F17-M with 1279 Strike, Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Falcon 24-M with 1279 Strike, Falcon 25-M with 1279 Strike, Falcon F-24-M with 1279 Strike, Falcon F-25-M with 1279 Strike, with Ives 5BB91 4.5 x 4.5 Hinges	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 2670 Guard with 267 Strike, Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Monarch 17-V, Monarch 18-V, Monarch 19-V, Monarch XX-V, Monarch 18-TPL, Monarch XX-TPL, Monarch F17-V, Monarch F18-V, Monarch F-19-V, Monarch F18-TPL, Monarch FXX-TPL with Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Falcon 24-V, Falcon 25-V, Falcon F-24-V, Falcon F-25-V, with Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 55 Rim with 1408 Strike and 5754 Mullion	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Monarch 18-C, Monarch 17-C, Monarch XX-C, Monarch F18-C, Monarch F17-C, Monarch FXX-C with Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Falcon 24-C, Falcon 25-C, Falcon F-24-C, Falcon F-25-C, with Ives 5BB91 4.5 x 4.5 Hinges	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF

L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 5547	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	4 ft. x 8 ft. Single Door	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Schlage B100, Schlage B400, Schlage B600/700/800, Schlage L400, Falcon D400, Falcon D800 with Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft. with 1/4 in. Glazing materials.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Von Duprin 33-Series exit devices Von Duprin 3327x8827 Surface Vertical Rod Exit devices	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF
L18, L16, L14, B18, B16, B14, T18, T16, T14, SL18, SL 16, CE 18, CE16	8 ft. x 8 ft.	F16, MU16, F14, MU14 Minimum 5-3/4 in. Jamb Depth	Monarch 17-R-2923, Monarch 18-Rx2923, Monarch 19-Rx2923, Monarch XX-Rx2923, Monarch F17-R, Monarch F18-R, Monarch FXX-R, with additional with 4203, F4023, CR4023, CR-F4023 and 4423 Mullions and Ives 5BB91 4.5 x 4.5 Hinge	Steelcraft PS-074/Durable HLT-205V Threshold (1/4 in.), Zero 328 Split Astragal	+50-40 PSF

Last Updated on 2009-09-09

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2009 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

