



ZHEM.R27043 Latching Hardware

[Page Bottom](#)

Latching Hardware

[See General Information for Latching Hardware](#)

HANCHETT ENTRY SYSTEMS INC

R27043

10027 S 51ST ST
PHOENIX, AZ 85044 USA

Model	Type	Config-uration	Max Door Size (ft-in.)	Stiffness Class (min)	Max Design Pressure (psf)	Max Impact Energy Resistance (ft-lbs)	Latch Throw Min (in.)	Max Latch Design Pressure (lbf)	Test Method(s) *
9600	Electric strike	Single out-swing	4 ft - 0 in. by 8 ft - 0 in.	I	60	350	3/4	960	SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203

* See [ZHCH](#) for ratings and construction details.

[Last Updated](#) on 2011-08-16

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

