ONLINE CERTIFICATIONS DIRECTORY

ZHEM.R27043 Latching Hardware

Page Bottom

Latching Hardware

See General Information for Latching Hardware

HANCHETT ENTRY SYSTEMS INC

R27043

10027 S 51ST ST PHOENIX, AZ 85044 USA

Model	Туре	Config- uration	Max Door Size (ft-in.)	Stiffness Class (min)	Max Design Pressure (psf)	Max Impact Energy Resistance (ft-lbs)	Latch Throw Min (in.)	Max Latch Design Pressure (Ibf)	Test Method(s)*
9600	Electric strike	Single out- swing	4 ft - 0 in. by 8 ft - 0 in.	I	60	350	3/4	960	SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203
1006	Electric strike Paired with Latch Bolt and Deadbolt Engaged	Single out- swing	4 ft - 0 in. by 8 ft - 0 in.	I	70	350	3/4	1120	SDI-BHMA A250.13, ASTM E330, ASTM E1886, ASTM E1996, TAS 201, TAS 202, TAS 203

* See ZHCH for ratings and construction details.

Last Updated on 2013-02-19

Questions?

Print this page

Terms of Use

Page Top

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the UL Environment database for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".