



ZHLL.R38772

Products for Use in Windstorm-rated Assemblies

[CTR](#)
 [Standards](#)
 [Page Bottom](#)
 [LIS Home Page](#)
 [Corporate Home Page](#)

Products for Use in Windstorm-rated Assemblies

[See General Information for Products for Use in Windstorm-rated Assemblies](#)

ACTIVE VENTILATION PRODUCTS INC
 311 1ST ST
 NEWBURGH, NY 12550 USA

May 10, 2017 R38772

Product	Assembly No.	Test Method	Ratings
Keepa Vent Series: Models KV 04, KV 06, KV 08, KV 10, KV 12	48	TAS 202 (Structural Load Only)	Design Pressure - ± 91 psf Static Test Pressure - ± 136 psf
		ASTM E330	Design Pressure - ± 91 psf Static Test Pressure - ± 136 psf
Round Back Vent Series: Models RBV 3 C2, RBV 3 C4, RBV 4 C2, RBV 4 C4, RBV 5 C2, RBV 5 C4, RBV 6 C2, RBV 6 C4, RBV 8 C2, RBV 8 C4, RBV 10 C2, RBV 10 C4	48	TAS 202 (Structural Load Only)	Design Pressure - ± 91 psf Static Test Pressure - ± 136 psf
		ASTM E330	Design Pressure - ± 91 psf Static Test

			Pressure - ± 136 psf
Universal Vent Series: Model UV 15	48	TAS 202 (Structural Load Only)	Design Pressure - ± 91 psf Static Test Pressure - ± 136 psf
		ASTM E330	Design Pressure - ± 91 psf Static Test Pressure - ± 136 psf
Universal Vent Series: Models UV 30, UV 45, UV 60, UV 75, UV 90, UV 105, UV 120, UV 135	48	TAS 202 (Structural Load Only)	Design Pressure - ± 68 psf Static Test Pressure - ± 102 psf
		ASTM E330	Design Pressure - ± 68 psf Static Test Pressure - ± 102 psf
