


MIAMI TECH, INC.

MECHANICAL UNIT ALUMINUM TIE-DOWN CLIP: AT GRADE & ROOF-TOP MOUNTED APPLICATIONS


ALUMINUM TIE-DOWN CLIP

SIDE VIEW TYP.



ALL OTHER CLIPS SIMILAR
VARYING LENGTH ONLY




1 4" LONG CLIP
1 N.T.S. FLATTENED




2 6" LONG CLIP
1 N.T.S. FLATTENED



3 8" LONG CLIP
1 N.T.S. FLATTENED



4 10" LONG CLIP
1 N.T.S. FLATTENED



5 12" LONG CLIP
1 N.T.S. FLATTENED

DESIGN NOTES:

1. THIS PRODUCT HAS BEEN DESIGNED IN ACCORDANCE WITH ASCE 7-16 AND THE FLORIDA BUILDING CODE SEVENTH EDITION (2020) FOR USE WITHIN AND OUTSIDE THE HIGH VELOCITY HURRICANE ZONE AS INDICATED IN THE ACCOMPANYING DESIGN SCHEDULES. THE DESIGN CRITERIA USED TO CALCULATE THE ALLOWABLE ROOF-TOP HEIGHTS CONSIDERS FBC CHAPTER 16: $(GC)_Lateral=1.90$ WITHIN THE HVHZ & OUTSIDE THE HVHZ, $(GC)_{Uplift}=1.5$ FOR ALL LOCATIONS (CONCURRENT).
2. ALL OTHER DESIGN VARIABLES ARE IN ACCORDANCE WITH ASCE 7 CHAPTERS 26 & 29.
3. THE HEIGHTS LISTED IN THE DESIGN SCHEDULES REPRESENT THE ALLOWABLE HEIGHT OF THE BUILDING.
4. THIS PRODUCT APPROVAL ALLOWS FOR EACH UNIT TO BE INSTALLED ON A MAXIMUM 30" TALL A/C STAND (CERTIFICATION BY OTHERS) ON TOP OF THE HEIGHTS LISTED IN THE DESIGN SCHEDULES.
5. NO 33-1/3% INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE DESIGN OF THIS SYSTEM.
6. DESIGN IS BASED ON CLIENT PROVIDED PRODUCT AND DIE SHEETS FROM TEST REPORT PROJECT #15-6206 BY FENESTRATION TESTING LABORATORY, INC.. NO SUBSTITUTIONS WITHOUT WRITTEN APPROVAL BY THIS ENGINEER SHALL BE PERMITTED.
7. ALL ALUMINUM TIE-DOWN CLIPS SHALL BE 0.080" 5052-H32 ALUMINUM WITH $F_y=28$ KSI OR BETTER.

GENERAL NOTES:

1. THIS PRODUCT HAS BEEN DESIGNED AND SHALL BE FABRICATED IN ACCORDANCE WITH THE REQUIREMENTS OF THE FLORIDA BUILDING CODE & ASCE 7. THIS PRODUCT MAY BE USED WITHIN AND OUTSIDE THE HIGH VELOCITY HURRICANE ZONE.
2. MAXIMUM & MINIMUM DIMENSIONS AND MINIMUM WEIGHT OF MECHANICAL UNIT SHALL CONFORM TO SPECIFICATIONS STATED HEREIN. ALL MECHANICAL SPECIFICATIONS (CLEAR SPACE, TONNAGE, ETC.) SHALL BE AS PER MANUFACTURER RECOMMENDATIONS AND ARE THE EXPRESS RESPONSIBILITY OF THE CONTRACTOR.
3. FASTENERS TO BE #10 X 3/4" OR GREATER STAINLESS STEEL 410 UNLESS NOTED OTHERWISE. ANCHORS REFERRED TO HEREIN SHALL BE ELCO BRAND, STAINLESS STEEL ONLY, INSTALLED TO 3000 PSI MIN CONCRETE. SEE ANCHOR TO HOST SCHEDULE FOR ANCHOR REQUIREMENTS. ALL FASTENERS SHALL HAVE APPROPRIATE CORROSION PROTECTION TO PREVENT ELECTROLYSIS.
4. ALL CONCRETE SPECIFIED HEREIN IS NOT PART OF THIS CERTIFICATION. AS A MINIMUM, ALL CONCRETE SHALL BE STRUCTURAL CONCRETE 4" MIN. THICK AND SHALL HAVE MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI, UNLESS NOTED OTHERWISE.
5. THE CONTRACTOR IS RESPONSIBLE TO INSULATE ALL MEMBERS FROM DISSIMILAR MATERIALS TO PREVENT ELECTROLYSIS.
6. ELECTRICAL GROUND, WHEN REQUIRED, TO BE DESIGNED & INSTALLED BY OTHERS.
7. THE ADEQUACY OF ANY EXISTING STRUCTURE TO WITHSTAND SUPERIMPOSED LOADS SHALL BE VERIFIED BY THE ONSITE DESIGN PROFESSIONAL AND IS NOT INCLUDED IN THIS CERTIFICATION. EXCEPT AS EXPRESSLY PROVIDED HEREIN, NO ADDITIONAL CERTIFICATIONS OR AFFIRMATIONS ARE INTENDED.
8. THE SYSTEM DETAILED HEREIN IS GENERIC AND DOES NOT PROVIDE INFORMATION FOR A SPECIFIC SITE. FOR SITE CONDITIONS DIFFERENT FROM THE CONDITIONS DETAILED HEREIN, A LICENSED ENGINEER OR REGISTERED ARCHITECT SHALL PREPARE SITE SPECIFIC DOCUMENTS FOR USE IN CONJUNCTION WITH THIS DOCUMENT.
9. WATER-TIGHTNESS OF EXISTING HOST SUBSTRATE SHALL BE THE FULL RESPONSIBILITY OF THE INSTALLING CONTRACTOR. CONTRACTOR SHALL ENSURE THAT ANY REMOVED OR ALTERED WATERPROOFING MEMBRANE IS RESTORED AFTER FABRICATION AND INSTALLATION OF STRUCTURE PROPOSED HEREIN. THIS ENGINEER SHALL NOT BE RESPONSIBLE FOR ANY WATERPROOFING OR LEAKAGE ISSUES WHICH MAY OCCUR AS WATER-TIGHTNESS SHALL BE THE FULL RESPONSIBILITY OF THE INSTALLING CONTRACTOR.
10. FOR AN EXPLANATION OF EXPOSURE AND RISK CATEGORIES THAT ACCOMPANY THE VULT WIND SPEEDS USED IN THIS APPROVAL, SEE ASCE 7.

VISIT ECALC.IO/26320

FOR SITE SPECIFIC DEVIATIONS
& MORE INFORMATION ABOUT THIS DOCUMENT
OR SCAN THIS QR CODE
VISIT ENGINEERINGEXPRESS.COM/MIAMITECH
FOR ADDITIONAL PLANS, REPORTS & RESOURCES



FRANK BENNARDO, PE
PE# 0046549 CA# 9985

7/09/20



CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

MIAMI TECH, INC.
3611 NW 74TH ST
MIAMI, FL
(305) 693-7054

MIAMI TECH CUTD TIE-DOWN CLIP CERTIFICATIONS
FBC 7TH EDITION (2020) PRODUCT APPROVAL
FL#19731.1

| REMARKS | DRWN | CHKD | DATE |
|---------------------|------|------|----------|
| INIT ISSUE | LAO | TSB | 02/05/16 |
| REV (ADD DETAILS) | RWN | FLB | 07/14/16 |
| REV 2017 FBC UPDATE | LAO | FLB | 08/15/17 |
| REV 2020 FBC UPDATE | CB | RWN | 6/09/20 |

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS

20-26320

SCALE: N.T.S.

C:\Users\colby\Engineering\Express\Production - Documents\Projects\20-26320 - FL19731.1 - Alum Tie-Down Clip System (at Roof or Grade)\WP\2020\FBC\20-26320 - FL19731.1 - Alum Tie-Down Clip System.dwg

FRANK BENNARDO, PE
 PE# 0046549 CA# 9985
 7/09/20


ENGINEERING EXPRESS
 CORPORATE OFFICE:
 160 SW 12th AVE, SUITE 106
 DEERFIELD BEACH, FL 33442
 (954) 354-0660 | (866) 396-9999
 TEAM@ENGINEERINGEXPRESS.COM
 ENGINEERINGEXPRESS.COM

MIAMI TECH, INC.
 3611 NW 74TH ST
 MIAMI, FL
 (305) 693-7054
 MIAMI TECH CUTD TIE-DOWN CLIP CERTIFICATIONS
 FBC 7TH EDITION (2020) PRODUCT APPROVAL
 FL#19731.1


| REMARKS | DRWN | CHKD | DATE |
|---------------------|------|------|----------|
| INIT ISSUE | LAO | TSB | 02/05/16 |
| REV (ADD DETAILS) | RWN | FLB | 07/14/16 |
| REV 2017 FBC UPDATE | LAO | FLB | 08/15/17 |
| REV 2020 FBC UPDATE | CB | RWN | 6/09/20 |

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®
 20-26320
 SCALE: N.T.S.
 2




C1 CONNECTION TYPE C1
 1"X6" CLIP - UTILIZE (1) AT EACH CORNER FOR A TOTAL OF (4) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIP 4" LONG




C3 CONNECTION TYPE C3
 1"X12" CLIP - UTILIZE (1) AT EACH CORNER FOR A TOTAL OF (4) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIPS 8" & 10" LONG

*NOTE: SEE ANCHOR TO HOST SCHEDULE FOR ALL EDGE DISTANCE TO ANCHOR SPACING LIMITATIONS. SEE PAGE 4.



C2 CONNECTION TYPE C2
 1"X6" CLIP - UTILIZE (2) AT EACH CORNER FOR A TOTAL OF (8) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIP 4" LONG




C4 CONNECTION TYPE C4
 1"X12" CLIP - UTILIZE (2) AT EACH CORNER FOR A TOTAL OF (8) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIPS 8" & 10" LONG

ALUMINUM TIE-DOWN CLIP


C:\Users\colby\Engineering\Express\Production - Documents\Projects\20-26320 - FL19731.1 - Alum Tie-Down Clip System.dwg
 07/09/2020 - 12:10pm colby

ATTACHMENT TO STAND



C1 CONNECTION TYPE C1

1"X6" CLIP - UTILIZE (1) AT EACH CORNER FOR A TOTAL OF (4) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIP 4" LONG




C3 CONNECTION TYPE C3


1"X12" CLIP - UTILIZE (1) AT EACH CORNER FOR A TOTAL OF (4) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIPS 8" & 10" LONG

ALTERNATE CLIP TO STAND DETAIL

SCALE: N.T.S.




*NOTE: SEE ANCHOR TO HOST SCHEDULE FOR ALL EDGE DISTANCE TO ANCHOR SPACING LIMITATIONS. SEE PAGE 4.



C2 CONNECTION TYPE C2

1"X6" CLIP - UTILIZE (2) AT EACH CORNER FOR A TOTAL OF (8) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIP 4" LONG



C4 CONNECTION TYPE C4

1"X12" CLIP - UTILIZE (2) AT EACH CORNER FOR A TOTAL OF (8) PER UNIT
 NOTE: ALSO APPLICABLE FOR CLIPS 8" & 10" LONG

FRANK BENNARDO, PE
 PE# 0046549 CA# 9985
 7/09/20

ENGINEERING EXPRESS
 CORPORATE OFFICE:
 160 SW 12th AVE, SUITE 106
 DEERFIELD BEACH, FL 33442
 (954) 354-0660 | (866) 396-9999
 TEAM@ENGINEERINGEXPRESS.COM
 ENGINEERINGEXPRESS.COM


MIAMI TECH, INC.
 3611 NW 74TH ST
 MIAMI, FL
 (305) 693-7054
 MIAMI TECH CUTD TIE-DOWN CLIP CERTIFICATIONS
 FCC 7TH EDITION (2020) PRODUCT APPROVAL
 FL#19731.1

| REMARKS | DRWN | CHKD | DATE |
|---------------------|------|------|----------|
| INIT ISSUE | LAO | TSB | 02/05/16 |
| REV (ADD DETAILS) | RWN | FLB | 07/14/16 |
| REV 2017 FCC UPDATE | LAO | FLB | 08/15/17 |
| REV 2020 FCC UPDATE | CB | RWN | 6/09/20 |

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.


20-26320
 SCALE: N.T.S.
 3

C:\Users\colby\Engineering\Production - Documents\Projects\20-26320 - FL19731.1 - Alum Tie-Down Clip System (at Roof or Grade)\WPV2020\FBC\20-26320 - FL19731.1 - Alum Tie-Down Clip System.dwg




1 1" CLIP ISOMETRIC DETAIL
4 N.T.S. ISOMETRIC

MECHANICAL UNIT BY OTHERS. ALUMINUM HOUSING UNITS SHALL BE 6063-T6 MIN. ALUMINUM SHEET WITH Fty=30 KSI, 0.125" MIN. THICKNESS, STEEL HOUSING UNITS SHALL BE ASTM A653 Fy=33KSI MIN. STEEL, GRADE 33, 22GA MIN. (t=0.0299").




2 1" TIE-DOWN CLIP ANCHOR DETAIL
4 3" = 1'-0" DETAIL
 CLIP IS DESIGNED FOR FULL CONTACT WITH THE BASE OF EACH MECHANICAL UNIT, TYP.



ANCHOR TO HOST SCHEDULE:

| SUBSTRATE | DESCRIPTION |
|---|--|
| CONCRETE: (4" THICK MIN, 3000 PSI MIN.) | (1)-1/4"Ø STAINLESS STEEL 410 DEWALT ULTRACON, 1 3/4" FULL EMBED TO CONCRETE, 2 1/2" MIN. EDGE DISTANCE, 3" MIN. SPACING TO ANY ADJACENT ANCHOR. |
| ALUMINUM: (0.125" MIN. THICK, 6061-T6 MIN. ALUMINUM) | (1)-#14 SAE STAINLESS STEEL BOLT 410 WITH NUT AND WASHER TOP & BOTTOM SS OD 1", 1/2" MINIMUM EDGE DISTANCE TO METAL EDGE |
| STEEL: (0.125" MIN. THICK, 50 KSI MIN. STEEL) | (1)-#14 SAE STAINLESS STEEL BOLT 410 WITH NUT AND WASHER TOP & BOTTOM SS OD 1", 1/2" MINIMUM EDGE DISTANCE TO METAL EDGE |

1. EMBEDMENT AND EDGE DISTANCE EXCLUDES FINISHES, IF APPLICABLE.
2. ENSURE MINIMUM EDGE DISTANCE AS NOTED IN ANCHOR SCHEDULE.
3. ENSURE MINIMUM SPACING TO ANY ADJACENT ANCHORS.
4. SEE DETAILS ON SHEET 4 FOR ANCHORS ATTACHING TO MECHANICAL UNIT.
5. PROTECT ALL METALS FROM DISSIMILAR METALS GENERAL NOTE #5



3 ALTERNATE (8) CLIP DETAIL
4 N.T.S. PLAN VIEW
 THIS DETAIL MAY BE USED AS AN ALTERNATE GEOMETRIC PATTERN FOR ALL CONNECTION TYPES THAT UTILIZE (2) CLIPS AT EACH CORNER FOR A TOTAL OF (8) CLIPS PER UNIT.

FRANK BENNARDO, PE
 PE# 0046549 CA# 9985
 7/09/20

ENGINEERING EXPRESS
 CORPORATE OFFICE:
 160 SW 12th AVE, SUITE 106
 DEERFIELD BEACH, FL 33442
 (954) 354-0660 | (866) 396-9999
 TEAM@ENGINEERINGEXPRESS.COM
 ENGINEERINGEXPRESS.COM

MIAMI TECH, INC.
 3611 NW 74TH ST
 MIAMI, FL
 (305) 693-7054
 MIAMI TECH CUTD TIE-DOWN CLIP CERTIFICATIONS
 FBC 7TH EDITION (2020) PRODUCT APPROVAL
 FL#19731.1

| REMARKS | DRWN | CHKD | DATE |
|---------------------|------|------|----------|
| INIT ISSUE | LAO | TSB | 02/05/16 |
| REV (ADD DETAILS) | RWN | FLB | 07/14/16 |
| REV 2017 FBC UPDATE | LAO | FLB | 08/15/17 |
| REV 2020 FBC UPDATE | CB | RWN | 6/09/20 |

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

20-26320
 SCALE: N.T.S.
4

ALUMINUM TIE-DOWN CLIP

TABLE 1 PERMISSIBLE INSTALLATION HEIGHTS: VuIt=175 MPH, EXPOSURE C

(FOR USE WITH A RISK CATEGORY II STRUCTURE IN THE HIGH VELOCITY HURRICANE ZONE (HVHZ)*)
RISK CATEGORY II IS PER ASCE 7-16

| MAXIMUM SURFACE AREA OF UNIT'S LARGEST FACE | UNIT HEIGHT | UNIT WIDTH | ALLOWABLE ROOF-TOP HEIGHT (H) TIE-DOWN CONFIGURATION TYPE | | | |
|---|-------------|------------|--|------------|----------|------------|
| | | | C1 | C2 | C3 | C4 |
| 6 FT ² | 29" MAX | 15" MIN | N/A | H ≤ 40 FT | N/A | H ≤ 40 FT |
| 9 FT ² | 36" MAX | 27" MIN | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 4 FT ² | 48" MAX | 36" MIN | AT GRADE | H ≤ 200 FT | AT GRADE | H ≤ 200 FT |
| 6 FT ² | | | N/A | H ≤ 140 FT | N/A | H ≤ 140 FT |
| 9 FT ² | | | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 12 FT ² | | | N/A | AT GRADE | N/A | AT GRADE |
| 16 FT ² | | | N/A | N/A | N/A | N/A |
| 20 FT ² | 60" MAX | 48" MIN | N/A | N/A | N/A | N/A |
| 25 FT ² | | | N/A | N/A | N/A | N/A |
| 30 FT ² | | | N/A | N/A | N/A | N/A |
| 36 FT ² | | | N/A | N/A | N/A | N/A |

*THIS TABLE IS PERMISSIBLE TO BE USED WITHIN THE HVHZ WHICH CONTAINS BROWARD AND MIAMI-DADE COUNTIES. CHECK WITH LOCAL AUTHORITY HAVING JURISDICTION FOR THE APPLICABILITY OF THIS TABLE WITHIN CERTAIN FLORIDA COUNTIES.

TABLE 2 PERMISSIBLE INSTALLATION HEIGHTS: VuIt=175 MPH, EXPOSURE D

(FOR USE WITH A RISK CATEGORY II STRUCTURE IN THE HIGH VELOCITY HURRICANE ZONE (HVHZ)*)
RISK CATEGORY II IS PER ASCE 7-16

| MAXIMUM SURFACE AREA OF UNIT'S LARGEST FACE | UNIT HEIGHT | UNIT WIDTH | ALLOWABLE ROOF-TOP HEIGHT (H) TIE-DOWN CONFIGURATION TYPE | | | |
|---|-------------|------------|--|------------|----------|------------|
| | | | C1 | C2 | C3 | C4 |
| 6 FT ² | 29" MAX | 15" MIN | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 9 FT ² | 36" MAX | 27" MIN | N/A | AT GRADE | N/A | AT GRADE |
| 4 FT ² | 48" MAX | 36" MIN | AT GRADE | H ≤ 200 FT | AT GRADE | H ≤ 200 FT |
| 6 FT ² | | | N/A | H ≤ 60 FT | N/A | H ≤ 80 FT |
| 9 FT ² | | | N/A | AT GRADE | N/A | AT GRADE |
| 12 FT ² | | | N/A | AT GRADE | N/A | AT GRADE |
| 16 FT ² | | | N/A | N/A | N/A | N/A |
| 20 FT ² | 60" MAX | 48" MIN | N/A | N/A | N/A | N/A |
| 25 FT ² | | | N/A | N/A | N/A | N/A |
| 30 FT ² | | | N/A | N/A | N/A | N/A |
| 36 FT ² | | | N/A | N/A | N/A | N/A |

*THIS TABLE IS PERMISSIBLE TO BE USED WITHIN THE HVHZ WHICH CONTAINS BROWARD AND MIAMI-DADE COUNTIES. CHECK WITH LOCAL AUTHORITY HAVING JURISDICTION FOR THE APPLICABILITY OF THIS TABLE WITHIN CERTAIN FLORIDA COUNTIES.

TABLE 3 PERMISSIBLE INSTALLATION HEIGHTS: VuIt=170 MPH, EXPOSURE C

(FOR USE WITH A RISK CATEGORY II STRUCTURE**) RISK CATEGORY II IS PER ASCE 7-16

| MAXIMUM SURFACE AREA OF UNIT'S LARGEST FACE | UNIT HEIGHT | UNIT WIDTH | ALLOWABLE INSTALLATION ROOF HEIGHT TIE-DOWN CONFIGURATION TYPE | | | |
|---|-------------|------------|---|-----------|-----------|-----------|
| | | | C1 | C2 | C3 | C4 |
| 6 ft ² | 29 in | 15 in | N/A | H ≤ 60 FT | N/A | H ≤ 60 FT |
| 9 ft ² | 36 in | 27 in | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 4 ft ² | 48 in | 36 in | H ≤ 15 FT | ≤ 200 FT | H ≤ 15 FT | ≤ 200 FT |
| 6 ft ² | 48 in | 36 in | AT GRADE | ≤ 180 FT | AT GRADE | ≤ 200 FT |
| 9 ft ² | 48 in | 36 in | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 12 ft ² | 48 in | 36 in | N/A | AT GRADE | N/A | AT GRADE |
| 16 ft ² | 48 in | 36 in | N/A | N/A | N/A | N/A |
| 20 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 25 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 30 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 36 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |

TABLE 4 PERMISSIBLE INSTALLATION HEIGHTS: VuIt=170 MPH, EXPOSURE D

(FOR USE WITH A RISK CATEGORY II STRUCTURE**) RISK CATEGORY II IS PER ASCE 7-16

| MAXIMUM SURFACE AREA OF UNIT'S LARGEST FACE | UNIT HEIGHT | UNIT WIDTH | ALLOWABLE INSTALLATION ROOF HEIGHT TIE-DOWN CONFIGURATION TYPE | | | |
|---|-------------|------------|---|-----------|----------|-----------|
| | | | C1 | C2 | C3 | C4 |
| 6 ft ² | 29 in | 15 in | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 9 ft ² | 36 in | 27 in | N/A | AT GRADE | N/A | AT GRADE |
| 4 ft ² | 48 in | 36 in | AT GRADE | ≤ 200 FT | AT GRADE | ≤ 200 FT |
| 6 ft ² | 48 in | 36 in | N/A | ≤ 100 FT | N/A | ≤ 100 FT |
| 9 ft ² | 48 in | 36 in | N/A | AT GRADE | N/A | AT GRADE |
| 12 ft ² | 48 in | 36 in | N/A | AT GRADE | N/A | AT GRADE |
| 16 ft ² | 48 in | 36 in | N/A | N/A | N/A | N/A |
| 20 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 25 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 30 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 36 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |

**AS AN EXAMPLE, THESE TABLES ARE PERMISSIBLE TO BE USED WITHIN PALM BEACH COUNTY. CHECK WITH LOCAL AUTHORITY HAVING JURISDICTION FOR THE APPLICABILITY OF THESE TABLES WITHIN CERTAIN FLORIDA COUNTIES.

FRANK BENNARDO, PE
PE# 0046549 CA# 9985



ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

MIAMI TECH, INC.

3611 NW 74TH ST
MIAMI, FL
(305) 693-7054

MIAMI TECH CUIDD TIE-DOWN CLIP CERTIFICATIONS
FBC 7TH EDITION (2020) PRODUCT APPROVAL
FL#19731.1

| REMARKS | DRWN | CHKD | DATE |
|---------------------|------|------|----------|
| INIT ISSUE | LAO | TSB | 02/05/16 |
| REV (ADD DETAILS) | IRWN | FLB | 07/14/16 |
| REV 2017 FBC UPDATE | LAO | FLB | 08/15/17 |
| REV 2020 FBC UPDATE | CB | RWN | 6/09/20 |

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®

20-26320

SCALE: N.T.S.

ALUMINUM TIE-DOWN CLIP



TABLE 5 PERMISSIBLE INSTALLATION HEIGHTS: VuIt=140 MPH, EXPOSURE B

(FOR USE WITH A RISK CATEGORY II STRUCTURE***)
RISK CATEGORY II IS PER ASCE 7-16

| MAXIMUM SURFACE AREA OF UNIT'S LARGEST FACE | UNIT HEIGHT | UNIT WIDTH | ALLOWABLE INSTALLATION ROOF HEIGHT TIE-DOWN CONFIGURATION TYPE | | | |
|---|-------------|------------|--|-----------|-----------|-----------|
| | | | C1 | C2 | C3 | C4 |
| 6 ft ² | 29 in | 15 in | H ≤ 15 FT | ≤ 200 FT | H ≤ 15 FT | ≤ 200 FT |
| 9 ft ² | 36 in | 27 in | AT GRADE | ≤ 200 FT | AT GRADE | ≤ 200 FT |
| 4 ft ² | 48 in | 36 in | ≤ 200 FT | ≤ 200 FT | ≤ 200 FT | ≤ 200 FT |
| 6 ft ² | 48 in | 36 in | H ≤ 40 FT | ≤ 200 FT | H ≤ 60 FT | ≤ 200 FT |
| 9 ft ² | 48 in | 36 in | AT GRADE | ≤ 200 FT | AT GRADE | ≤ 200 FT |
| 12 ft ² | 48 in | 36 in | AT GRADE | ≤ 120 FT | AT GRADE | ≤ 120 FT |
| 16 ft ² | 48 in | 36 in | N/A | H ≤ 40 FT | N/A | H ≤ 40 FT |
| 20 ft ² | 60 in | 48 in | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 25 ft ² | 60 in | 48 in | N/A | AT GRADE | N/A | AT GRADE |
| 30 ft ² | 60 in | 48 in | N/A | AT GRADE | N/A | AT GRADE |
| 36 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |

TABLE 6 PERMISSIBLE INSTALLATION HEIGHTS: VuIt=140 MPH, EXPOSURE C

(FOR USE WITH A RISK CATEGORY II STRUCTURE***)
RISK CATEGORY II IS PER ASCE 7-16

| MAXIMUM SURFACE AREA OF UNIT'S LARGEST FACE | UNIT HEIGHT | UNIT WIDTH | ALLOWABLE INSTALLATION ROOF HEIGHT TIE-DOWN CONFIGURATION TYPE | | | |
|---|-------------|------------|--|-----------|----------|-----------|
| | | | C1 | C2 | C3 | C4 |
| 6 ft ² | 29 in | 15 in | AT GRADE | ≤ 200 FT | AT GRADE | ≤ 200 FT |
| 9 ft ² | 36 in | 27 in | N/A | ≤ 160 FT | AT GRADE | ≤ 160 FT |
| 4 ft ² | 48 in | 36 in | ≤ 100 FT | ≤ 200 FT | ≤ 100 FT | ≤ 200 FT |
| 6 ft ² | 48 in | 36 in | AT GRADE | ≤ 200 FT | AT GRADE | ≤ 200 FT |
| 9 ft ² | 48 in | 36 in | AT GRADE | ≤ 180 FT | AT GRADE | ≤ 180 FT |
| 12 ft ² | 48 in | 36 in | N/A | H ≤ 40 FT | N/A | H ≤ 40 FT |
| 16 ft ² | 48 in | 36 in | N/A | AT GRADE | N/A | AT GRADE |
| 20 ft ² | 60 in | 48 in | N/A | AT GRADE | N/A | AT GRADE |
| 25 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 30 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 36 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |

TABLE 7 PERMISSIBLE INSTALLATION HEIGHTS: VuIt=140 MPH, EXPOSURE D

(FOR USE WITH A RISK CATEGORY II STRUCTURE***)
RISK CATEGORY II IS PER ASCE 7-16

| MAXIMUM SURFACE AREA OF UNIT'S LARGEST FACE | UNIT HEIGHT | UNIT WIDTH | ALLOWABLE INSTALLATION ROOF HEIGHT TIE-DOWN CONFIGURATION TYPE | | | |
|---|-------------|------------|--|-----------|-----------|-----------|
| | | | C1 | C2 | C3 | C4 |
| 6 ft ² | 29 in | 15 in | N/A | ≤ 200 FT | N/A | ≤ 200 FT |
| 9 ft ² | 36 in | 27 in | N/A | ≤ 80 FT | N/A | ≤ 80 FT |
| 4 ft ² | 48 in | 36 in | H ≤ 40 FT | ≤ 200 FT | H ≤ 40 FT | ≤ 200 FT |
| 6 ft ² | 48 in | 36 in | AT GRADE | ≤ 200 FT | AT GRADE | ≤ 200 FT |
| 9 ft ² | 48 in | 36 in | N/A | ≤ 80 FT | N/A | ≤ 100 FT |
| 12 ft ² | 48 in | 36 in | N/A | H ≤ 15 FT | N/A | H ≤ 15 FT |
| 16 ft ² | 48 in | 36 in | N/A | AT GRADE | N/A | AT GRADE |
| 20 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 25 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 30 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |
| 36 ft ² | 60 in | 48 in | N/A | N/A | N/A | N/A |

***AS AN EXAMPLE, THESE TABLES ARE PERMISSIBLE TO BE USED WITHIN BREVARD COUNTY. CHECK WITH LOCAL AUTHORITY HAVING JURISDICTION FOR THE APPLICABILITY OF THIS TABLE WITHIN CERTAIN FLORIDA COUNTIES.



ENGINEERING EXPRESS
CORPORATE OFFICE:
160 SW 12th AVE, SUITE 106
DEERFIELD BEACH, FL 33442
(954) 354-0660 | (866) 396-9999
TEAM@ENGINEERINGEXPRESS.COM
ENGINEERINGEXPRESS.COM

MIAMI TECH, INC.
3611 NW 74TH ST
MIAMI, FL
(305) 693-7054

MIAMI TECH CUIDD TIE-DOWN CLIP CERTIFICATIONS
FBC 7TH EDITION (2020) PRODUCT APPROVAL
FL#19731.1

| REMARKS | DRWN | CHKD | DATE |
|---------------------|------|------|----------|
| INIT ISSUE | LAO | TSB | 02/05/16 |
| REV (ADD DETAILS) | RWN | FLB | 07/14/16 |
| REV 2017 FBC UPDATE | LAO | FLB | 08/15/17 |
| REV 2020 FBC UPDATE | CB | RWN | 6/09/20 |

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®
20-26320
SCALE: N.T.S.

ALUMINUM TIE-DOWN CLIP

C:\Users\colby\Engineering\Express\Production - Documents\Projects\20-26320 - FL19731.1 - Alum Tie-Down Clip System (at Roof or Grade)\WP\2020\FBC\20-26320 - FL19731.1 - Alum Tie-Down Clip System.dwg