

398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

# **Product Evaluation Report**

of

Croft, LLC Series 20 Single Hung Tilt Window (Non-HVHZ) (Non-Impact)

## for

**Florida Product Approval** 

## FL# FL16082

# Report No. 7707

## **Current Florida Building Code**

Method: Category: Sub – Category: 1 – A (Certificate) Windows Single Hung

Product: Materials: Product Dimensions: Series 20 Single Hung Tilt Window PVC See Installation Instructions, 0020-951


## **Prepared for:**

Croft, LLC P.O. Box 826 McComb, MS. 39649

### Prepared by:

Hermes F. Norero, P.E. Florida Professional Engineer # 73778 Date: 9/3/2021

Contents: Evaluation Report Pages 1 – 3



Hermes F. Norero, P.E. Florida P.E. No. 73778



 FL#:
 FL16082

 Date:
 9/3/2021

 Report No:
 7707

### 398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Manufacturer:	:	Croft, LLC	
Product Category:		Windows	
Product Sub-Category:		Single Hung	
Compliance Method:		State Product Approval Method (1)(a)	
Product Name	:	Series 20 Single Hung Tilt Window (Non-HVHZ) (Non-Impact)	
Scope:	This is a Product Evaluation Report issued by Hermes F. Norero, P.E. (FL # 73778) <b>Croft, LLC</b> based on <u>Method 1a</u> of the State of Florida Product Approval, Department of Business and Professional Regulation - Florida Building Commission.		
	Hermes F. Norero, P.E. does not have nor will acquire financial interest in the com manufacturing or distributing the product or in any other entity involved in the ap process of the product named herein.		
	This product has been evaluated for use in locations adhering to the current Florida Building Code.		
	See Installation Instructions <b>0020-951</b> , signed and sealed by Hermes F. Norero, P.E. (FL # 73778) for specific use parameters.		
Limits of Use:			
	1.	This product has been evaluated and is in compliance with the current Florida Building Code, <u>excluding</u> the "High Velocity Hurricane Zone" (HVHZ).	
	2.	Product anchors shall be as listed and spaced as shown on details. Anchor embedment into substrate material shall be beyond wall dressing or stucco.	
	3.	When used in areas requiring wind borne debris protection this product complies with Chapter 16 of the current Florida Building Code and <u>does require</u> an impact resistant covering.	
	4.	Site conditions that deviate from the details of installation instructions <b>0020-951</b> require further engineering analysis by a licensed engineer or registered architect.	
	5.	See Installation Instructions <b>0020-951</b> for size and design pressure limitations.	

5. See Installation Instructions **0020-951** for size and design pressure limitations.

Page 2 of 3

954.399.8478

C

6

954.744.4738



### 398 E DANIA BEACH BLVD. SUITE 338, DANIA BEACH, FL 33004

Certification Agency:	The manufacturer has demonstrated compliance of manufacture of in accordance with the Florida Building Code for manufacturing und approved certification agency through <b>Fenestration and Glazing Inc</b> Alliance (formerly AAMA) (FBC Organization # CER1498).	ler an
Performance Standards:	The product described herein has been evaluated per:	
	• AAMA/WDMA/CSA 101/I.S.2/A440-11	
Referenced Data:		
	<ol> <li>Product Testing performed by Architectural Testing, Inc. (FBC Organization # TST1910)</li> </ol>	
	Report #: B6276.03-801-47, Report Date: 06/20/2012	
	<ol> <li>Certification Agency</li> <li>Fenestration and Glazing Industry Alliance (formerly AAM/ (FBC Organization #: CER1498)</li> </ol>	۹)

#### Installation:

Refer to Installation Instructions (0020-951) for anchor spacing and more details of the installation requirements.

### **Design Pressure:**

Refer to Installation Instructions (0020-951) for design pressures based on size, configuration, and glass types.

