

Tally Office Bldg.
Budget Price 8-11-2020

Schindler Elevator Corporation
Traction Elevator Specification Summary

Tallahassee, FL 32303

Project Information:

Opportunity ID: 0201685036-AA
 Unit(s) in Estimate: 01
 Units in Bank: 01
 Product Code: 450
 Sales Office: 9686
 Installation Office: 9686

Sales Rep Information:

Chris Cornelius
 9143 Philips Highway
 Suite 260
 Jacksonville, FL 32256
 Phone: (904) 880-4922 Ext 223
 Fax: (904) 880-4916
 Chris.Cornelius@schindler.com

Product:	Schindler 3300	Opening Size:	3 Ft. 0.00 In. X 7 Ft. 0.00 In.
Application:	3300 MRL	Cab Height:	7 Ft. 9 In.
Capacity:	2100 lbs General Purpose	Cab Type:	3300
Speed:	100 FP	Pit Depth:	5 Ft. 0 In.
Travel:	12 Ft. 0.00 In.	Overhead:	12 Ft. 7 In.
Cwt Location:	Side	Inside Cab Width:	5' 9 15/16"
Stops:	2 (2 Front / 0 Rear)	Inside Cab Depth:	4' 4 13/16"
Power Supply:	208 Volts 60 Hz 3 Phase	Hoistway Width:	7 Ft. 6.00 In.
Sprinklers In Hoistway:	N	Hoistway Depth:	5 Ft. 9.00 In.
Doors:	Two Speed Side Opening 01 LH	Seismic Equipment:	N
		NFPA Code Year:	2013

Cab:

Cab Walls LH Side: Laminate - type to be defined
 Cab Walls RH Side: Laminate - type to be defined
 Cab Walls Rear: Laminate - type to be defined
 Base, Frieze: Aluminum
 Front Return, Transom: #4 Stainless Steel
 Cab Doors: #4 Stainless Steel
 Canopy: Schindler
 Ceiling Type: LED Down Light
 Ceiling Finish: Stainless Steel #4
 Cab Threshold: Aluminum
 Threshold Extensions
 Handrail Type: Straight Rectangular
 Handrail Finish: Brushed Aluminum
 Handrail Location: Rear
 Handrail Row Qty: 1
 Platform Recess: 0.375
 Protective Pads: None
 Protective Pads Source: None
 Cab Finished Floor: Carpet By Others

Features:

Follow IBC - 2015
 Audible Gong (Std)
 Infrared Door Protection(Std)
 Phase Monitor Relay(Std)
 Independent Service/HES (Std)
 Top Exit Lock
 FER Door Operator
 T127 Rails
 Keyed Emergency Stop Switch
 Top Exit Switch
 ADA Compliant Phone
 Sliding Guide Shoes
 1 Speed Fan
 2 Hoistway Access Switches
 Firefighter's Service Phase 2
 Class B Fire Rating For Cab
 Top Exit Guard
 Smoke Detector Provisions
 1 Intermediate Support - by Customer
 Intermediate Support(s): 1
 Automatic Evacuation
 Pit Ladder Source: GC
 STM - With Fire Retardant

Entrances:

Emergency Escutcheons
Doors:
 (2) #4 Stainless Steel
Frames:
 (2) #4 Stainless Steel
Sills:
 (2) Aluminum
Sill Mounting:
 (2) Easy Match

Cab Fixtures:

Type: Standard
 Finish: #4 Stainless Steel
 (1) L.E.D. Car Position Indicator
 1 Main COP
 (1) Car Lantern(s)
 Certificate Frame

Hall Fixtures:

Hall Fixtures Type
 Jamb Mounted
 Hall Fixtures Finish
 (2) #4 SS Push Buttons
 (1) Separate FER Switch

New Product Service:

12 Months, 8 Hours Callback

This bid is subject to change after forty-five (45) days.

Visit Our Website @ www.us.schindler.com

2020.2