Florida Building Code 7th Edition (2020) High-Velocity Hurricane Zone Uniform Permit Application Form

Section A (General Information)

Ma	Master Permit No											Process No													
Cor	ntrac	tor's	Nam	ie																					
Job	Add	lress	i																						_
													CAT												-
	Lov	w Slo	ре							Ме	chan	ically	/ Fas	tene	d Tile	Э				tar/A	Adhes	sive		Set	
☐ Asphaltic Shingles ☐ Metal Panel/Shingles											Tiles □ Wood Shingles/Shakes														
										Pre	escrip	otive	BUR	-RAS	3 150)									
_						_							OF T		Ξ						_				
	Nev	v roo	of			Re	epair		D00				ance		TION		Re	roofi	ng		[□ F	Reco	verir	g
Lov	v Slo	pe R	Roof /	Area	(SF)								of Al								Т	otal	(SF) <u>.</u>		
																					and ones				

parapets.

Florida Building Code 7th Edition (2020) High-Velocity Hurricane Zone Uniform Permit Application Form

Section D (Steep Sloped Roof System)

Roof		System								
Number:					Notice	of Acceptance				
Minimum Design Wind	l Pressures. If Apr	olicable (From RA	S 127 or Calcul	ations):						
	Zone 2e				Zone 3r:					
	Deck 1	Type:								
	Deck	уре.								
	\ T\	pe Underlaym	ent:							
Roof Slope:	\	,								
: 12		Insulation:								
		Fire Bar	rrier:							
Ridge Ventilat	tion?	Fas	stener Type &							
			Adhesive T	ype:						
			Type Ca	ap Sheet:						
Mean Roof	Height:		Roc	of Covering:						
				Type & Size	Drip					
				Edge:						

Florida Building Code 7th Edition (2020) High-Velocity Hurricane Zone Uniform Permit Application Form

Section E (Tile Calculations)

For Moment based tile systems, choose either Method 1 or 2. Compare the values for M_r with the values from M_f . If the M_f values are greater than or equal to the M_r values, for each area of the roof, then the tile attachment method is acceptable.

Method 1 "Moment Based Tile Calculations Per RAS 127"

(Zone 1:	x? = _) – Mg:	$_{} = M_{r1} $	Product Approval M _f
(Zone 2e:	x? = _) – Mg:	_ = M _{r2e}	Product Approval M _f
(Zone 2n:	x? = _) – Mg:	_ = <mark>M_{r2n}</mark>	Product Approval M _f
(Zone 2r:	x? =) – Mg:	= <mark>M_{r2r}</mark>	Product Approval M _f
(Zone 3e:	x? =) – Mg:	_ = <mark>M_{r3e}</mark>	Product Approval M _f
(Zone 3r:	x? =) — Ma:	$= M_{r3r}$	Product Approval M _f

Method 2 "Simplified Tile Calculations Per Table Below"

Required Moment of Resistance (M_r) From Table Below _____ Product Approval M_f _____

	(')									
M _r required Moment Resistance*										
Mean Roof Height Roof Slope	150	20□	25□	30□	40□					
2:12	34.4	36.5	38.2	39.7	42.2					
3:12	32.2	34.4	36.0	37.4	39.8					
4:12	30.4	32.2	33.8	35.1	37.3					
5:12	28.4	30.1	31.6	32.8	34.9					
6:12	26.4	28.0	29.4	30.5	32.4					
7:12	24.4	25.9	27.1	28.2	30.0					

^{*}Must be used in conjunction with a list of moment based tile systems endorsed by the Broward County Board of Rules and Appeals.

For Uplift based tile systems use Method 3. Compared the values for F' with the values for F_r . If the F' values are greater than or equal to the F_r values, for each area of the roof, then the tile attachment method is acceptable.

Method 3 "Uplift Based Tile Calculations Per RAS 127"

(Zone 1:	x L	_ =	_ x w: =) – W:	_ x cos r	= F _{r1}	Product Approval F'
(Zone 2e:	x L	=_	x w: = _) – W:	x cos r	= F _{r2e}	Product Approval F'
(Zone 2n:	x L	=_	x w: = _) – W:	x cos r _	= F _{r2n}	Product Approval F'
(Zone 2r:	x L	=	x w: =) – W:	x cos r	= F _{r2r}	Product Approval F'
(Zone 3e:	x L	=_	x w: = _) – W:	x cos r _	= F _{r3e}	Product Approval F'
(Zone 3r:	x L	=	x w: =) – W:	x cos r	= <mark>F_{r3r}</mark>	Product Approval F'