## TABLE 1017.2 EXIT ACCESS TRAVEL DISTANCE

| OCCUPANCY               | WITHOUTSPRINKLERSYSTEM(feet) | WITHSPRINKLERSYSTEM(feet) |
|-------------------------|------------------------------|---------------------------|
| A,E,F-1,M,R, <u>S-1</u> | 200                          | 250b                      |
| I-1                     | NotPermitted                 | 250b                      |
| В                       | 200                          | 300c                      |
| F-2,S-2,U               | 300                          | 400c                      |
| H-1                     | NotPermitted                 | 75d                       |
| H-2                     | NotPermitted                 | 100d                      |
| H-3                     | NotPermitted                 | 150d                      |
| H-4                     | NotPermitted                 | 175d                      |
| H-5                     | NotPermitted                 | 200c                      |
| I-2,I-3,I-4             | NotPermitted <u>e</u>        | 200c                      |
| S-1                     | 200                          | 4 <del>00</del> b         |

For SI: 1 foot = 304.8 mm.

See the following sections for modifications to exit access travel distance requirements:

Section 402.8: For the distance limitation in malls.

Section 404.9: For the distance limitation through an atrium space.

Section 407.4: For the distance limitation in Group I-2.

Sections 408.6.1 and 408.8.1: For the distance limitations in Group I-3.

Section 411.4: For the distance limitation in special amusement buildings.

Section 412.7: For the distance limitations in aircraft manufacturing facilities.

Section 1006.2.2.2: For the distance limitation in refrigeration machinery rooms.

Section 1006.2.2.3: For the distance limitation in refrigerated rooms and spaces.

Section 1006.3.3: For buildings with one exit.

Section 1017.2.2: For increased distance limitation in Groups F-1 and S-1.

Section 1029.7: For increased limitation in assembly seating.

Section 3103.4: For temporary structures.

Section 3104.9: For pedestrian walkways.

Buildings equipped throughout with an *automatic sprinkler system* in accordance with Section 903.3.1.1 or 903.3.1.2. See Section 903 for occupancies where *automatic sprinkler systems* are permitted in accordance with Section 903.3.1.2.

Buildings equipped throughout with an automatic sprinkler system in accordance with Section 903.3.1.1.

Group H occupancies equipped throughout with an automatic sprinkler system in accordance with Section 903.2.5.1.

Group I-4 day care facilities for which an automatic sprinkler system is not required in accordance with Section 903.2.6, exception 2.