



Access Lifts Florida Inc.
3040 N 29th Ave, Suite 3
Hollywood, FL 33020
Phone: (954) 826-5438
Email: info@accessliftsfl.com
Website: www.accessliftsfl.com

Prepared by: Jim Jeschonek
Jim.jeschonek@gmail.com
(561-602-7506)
Date: 2/18/2025

PROPOSAL Vertical Platform Lift

Project Reference: Grow Healthy Dispensary Tequesta, 19510 us 1 Tequesta Florida 33469

Prepared for: Dillion Peel: OWL SERVICES: dillion.peel@owlservices.com 561-947-0866

Product: Symmetry SLH-120 Shaft way Lift Indoor Same Side openings

SCOPE: This proposal is intended to cover the complete furnishing of a Symmetry Vertical Platform Lift and installation of equipment by Access Lifts Inc. Two pre-site visits will be conducted one at to check and verify work specified by construction drawing provided to the general contractor. Contract and shop drawings must precede site visits. All work shall be performed in a workmanlike manner and shall include all work and material in accordance with the following as specified herein:

Package Type: Cibes/ Symmetry VPL SLH-120 Same Side Indoor

Stops: 2

Drive: Hydraulic

Door location: Same Side

Platform Size: 36"x54"

Rated Capacity/ Speed: 750Lbs / 17FPM

Shaftway Model: Shaft to be provided by others required shaft Shaft Size 53.25 wide x55.25" deep

Color: Powder coated Ivory Textured

Travel: 96" – to be field verified travel not to exceed 123"

PIT: 3" to avoid ramping

Doors/Gates: Lower and Upper 6'8" Fire Doors and Frames Primed with Auto Openers,

Additional included options: Platform emergency Lighting, ADA Phone and manual lowering device, stand by power package, and, AUDIBLE ALARM IS INCLUDED, ,emergency platform lowering

WORK BY OTHERS (TO BE SUPPLIED BY OTHERS):

- Dedicated 120 VAC LOCKABLE, FUSED DISCONNECT SWITCH MOUNTED WITHIN SIGHT OF LIFT PER NEC (SEE NFPA 70 SECTION 620.51) Location of disconnect TBD by Access Lifts Inc.
- Phone Line: Standard dedicated analog phone line/ 24/7 monitoring
- Attachment point brackets or support wall for tower and Lower and Upper landing gate
- 5FTC Lighting
- All finish work, electrical, cutouts is by others
- Concrete Pad /shaft work by others
- Support wall or blocking for Lift and Upper gate support by others.
- All cutouts and weather sealing into building for the Doors are by others.



ACCEPTANCE OF INSTALLATION: Delivery and installation of the Symmetry Wheel Chair Lift indoor is by Access Lifts Florida Inc. All other work, including but not limited to the hoist way, support wall construction, pit requirement, and power supply to the unit is not the responsibility of Access Lifts Inc. (permit or approval from local building authority is by owner). **All Engineering stamps, local building permits/inspections, additional drawings, custom details, calculations, x-ray or scanning for post tension, slab/concrete testing, special circumstances, or any associated fees are not included in this proposal and will incur extra charges if required (unless listed as provided in proposal)**

NOTE: ALL CUT OUTS ALL FINISH WORK WILL BE BY OTHERS ALL ELECTRICAL WORK WILL BE BY OTHERS

ACCEPTANCE OF PROPOSAL: The contract price, terms, specifications, and conditions are satisfactory and are hereby accepted. Access Lifts Inc. a Cibes Company is authorized to proceed with provision of the equipment specified. I understand this order is subject to cancellation charges under the following schedule: 25% if cancelled prior to engineering work, 50% after engineering is complete, 70% if in production, and 100% if production is completed. All orders are subject to credit approval. We reserve the right to discontinue our work at any time until payments have been made as agreed and we have assurance satisfactory to us that the subsequent payments will be made as they become due. A monthly service charge of 1 ½ % will be due on all amounts not paid within 30 days. You also agree to pay, in addition to any defaulted amount plus service charges, all attorneys' fees, collection costs, or court costs in connection therewith.

WARRANTY: Manufactures warranty 4-year limited parts warranty on the basic unit, including all electrical and drive components.. **We provide a One Year labor warranty that runs from the date of completion of the work. Any work required will be completed during normal working hours and days. No overtime work is included. Warranties provided by us on the manufacture do not cover any parts or labor required as a result of misuse or vandalism or any other work performed by anyone other than Access Lifts Inc. personnel. Access lifts Inc. will not under this warranty reimburse purchaser or the owner for the cost of work done by others.**

This warranty is in lieu of any other liability for defects. Access Lifts Inc. makes no warranty of merchantability and no warranties which extend beyond the description in this agreement, nor are there any other warranties, express or implied, by operation of law or otherwise.

Site Checks: Any additional site checks other than the two (2) site checks included in this proposal will be billed at \$225.00/hr.



PRICE ESCALATION:

This proposal is submitted for acceptance and valid for **30** days from the date submitted by us. Once executed, the pricing is valid for **6** months from date of signature. If site is not available for installation before this time, Access Lifts Florida Inc. reserves the right to adjust pricing in accordance with manufacturing cost increases and Consumer Price Index (CPI).

This proposal, for a Symmetry Vertical Platform Lift, prepared for the property referenced above, when signed and accepted by the Purchaser and approved by a Representative of Access Lifts Inc shall constitute exclusively and entirely the contract between parties, and all prior representations or agreements, whether written or verbal, not incorporated herein, are superseded. No changes in or additions to this agreement will be recognized unless made in writing and properly executed by both parties.

Includes Elevator Permit/Inspection,

TOTAL PURCHASE PRICE: \$42,122.00 (without additional options)

Payment Schedule:

40% at Signature of Contract, to issue Symmetry shop drawings

50% Prior to Equipment Release

10% at Completion

Due Date	Payment %	\$ Amount	\$ Remaining
Deposit required	40%	\$ 16,848.80	\$ 25,273.20
To release to Production	50%	\$ 21,061.00	\$ 4,212.20
Upon Completion	10%	\$ 4,212.20	\$ -

<p>Customer:</p> <p>By: _____ (Signature of Authorized Representative)</p> <p>_____</p> <p>(Printed or Typed Name)</p> <p>Date: _____</p>	<p>Access Lifts Manager Approval:</p> <p>By: _____</p> <p>Rafael Soares</p> <p>Title: Managing Director</p> <p>Date: _____</p>
--	---

ESTIMATED LEAD TIMES (SUBJECT TO CHANGE)

- 1. Drawings: 7-10 work days from signed contract and deposit payment received**
- 2. Manufacturing: 8-12 weeks once drawings approved and release payment is received(EWP Unit 16-22 Weeks)**
- 3. Installation: 3-5 work days after delivery to job site**
- 4. Inspection: 1 day**
- 5. Turnover: same day as final payment received**



ATTACHMENT "A"
VERTICAL PLATFORM LIFT
NEW INSTALLATION & EXISTING BUILDING
WORK NOT INCLUDED

This proposal does not include the following work and is conditioned on the proper performance of such work by the General Contractor or other Subcontractors.

A legal hoistway, when applicable, properly framed and enclosed, and including a proper depth pit when required. Adequate supports and foundation to carry the loads of all equipment as specified. The hoistway shaft and enclosure are to be constructed and furnished to enclose the lift in accordance with local building codes. The shaft/enclosure shall allow for a uniform and level pit below the finished floor level of the bottom landing and an adequate overhead space above the floor at the top landing. Pit depth and overhead to be as required by manufacturer. If doors are of construction grade (non-enclosure type doors) doorjambes are to be rabbited for sheetrock. No casings are to be furnished inside the shaft. Shaft doors are to be solid core. If thresholds are furnished across the door openings, their width should be extended from door to edge of shaft.

Placement of the Lift in the Shaft: One full opening of the hoistway shaft is to be left open at the lowest level in order to allow Access Lifts Inc. to install the platform lift, unless otherwise agreed upon in writing. Provision is to be made to enable Access lifts Inc. to maneuver the platform lift to the designated location. All protection of finished surfaces surrounding the hoistway including ingress path is the responsibility of the owner/contractor during installation. Completion of Contractor related work must occur at the appropriate time during the lift installation.

It is agreed in the event asbestos material is knowingly or unknowingly removed or disturbed in any manner at the job site, you will monitor our work place and prior to and during our manning of the job, you will certify that asbestos in the environment does not exceed .01 fibers per cc as tested by NIOSH 7400. In the event our employees or those of our subcontractors are exposed to an asbestos hazard, PCP's or other hazardous substances, you agree to indemnify, defend, and hold us harmless from all damages, claims, suits, expenses, and payments resulting from such exposure. Removal and disposal of asbestos containing material is the responsibility of the contractor.

Provide OSHA compliant removable temporary enclosures or other protection (barricades and kickboards) from open hoistways during the time the lift is being installed. Proper placement of conduit, cutting and patching of walls, floors, etc., and removal of such obstruction as may be necessary for proper installation of the lift. Pockets or blockouts for landing controls.

Suitable connections from the power main to the controller/J-Box as required, including necessary circuit breakers and fused mainline disconnect switches per drawings and N.E.C. (Per N.E.C. articles 620-22 and 620-51.) Electric power without charge, for construction, testing and adjusting of the same characteristics as the permanent supply. Owner/General Contractor to provide a bonded ground wire, properly sized, from the elevator controller(s) to the primary building ground.

Any governmentally required safety provisions not directly involved for lift installation.

Furnishing, installing and maintaining the required fire rating of hoistway walls, including the penetration of fire well by lift fixture boxes, is not the responsibility of the elevator contractor.

All painting, except as otherwise specified.

Composite cleanup crews will not be provided. Elevator contractor will be responsible for own housekeeping. General Contractor to provide adequate refuse receptacle.

Costs for additional inspections of the lift equipment by code authorities after the initial one fails due to items that are the responsibility of the contractor or for assisting others inspection equipment installed by others.

Owners/General Contractor agrees to provide a dry and secure area adjacent to the hoistway(s) at ground level for storage of the lift equipment at the time of delivery will be at contractor's expense.

Should unusual conditions be encountered during installation, contractor will be notified immediately and written authorization to proceed shall be obtained by Subcontractor. The contract price shall be increased by the amount of additional labor at Subcontractor's usual billing rates, and the actual cost of any additional material plus 15%.