



# AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report(s). This authorization also applies to the Multiple Listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The Certification Mark(s) may be applied only at the location of the Party Authorized to Apply Mark.

**Applicant:** Ceco Door Products (Milan)  
 9159 Telecom Drive  
 Milan, TN 38358

**Country:**

**Contact:** Dwayne Charlton

**Phone:** 731-686-4282

**Fax:** 731-723-1310

**Email:** dcharlton@cecodoor.com

**Party Authorized to Apply Mark:** See following page(s)

**Evaluation Center:** Intertek (Middleton)

**Control/Client Number:** 242757

Authorized By:   
 Dean Davidson, Director of Certification

Intertek Testing Services NA, Inc.  
 545 E. Algonquin Road, Ste H., Arlington Heights, IL 60005 USA  
 Phone: 847-439-5667 Fax: 847-439-7320



**Intertek**

This document supersedes all previous Authorizations to Mark for the noted Report Number.



This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

<b>Testing Standard(s):</b>	ASTM E330 (2002), ASTM E331 (2000), ASTM E1886 (2002), ASTM E1996 (2003), ANSI A250.13 (2003), TAS 203, ASTM E330 (2014), ASTM E1996 (R2014), ASTM E1886 (R2013), ANSI A250.13 (R2014), ASTM E331 (2016), TAS 201, TAS 202, ASTM E1886 (2005), ANSI A250.13 (2005), ASTM E1996 (2008), ASTM E331 (2009),
<b>Product:</b>	Ceco Volume IA Windstorm Doors - Manufacturing

**ATM for Report:** 3118505, 3126983, 3132419-001, 3159480, 3159865, 3163505, 3190362MID-002, Letter Report 100407338, 100407338MID-003, Letter Report 100545411, 100545411MID-003, Letter Report 100859994, 100859994MID-003, Letter Report 101343015MID-001, 101274930MID-

**ATM Issue Date:** 09/07/2017



003, 101274930MID-004, 102016058MID-001, 102349537MID-001,  
102750916MID-003, 103009100MID-001

AUTHORIZATION STAMP  Intertek JA 2/10/14	 <b>ASSA ABLOY</b>	VOLUME: 1
		SECTION: 7
	MANUFACTURING LOCATIONS	PAGE: 2

**WARNOCK HERSEY FOLLOW-UP SERVICE PROCEDURE**

**WINDSTORM CLASSIFICATION MATRICES**

Stiffness Class I					Impact 350 ft-lbs		
Door Type	Configuration	Max. Size	Min. Gauge	*Max. Design Load (psf)	Min. Latch Throw (in)	Lock Side - Min. Latch Strength (lbf)	Hardware Type
Medallion Legion Ultra Regent Omega Fuego	Inswing/ Outswing	30 x 70 Single	18	+/- 60	1/2" cylindrical 3/4" mortise	630	Cylindrical Lock, Mortise Lock (Deadbolt not required)
Medallion Legion Ultra Regent Omega Fuego	Inswing/ Outswing	30 x 70 Single	18	+/- 70	1/2" cylindrical, 1" deadlock 3/4" mortise, 1" deadbolt 1/2" act latch, 1" deadbolt (ICL)	735	Cylindrical Lock x Deadlock, Mortise Lock w/deadbolt, Interconnected lock
Medallion Legion Ultra Regent Omega	Outswing	30 x 80 Single	18	+/- 60	3/4" mortise, 1" deadbolt n/a rim/vertical rod exit	720	Mortise Lock w/deadbolt, Rim Exit, Vertical Rod Exit
Medallion Legion Ultra Regent Omega Fuego	Outswing	30 x 70 Single	18	+/- 60	1/2" cylindrical 3/4" mortise n/a mortise/rim/vertical rod exit	630	Cylindrical Lock, Mortise Lock (Deadbolt not required), Mortise Exit, Rim Exit, Vertical Rod Exit
Medallion Legion Ultra Regent Omega Fuego	Outswing	40 x 80 Single	16	+/- 70	3/4" mortise, 1" deadbolt n/a rim/vertical rod exit	1120	Mortise Lock w/deadbolt, Rim Exit, Vertical Rod Exit
Medallion	Outswing	80 x 80 Pair	16	+/- 70	3/4" mortise, 1" deadbolt / 1 1/4" surface bolt n/a rim exit	1120	Mortise Lock w/deadbolt (active) / Surface Bolts (inactive), Rim Exit x Mullion
Legion Ultra Regent Omega Fuego	Outswing	80 x 80 Pair	16	+/- 70	3/4" mortise, 1" deadbolt / 1 1/4" surface bolt	1120	Mortise Lock w/deadbolt (active) / Surface Bolts (inactive)




AUTHORIZATION STAMP  Intertek JAA 2/10/14	 <b>Ceco Door</b> <hr/> <b>ASSA ABLOY</b>	VOLUME: 1
		SECTION: 7
	MANUFACTURING LOCATIONS	PAGE: 3

WARNOCK HERSEY FOLLOW-UP SERVICE PROCEDURE

WINDSTORM CLASSIFICATION MATRICES

Stiffness Class I							Impact 350 ft-lbs
Door Type	Configuration	Max. Size	Min. Gauge	*Max. Design Load (psf)	Min. Latch Throw (in)	Lock Side - Min. Latch Strength (lbf)	Hardware Type
Trio Trio-E	Inswing/ Outswing	30x70 Single	18	±100	1/2" cylindrical 3/4" mortise lock	1050	Cylindrical Lock, Mortise Lock w/ Deadbolt function
Trio Trio-E	Outswing	30x70 Single	18	±100	3/4" rim exit	1050	Rim Exit
Trio Trio-E	Inswing/ Outswing	60x70 Pair	18	±70	1/2" cylindrical 1" deadlock 3/4" mortise lock	735	Cylindrical x Deadlock, Mortise Lock w/ Deadbolt function (active), Flush Bolt or Surface Bolt(In- Active)
Trio Trio-E	Inswing/ Outswing	40x80 Single	18	±70	1/2" cylindrical 3/4" mortise lock	1120	Cylindrical Lock, Mortise Lock w/ Deadbolt function
Trio Trio-E	Outswing	40x80 Single	18	±70	3/4" rim exit	1120	Rim Exit
Trio Trio-E	Outswing	80x80 Pair	18	±70	3/4" rim exit x 3/4" rim exit 3/4" Vertical Rod Exit x 3/4" Vertical Rod Exit	1120	Rim Exit x Hardware Mullion Vertical Rod Exit x Vertical Rod Exit
Trio Trio-E	Inswing/ Outswing	80x80 Pair	18	±70	1/2" cylindrical 1" deadlock 3/4" mortise lock	1120	Cylindrical Lock x Deadlock, Mortise Lock w/ Deadbolt function, (Active) Flush Bolt or Surface Bolt(In- Active)



AUTHORIZATION STAMP  Intertek <i>RW</i> <i>11-10-2016</i>	 	VOLUME: 1
		SECTION: 7
	MANUFACTURING LOCATIONS	PAGE: 4

**WARNOCK HERSEY FOLLOW-UP SERVICE PROCEDURE**

**WINDSTORM CLASSIFICATION MATRICES (cont.)**

<b>Stiffness Class II</b>						<b>Impact 350 ft-lbs</b>	
<b>Door Type</b>	<b>Configuration</b>	<b>Max. Size</b>	<b>Min. Gauge</b>	<b>*Max. Design Load (psf)</b>	<b>Min. Latch Throw (in)</b>	<b>Lock Side - Min. Latch Strength (lbf)</b>	<b>Hardware Type</b>
Imperial Versadoor Mercury	Inswing/ Outswing	30 x 70 Single	18	+/- 70	1/2" cylindrical, 1" deadlock 3/4" mortise, 1" deadbolt 1/2" act latch, 1" deadbolt (ICL)	735	Cylindrical Lock x Deadlock, Mortise Lock w/deadbolt, Interconnected lock
Imperial Versadoor Mercury	Outswing	30 x 70 Single	18	+/- 60	1/2" cylindrical 3/4" mortise n/a mortise/rim/vertical rod exit	630	Cylindrical Lock, Mortise Lock (Deadbolt not required), Mortise Exit, Rim Exit, Vertical Rod Exit

\*Glass lights may limit design loads. See details to follow for additional information.