## NAMI NOTICE OF PRODUCT LINE CERTIFICATION



Certification No.: NI009861-R5 Page 1

Date: 04/14/2009

Revision Date: 01/20/2020

Certification Program: Structural

Company: <u>Jeld-Wen</u>
Code: <u>1822-1</u>

The "Notice of Product Line Certification" is valid only when Administrator's Seal is applied to the upper left hand portion of this form and a certification label is applied to the product. This certification seal represents product conformity to the applicable specification and that all certification criteria have been satisfied.

The products and systems listed below are approved for listing in the Directory of Certified Products at <a href="https://www.NAMICertification.com">www.NAMICertification.com</a>. Please review, and advise NAMI immediately if data, as shown requires corrections.

**Company: Jeld-Wen Exterior Doors** 

3737 Lakeport Boulevard Klamath Falls, OR 97601

Product Line: Jeld-Wen Gladiator/Finishield Glazed Wood-Edge Steel Double

**Doors with Glazed Fixed Side-Lites** 

Test Report: NCTL-210-3558-1 & NCTL-210-3558-1A

Section 1: General Description of the Products and Systems under this

Certification

1.1 Frame: The frame jambs consist of wood with all corners coped and butted. The head/jamb corners were fastened with three (4) 16 ga 7/16" crown x 2" long staples per corner. The threshold was attached to the side jambs with three (3) 16 ga 1/4" crown x 2" long wire staples at each end.

- **1.2 Door Panel/Sidelite Construction:** Each door panel was constructed from two (2) face sheets of 25 gauge (0.018" minimum) galvanized steel and an internal expanded polystyrene foam core.
- **1.3 Sidelite Glazing:** The overall insulated glass unit was comprised of two (2) 1/8" sheets of clear tempered glass.

Certification No.: NI009861-R5 Page 2

## **Section 2: Registered Suppliers**

2.1 Door Lites: ODL2.2 Astragal: Global

2.3 Sills: Endura, AFCO

See additional Pages of Certification for Certified Product Line Matrix(s) and Installation Details. If you have any questions regarding this certification, please contact NAMI at (804) 684-5124.

## **NOTICE OF PRODUCT CERTIFICATION**



Company: Jeld-Wen Exterior Doors Certification No.: NI009861-R5 Page 3

3737 Lakeport Boulevard Certification Date: 04/14/2009
Klamath Falls, OR 97601 Expiration Date: 10/31/2028
Revision Date: 01/20/2020

Product: Series "Gladiator/Finishield" Glazed Wood Edge Steel Doors w/ or w/o Side-Lites

(w/Wood Frame unless noted)

Specification: TAS 202-94/ASTM E283-04/E330-02/E331-00

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at <a href="https://www.Namicertification.com">www.Namicertification.com</a>. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or	Glazed or	Maximum	Design Pressure	Missile Impact	Test Report Number Drawing Number &
	Outswing	Opaque	Size	Pos/Neg	Rated	Comments
X Single	I/S or O/S	Glazed	3'2" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A  Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3"  w/o Surface Bolts  Installation Details: JW122008(1-14)/JW192008(1-14)
X Single	I/S or O/S	Glazed	3'2" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A  Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3"  w/Surface Bolts  Installation Details: JW122008(1-14)/JW192008(1-14)
OX/XO Single w/Sidelite	I/S or O/S	Glazed	6'3" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A  Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3"  w/o Surface Bolts  Installation Details: JW122008(1-14)/JW192008(1-14)
OX/XO Single w/Sidelite	I/S or O/S	Glazed	6'3" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A  Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3"  w/Surface Bolts  Installation Details: JW122008(1-14)/JW192008(1-14)
XX Double	I/S or O/S	Glazed	6'2" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A  Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3"  w/o Surface Bolts  Installation Details: JW122008(1-14)/JW192008(1-14)
XX Double	I/S or O/S	Glazed	6'2" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A  Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3"  w/Surface Bolts  Installation Details: JW122008(1-14)/JW192008(1-14)

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072 Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE:

## **NOTICE OF PRODUCT CERTIFICATION**



Company: Jeld-Wen Exterior Doors Certification No.:

3737 Lakeport Boulevard Certification Date: 04/14/2009 Klamath Falls, OR 97601 Expiration Date: 10/31/2028 Revision Date: 01/20/2020

NI009861-R5 Page 4

Product: Series "Gladiator/Finishield" Glazed Wood Edge Steel Doors w/ or w/o Side-Lites

(w/Wood Frame unless noted)

Specification: TAS 202-94/ASTM E283-04/E330-02/E331-00

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at <a href="https://www.Namicertification.com">www.Namicertification.com</a>. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing	Glazed		Design	Missile	Test Report Number
	or	or	Maximum	Pressure	Impact	Drawing Number &
	Outswing	Opaque	Size	Pos/Neg	Rated	Comments
OXX/XXO Double w/Sidelite	I/S or O/S	Glazed	9'3" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXX/XXO Double w/Sidelite	I/S or O/S	Glazed	9'3" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXO Single w/Sidelites	I/S or O/S	Glazed	9'4" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXO Single w/Sidelites	I/S or O/S	Glazed	9'4" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXXO Double w/Sidelites	I/S or O/S	Glazed	12'5" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXXO Double w/Sidelites	I/S or O/S	Glazed	12'5" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072 Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: \_\_\_\_\_