## NAMI NOTICE OF PRODUCT LINE CERTIFICATION



Certification No.: NI009861-R6 Page 1

Date: <u>04/14/2009</u>

**Revision Date: 05/09/2022** 

Certification Program: Structural\_\_\_\_

Company: <u>Jeld-Wen</u> Code: 1822-1

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

**Company: Jeld-Wen Exterior Doors** 

3737 Lakeport Boulevard Klamath Falls, OR 97601

Product Line: Jeld-Wen Gladiator/Finishield Glazed Wood-Edge Steel Double

**Doors with Glazed Fixed Side-Lites** 

Test Report: NCTL-210-3558-1 & NCTL-210-3558-1A

Section 1: General Description of the Products and Systems under this

Certification

- 1.1 Frame: The frame jambs consist of wood with all corners coped and butted. The head/jamb corners were fastened with three (4) 16 ga 7/16" crown x 2" long staples per corner. The threshold was attached to the side jambs with three (3) 16 ga 1/4" crown x 2" long wire staples at each end.
- **1.2 Door Panel/Sidelite Construction:** Each door panel was constructed from two (2) face sheets of 25 gauge (0.018" minimum) galvanized steel and an internal expanded polystyrene foam core.
- **Sidelite Glazing:** The overall insulated glass unit was comprised of two (2) 1/8" sheets of clear tempered glass.

Certification No.: NI009861-R6 Page 2

## **Section 2: Registered Suppliers**

2.1 Door Lites: ODL2.2 Astragal: Global

2.3 Sills: Endura, AFCO

See additional Pages of Certification for Certified Product Line Matrix(s) and Installation Details. If you have any questions regarding this certification, please contact NAMI at (804) 684-5124.

## **NOTICE OF PRODUCT CERTIFICATION**



Company: Jeld-Wen Exterior Doors

3737 Lakeport Boulevard Certification Date: 04/14/2009 Klamath Falls, OR 97601 Expiration Date: 10/31/2028 Revision Date: 05/09/2022

**Certification No.:** 

NI009861-R6 Page 3

Product: Series "Gladiator/Finishield" Glazed Wood Edge Steel Doors w/ or w/o Side-Lites

(w/Wood Frame unless noted)

Specification: TAS 202-94/ASTM E283-04/E330-02/E331-00

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or	Glazed or	Maximum	Design Pressure	Missile Impact	Test Report Number Drawing Number &
	Outswing	Opaque	Size	Pos/Neg	Rated	Comments
X Single	I/S or O/S	Glazed	3'2" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
X Single	I/S or O/S	Glazed	3'2" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OX/XO Single w/Sidelite	I/S or O/S	Glazed	6'3" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OX/XO Single w/Sidelite	I/S or O/S	Glazed	6'3" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
XX Double	I/S or O/S	Glazed	6'2" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
XX Double	I/S or O/S	Glazed	6'2" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072 Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE:

## **NOTICE OF PRODUCT CERTIFICATION**



Company: Jeld-Wen Exterior Doors

3737 Lakeport Boulevard Klamath Falls, OR 97601 Certification No.: NI009861-R6 Page 4

Certification Date: 04/14/2009 Expiration Date: 10/31/2028 Revision Date: 05/09/2022

Product: Series "Gladiator/Finishield" Glazed Wood Edge Steel Doors w/ or w/o Side-Lites

(w/Wood Frame unless noted)

Specification: TAS 202-94/ASTM E283-04/E330-02/E331-00

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit <a href="www.namicertification.com">www.namicertification.com</a>. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

	Inswing	Glazed	(AIVAD) and the Sta	Design	Missile	Test Report Number
Configuration	or	or	Maximum	Pressure	Impact	Drawing Number &
	Outswing	Opaque	Size	Pos/Neg	Rated	Comments
OXX/XXO Double w/Sidelite	I/S or O/S	Glazed	9'3" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXX/XXO Double w/Sidelite	I/S or O/S	Glazed	9'3" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A/W-2025  Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts  Installation Details: JW122008(1-14)/JW192008(1-14)
OXO Single w/Sidelites	I/S or O/S	Glazed	9'4" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXO Single w/Sidelites	I/S or O/S	Glazed	9'4" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXXO Double w/Sidelites	I/S or O/S	Glazed	12'5" x 6'10"	+45/-45	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/o Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)
OXXO Double w/Sidelites	I/S or O/S	Glazed	12'5" x 6'10"	+55/-55	No	NCTL-210-3558-1/210-3558-1A/W-2025 Max Panel Size: 3'0" x 6'7"Daylight Opening: 1'9" x 5'3" w/Surface Bolts Installation Details: JW122008(1-14)/JW192008(1-14)

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072 Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: \_\_\_\_\_