



LISTING INFORMATION OF

**Curries Type 2 and 3: And Curries Type 8 Vision Light Kit 70
psf**

SPEC ID: 19091

Curries Company
1502 12th Street NW
PO Box 1648
Mason City, IA 50401
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

| Model# | Glass Type | Glazing Method | Door Stiffness Class | Frame Type | Frame Material | Max Size (in) | | Ratings D.L | |
|------------------|-------------------------------|---|----------------------|------------------------------|----------------|---------------|----|----------------|--------------|
| | | | | | | W | H | Structural PSF | Impact ft-lb |
| Curries Type 2,3 | 0.472" Glasslam Safety Plus 2 | Mechanically captured with glazing tape and Structural silicone | 1 | Integral with removable stop | Steel | 24 | 42 | 70 | 350 |
| Curries Type 8 | See Table below | Mechanically captured with glazing tape and Structural silicone | 1 | integral with removable stop | Steel | 23 | 53 | 70 | 350 |

D. L. = Maximum design load. NR = Not Rated

| Glass Options for Curries Type 8 | Total Glass Assembly Thickness | Interlayer Material |
|----------------------------------|--------------------------------|--------------------------|
| Keralite Ultra 90HI | 1- 1/2" | 0.090" PVB or 0.090" SGP |
| Swissflam 45 HI | 1-3/8" | 0.090" PVB or 0.090" SGP |

| Product | Product Approval No. |
|---|----------------------|
| Curries 70 psf Vision Light Kits/Curries Store Front Frames | FL # 12537 |

| Attribute | Value |
|-----------------|---------------------------------|
| Criteria | ASTM E330 (2002) |
| Criteria | ASTM E1886 (2002) |
| Criteria | ASTM E1996 (2003) |
| Criteria | ANSI A250.13 (2003) |
| Criteria | TAS 203 |
| Criteria | TAS 201 |
| Criteria | TAS 202 |
| CSI Code | 08 11 00 Metal Doors and Frames |
| DP Rating (psf) | 70 |

| | |
|------------------------------------|--------------------|
| Hurricane Impact Load Rating ft-lb | 350 |
| Impact Missile Level | Level D |
| Intertek Services | Certification |
| Listed or Inspected | LISTED |
| Listing Section | WINDSTORM - FRAMES |
| Report Number | 3060066; 3085345 |
| Spec ID | 19091 |
| Stiffness Class | I |
| Swing | In swing |
| Swing | Out swing |
| Verification Testing | No |