



LISTING INFORMATION OF
Curries Storefront Frames (Windstorm) 70 psf
SPEC ID: 19088

Curries Company
1502 12th Street NW
PO Box 1648
Mason City, IA 50401
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

Product Covered:

Curries Storefront Frames (Windstorm) 70 psf

Product Description:

16 gauge Steel Frame with reinforcements and Welded Corner construction. Allowed in masonry, Steel Stud and wood Stud Walls.

Model	Configuration	Max. Width (in)	Max. Height (in)
Hollow Metal	Single Out-swing Door with Sidelight	36"	96"
Hollow Metal	Single In-Swing Door with Sidelights	36"	84"
Hollow Metal	Pair of Out-swing Doors with Sidelight	72"	96"
Hollow Metal	Window Frame	36"	96"
Transoms	Transoms	72"	30"

Widths listed above are of individual door and window units. Sidelights may be mulled to frames of door units to increase the storefront opening width. Multiple Window frames may be mulled together to increase storefront opening width.

Limitation: Air Infiltration and Water Penetration Testing are in reference to the Fixed Glass Only.

FLORIDA PRODUCT APPROVAL

EVALUATION METHOD	BUILDING CODE	FL NO.
Certification Agency	2017	12537.2

Attribute	Value
Criteria	ASTM E330 (2002)
Criteria	ASTM E1886 (2002)
Criteria	ANSI A250.13 (2003)
Criteria	ASTM E1996 (2002)
Criteria	TAS 203
Criteria	TAS 201
Criteria	TAS 202 - Structural
Criteria	TAS 202 - Water Penetration

Criteria	TAS 202 - Air Infiltration
CSI Code	08 11 00 Metal Doors and Frames
DP Rating (psf)	70
Hurricane Impact Load Rating ft-lb	350
Impact Missile Level	Level D
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	WINDSTORM - FRAMES
Report Number	3144406Mid-006b
Spec ID	19088
Swing	Out swing
Verification Testing	No