

NOTICE OF PRODUCT CERTIFICATION



Company: JELD-WEN Doors
3737 Lakeport Boulevard
Klamath Falls, OR 97601

Certification No.: NI011096-R3
Certification Date: 05/07/2012
Expiration Date: 08/31/2027
Revision Date: 05/13/2019

Product: “Energy Saver/Contour” Opaque Wood-Edge Steel Door w/ or w/o Sidelites (wood frame)

Specification: TAS 201/202/203-94

The “Notice of Product Certification” is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI’s Certified Product Listing at www.Namicertification.com. NAMI’s Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	O/S	Opaque	3’2” x 8’2”	+50/-60	7.5 psf	Yes	CTLA 696WA/CTLA 961W/W-1897 Max Panel Size: 3’0” x 8’0” w/Bump Face Threshold Installation Details: S-2108-01 (1-8)
X Single	O/S	Opaque	3’2” x 8’2”	+60/-60	10.0 psf	Yes	CTLA 696WA/CTLA 961W/W-1897 Max Panel Size: 3’0” x 8’0” w/High Dam Threshold Installation Details: S-2108-01 (1-8)
OX/XO Single w/Sidelite	O/S	Door-Opaque Sidelite-Glazed	4’5” x 8’2”	+50/-60	7.5 psf	Door-Yes Sidelite-No	CTLA 696WA/CTLA 961W/W-1897 Max Panel Size: 3’0” x 8’0”w/Bump Face Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OX/XO Single w/Sidelite	O/S	Door-Opaque Sidelite-Glazed	4’5” x 8’2”	+60/-60	10.0 psf	Door-Yes Sidelite-No	CTLA 696WA/CTLA 961W/W-1897 Max Panel Size: 3’0” x 8’0”w/High Dam Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OXO Single w/Sidelites	O/S	Door-Opaque Sidelites-Glazed	5’10” x 8’2”	+50/-60	7.5 psf	Door-Yes Sidelites-No	CTLA 696WA/CTLA 961W/W-1897 Max Panel Size: 3’0” x 8’0”w/Bump Face Threshold Sidelites DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OXO Single w/Sidelites	O/S	Door-Opaque Sidelites-Glazed	5’10” x 8’2”	+60/-60	10.0 psf	Door-Yes Sidelites-No	CTLA 696WA/CTLA 961W/W-1897 Max Panel Size: 3’0” x 8’0”w/High Dam Threshold Sidelites DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____ 

NOTICE OF PRODUCT CERTIFICATION



Company: JELD-WEN Doors
3737 Lakeport Boulevard
Klamath Falls, OR 97601

Certification No.: NI011096.01-R2
Certification Date: 05/07/2012
Expiration Date: 08/31/2027
Revision Date: 05/13/2019

Product: “Energy Saver/Contour” Opaque Wood-Edge Steel Door w/ or w/o Sidelites (wood frame)

Specification: TAS 201/202/203-94

The “Notice of Product Certification” is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI’s Certified Product Listing at www.Namicertification.com. NAMI’s Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
XX Double	O/S	Opaque	6’8” x 8’2”	+47/-43	7.5 psf 10.0 psf*	Yes	CTLA 696WA/CTLA 961W Max Panel Size: 3’0” x 8’0” w/Bump Face or High Dam Threshold Installation Details: S-2108-01 (1-8)
OXX/XXO Double w/Sidelite	O/S	Doors-Opaque Sidelites-Glazed	7’6” x 8’2”	+47/-43	7.5 psf 10.0 psf*	Doors-Yes Sidelite-No	CTLA 696WA/CTLA 961W Max Panel Size: 3’0” x 8’0” w/Bump Face or High Dam Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OXXO Double w/Sidelites	O/S	Doors-Opaque Sidelites-Glazed	8’11” x 8’2”	+47/-43	7.5 psf 10.0 psf*	Doors-Yes Sidelite-No	CTLA 696WA/CTLA 961W Max Panel Size: 3’0” x 8’0” w/Bump Face or High Dam Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)

*High Dam Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____