

NOTICE OF PRODUCT CERTIFICATION



Company: JELD-WEN Doors
 3737 Lakeport Boulevard
 Klamath Falls, OR 97601

Certification No.: NI011096.01-R3
Certification Date: 05/07/2012
Expiration Date: 08/31/2027
Revision Date: 05/09/2022

Product: “Energy Saver/Contour” Opaque Wood-Edge Steel Door w/ or w/o Sidelites (wood frame)

Specification: TAS 201/202/203-94

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namincertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
XX Double	O/S	Opaque	6’8” x 8’2”	+47/-43	7.5 psf 10.0 psf*	Yes	CTLA 696WA/CTLA 961W/W-2025 Max Panel Size: 3’0” x 8’0” w/Bump Face or High Dam Threshold Installation Details: S-2108-01 (1-8)
OXX/XXO Double w/Sidelite	O/S	Doors-Opaque Sidelites-Glazed	7’6” x 8’2”	+47/-43	7.5 psf 10.0 psf*	Doors-Yes Sidelite-No	CTLA 696WA/CTLA 961W/W-2025 Max Panel Size: 3’0” x 8’0” w/Bump Face or High Dam Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OXXO Double w/Sidelites	O/S	Doors-Opaque Sidelites-Glazed	8’11” x 8’2”	+47/-43	7.5 psf 10.0 psf*	Doors-Yes Sidelite-No	CTLA 696WA/CTLA 961W/W-2025 Max Panel Size: 3’0” x 8’0” w/Bump Face or High Dam Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)

*High Dam Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
 Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____

NOTICE OF PRODUCT CERTIFICATION



Company: JELD-WEN Doors
3737 Lakeport Boulevard
Klamath Falls, OR 97601

Certification No.: NI011096-R5
Certification Date: 05/07/2012
Expiration Date: 08/31/2027
Revision Date: 05/09/2022

Product: “Energy Saver/Contour” Opaque Wood-Edge Steel Door w/ or w/o Sidelites (wood frame)

Specification: TAS 201/202/203-94

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Design Pressure Pos/Neg	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	O/S	Opaque	3’2” x 8’2”	+50/-60	7.5 psf	Yes	CTLA 696WA/CTLA 961W/W-1897/W-1905/W-2025 Max Panel Size: 3’0” x 8’0” w/Bump Face Threshold Installation Details: S-2108-01 (1-8)
X Single	O/S	Opaque	3’2” x 8’2”	+60/-60	10.0 psf	Yes	CTLA 696WA/CTLA 961W/W-1897/W-1905/W-2025 Max Panel Size: 3’0” x 8’0” w/High Dam Threshold Installation Details: S-2108-01 (1-8)
OX/XO Single w/Sidelite	O/S	Door-Opaque Sidelite-Glazed	4’5” x 8’2”	+50/-60	7.5 psf	Door-Yes Sidelite-No	CTLA 696WA/CTLA 961W/W-1897/W-1905/W-2025 Max Panel Size: 3’0” x 8’0”w/Bump Face Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OX/XO Single w/Sidelite	O/S	Door-Opaque Sidelite-Glazed	4’5” x 8’2”	+60/-60	10.0 psf	Door-Yes Sidelite-No	CTLA 696WA/CTLA 961W/W-1897/W-1905/W-2025 Max Panel Size: 3’0” x 8’0”w/High Dam Threshold Sidelite DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OXO Single w/Sidelites	O/S	Door-Opaque Sidelites-Glazed	5’10” x 8’2”	+50/-60	7.5 psf	Door-Yes Sidelites-No	CTLA 696WA/CTLA 961W/W-1897/W-1905/W-2025 Max Panel Size: 3’0” x 8’0”w/Bump Face Threshold Sidelites DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)
OXO Single w/Sidelites	O/S	Door-Opaque Sidelites-Glazed	5’10” x 8’2”	+60/-60	10.0 psf	Door-Yes Sidelites-No	CTLA 696WA/CTLA 961W/W-1897/W-1905/W-2025 Max Panel Size: 3’0” x 8’0”w/High Dam Threshold Sidelites DLO: 7” x 6’7” (1/8” Tempered Glass) Installation Details: S-2108-01 (1-8)

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____