## NOTICE OF PRODUCT CERTIFICATION I



CERTIFICATION NO: NI011593.10-R4

**DATE:** <u>10/28/2013</u>

CERTIFICATION PROGRAM: Structural

COMPANY: ProVia Door
CODE: 1212-1

**REVISION DATE: 04/11/2022** 

To verify that the "Notice of Product Certification" is valid, please visit <a href="www.NAMICertification.com">www.NAMICertification.com</a> to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status.

Please review and advise NAMI if any corrections are required to this document.

| COMPANY NAME AND ADDRESS | PRODUCT DESCRIPTION   |
|--------------------------|---|
| ProVia LLC               | Steel Out-Swing Glazed Double   |
| 2150 State Route 39      | Side Hinged Doors w/Sidelites & Transom   |
| Sugarcreek, OH 44681     | Impact Rated  |
|                          | Configuration: O/OXXO Glazing: IG-Exterior-1/8" Tempered Glass/ Interior-Laminate-1/8" Annealed Glass/0.090" Solutia Interlayer/1/8" Annealed Glass or IG-Exterior-Laminate-1/8" Annealed Glass/0.090" Solutia Interlayer/1/8" Annealed Glass/Center-1/8" Tempered Glass/Interior-1/8" Tempered Glass/ IG-Exterior-1/8" Tempered Glass/Center-1/8" Tempered Glass/Laminate-1/8" Annealed Glass/0.090" Solutia Interlayer/1/8" Annealed Glass or IG-Exterior-1/8" Tempered Glass/Center-Decorative Inlay/Interior-Laminate-1/8" Annealed Glass/0.090" Solutia Interlayer/1/8" Annealed Glass or IG-Exterior-1/8" Tempered Glass/Center-Wrought Iron Decorative Inlay/Interior-Laminate-1/8" Annealed Glass/0.090" Solutia Interlayer/1/8" Annealed Glass/0.090" Solutia Interlayer/1/8" Annealed Glass |
|                          | Frame: W-3322mm(130.78") H-2999mm(118.09")  |
|                          | Panel: W-908mm(35.75") H-2411mm(94.93")   |
|                          | Sidelite: W-645mm(25.38") H-2479mm(97.6")   |
|                          | Transom: W-3322mm(130.78") H-406mm(16")   |

| SPECIFICATION                          | PRODUCT RATING                    |
|--|-----------------------------------|
| ASTM E283-04(12)/E330-02(10)           | Design Pressure: 2633 Pa (55 psf) |
| ASTM E1886-05/05/E1996-02/04/06/09/12a | Wind Zone 3-Missile Level D       |

Product Tested By: National Certified Testing Laboratories

Report No: NCTL-110-15660-1/NCTL-110-15660-2/NCTL-110-15650-2/NCTL-110-15650-4/NCTL-110-

15651-2/NCTL-110-15651-4/NCTL-110-15652-2/NCTL-110-15652-3/W-1636/W-2002/W-2024

Expiration Date: <u>December 31, 2024</u>

Administrator's Signature:

## NATIONAL ACCREDITATION & MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway Hayes, VA 23072 Tel: (804) 684-5124/nami@namiinc.com