

NOTICE OF PRODUCT CERTIFICATION



CERTIFICATION NO: NI012196.04-R2
DATE: 11/20/2014
CERTIFICATION PROGRAM: Structural
COMPANY: Eastern
CODE: 1783-1
REVISION DATE: 12/30/2014

To verify that the "Notice of Product Certification" is valid, please visit www.NAMICertification.com to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<p>Eastern Architectural Systems</p> <p>10030 Bavaria Road</p> <p>Ft. Myers, FL 33913</p>	<p>Series "176 SS"</p> <p>Vinyl Horizontal Sliding Window</p> <p>w/Fin or Flange Frame</p> <p>Configuration: XO Glazing: IG-Ext-3/16" Annealed Glass/Laminate-1/8" Annealed Glass/0.090" SGP Interlayer by DuPont/1/8" Annealed Glass</p> <p>Frame: W-1880mm(74.00") H-1600mm(63.00")</p> <p>Panel: W-927mm(36.25") H-1543mm(60.75")</p>

SPECIFICATION	PRODUCT RATING
<p>AAMA 506-08</p> <p>AAMA/WDMA/CSA 101/I.S.2/A440-11</p> <p>AAMA/WDMA/CSA 101/I.S.2/A440-08</p> <p>AAMA/WDMA/CSA 101/I.S.2/A440-05</p> <p>ASTM E1886-05/E1996-09</p> <p>TAS 201/202/203-94</p>	<p>Design Pressure: ±3351 Pa (70 psf)</p> <p>Class LC-PG70 1880 x 1600 (74 x 63)-HS</p> <p>HS-LC50 1880 x 1600 (74 x 63)</p> <p>Positive Design Pressure: 3351 Pa (70 psf)</p> <p>Negative Design Pressure: 4069 Pa (85 psf)</p> <p>Wind Zone 4-Missile Level D</p> <p>Large Missile Impact Rated</p> <p>Water Penetration Resistance Test Pressure: 502 Pa(10.50 psf)</p> <p>Qualifying Configurations: OX, XO</p>

Product Tested By: Certified Testing Laboratories, Inc.
 Report No: CTLA-3005W-3A/CTLA-3005W-3D
 Expiration Date: **June 30, 2018**

Administrator's Signature: _____

**NATIONAL ACCREDITATION AND
 MANAGEMENT INSTITUTE, INC.**
 4794 George Washington Memorial Highway
 Hayes, VA 23072
 Tel: (804) 684-5124/ Fax: (804) 684-5122