NOTICE OF PRODUCT CERTIFICATION



Masonite International Corporation Company:

1955 Powis Road

West Chicago, IL 60185

Certification No.: NI006721.01 **Certification Date:**

09/22/2006 12/31/2020

Expiration Date: Revision Date:

11/21/2014

Product:

Fir Glazed Inswing or Outswing Wood Door w/ or w/o Non-Impact Rated Sidelites

(w/Wood Frame unless noted)

Specification: PA 202/TAS 202/ASTM E330

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

	Inswing	Glazed		Structural	Water	Missile	Test Report Number
Configuration	or	or	Maximum	Design	Test	Impact	Drawing Number &
	Outswing	Opaque	Size	Pressure	Pressure	Rated	Comments
X	I/S	Glazed	3'0" x 6'8"	+47.5/-47.5	2.86 psf	No	NCTL-210-3314-1
Single					_		Maximum Panel Size: 3'0" x 6'8"
8							Anchor Details-MA-FL0156-06
X	O/S	Glazed	3'0" x 6'8"	+47.5/-47.5	4.50 psf	No	NCTL-210-3314-1
Single							Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06
XX	I/S	Glazed	6'0" x 6'8"	+47.5/-47.5	2.86 psf	No	NCTL-210-3314-1
Double							Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06
XX	O/S	Glazed	6'0" x 6'8"	+47.5/-47.5	4.50 psf	No	NCTL-210-3314-1
Double							Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06
XO/OX	I/S	Glazed	6'0" x 6'8"	+47.5/-47.5	2.86 psf	Door-No	NCTL-210-3314-1
Single w/Sidelite						Sidelite-No	Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06
XO/OX	O/S	Glazed	6'0" x 6'8"	+47.5/-47.5	4.50 psf	Door-No	NCTL-210-3314-1
Single w/Sidelite						Sidelite-No	Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06
OXO	I/S	Glazed	5'0" x 6'8"	+47.5/-47.5	2.86 psf	Door-No	NCTL-210-3314-1
Single w/Sidelites						Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
_							Anchor Details-MA-FL0156-06
OXO	O/S	Glazed	5'0" x 6'8"	+47.5/-47.5	4.50 psf	Door-No	NCTL-210-3314-1
Single w/Sidelites						Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06
OXXO	I/S	Glazed	8'0" x 6'8"	+47.5/-47.5	2.86 psf	Doors-No	NCTL-210-3314-1
Double w/Sidelites						Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06
OXXO	O/S	Glazed	8'0" x 6'8"	+47.5/-47.5	4.50 psf	Doors-No	NCTL-210-3314-1
Double w/Sidelites						Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
							Anchor Details-MA-FL0156-06

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: