## **NOTICE OF PRODUCT CERTIFICATION**



Company:	Masonite International Corporation 1955 Powis Road	Certification No.: Certification Date:	NI012729.01-R1 07/16/2015		
	West Chicago, IL 60185	<b>Expiration Date:</b>	12/31/2019		
		<b>Revision Date:</b>	09/10/2015		
<b>Product:</b>	Fiberglass Integral Glazed Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites				
	(w/Wood Frame unless noted)				
Specification:	TAS 202/ASTM E330				
Glazing:	IG-3mm Tempered Glass				

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or	Glazed or	Maximum Size	Structural Design	Water Test	Missile	Test Report Number
Configuration	Outswing					Impact Rated	Drawing Number & Comments
		Opaque		Pressure(psf)	Pressure		
Х	I/S or	Glazed	3'0" x 6'8"	+55/-60	0.0 psf	No	ATLNC0303.01
Single	I/S ADA						Maximum Panel Size: 3'0" x 6'8"
					HAR MERCAN PROVIDE		Anchor Detail-MA-FL0182
Х	O/S	Glazed	3'0" x 6'8"	+60/-55	5.25 psf <sup>1</sup>	No	ATLNC0303.01
Single					6.00 psf <sup>2</sup>		Maximum Panel Size: 3'0" x 6'8"
25					7.05 psf <sup>3</sup>		Anchor Detail-MA-FL0182
XX	I/S or	Glazed	6'0" x 6'8"	+55/-60	0.0 psf	No	ATLNC0303.01
Double	I/S ADA				•		Maximum Panel Size: 3'0" x 6'8"
							Anchor Detail-MA-FL0182
XX	O/S	Glazed	6'0" x 6'8"	+60/-55	5.25 psf <sup>1</sup>	No	ATLNC0303.01
Double					6.00 psf <sup>2</sup>		Maximum Panel Size: 3'0" x 6'8"
					7.05 psf <sup>3</sup>		Anchor Detail-MA-FL0182
XO/OX	I/S	Glazed Door	6'0" x 6'8"	+55/-60	0.0 psf	Door-No	ATLNC0303.01
Single w/Sidelite		Glazed Sidelite			P	Sidelite-No	Maximum Panel Size: 3'0" x 6'8"
2							Anchor Detail-MA-FL0182
XO/OX	O/S	Glazed Door	6'0" x 6'8"	+60/-55	5.25 psf <sup>1</sup>	Door-No	ATLNC0303.01
Single w/Sidelites		Glazed Sidelite	and and provide the		6.00 psf <sup>2</sup>	Sidelite-No	Maximum Panel Size: 3'0" x 6'8"
5					7.05 psf <sup>3</sup>		Anchor Detail-MA-FL0182
OXO	I/S	Glazed Door	9'0" x 6'8"	+55/-60	0.0 psf	Door-No	ATLNC0303.01
Single w/Sidelites		Glazed Sidelites			010 por	Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
Single Woldentes		Shized Shientes				Sidentes ite	Anchor Detail-MA-FL0182
OXO	O/S	Glazed Door	9'0" x 6'8"	+60/-55	5.25 psf <sup>1</sup>	Door-No	ATLNC0303.01
Single w/Sidelites		Glazed Sidelites			6.00 psf <sup>2</sup>	Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
Single Woldentes		Glazed Blachtes			7.05 psf <sup>3</sup>	Sidentes 110	Anchor Detail-MA-FL0182
OXXO	I/S	Glazed Doors	12'6" x 6'8"	+55/-60	0.0 psf	Doors-No	ATLNC0303.01
Double w/Sidelites		Glazed Sidelites			0.0 pb1	Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
2 suble w/blackeb		Shabed Shaentes				Sidentes 110	Anchor Detail-MA-FL0182
OXXO	O/S	Glazed Doors	12'6" x 6'8"	+60/-55	5.25 psf <sup>1</sup>	Doors-No	ATLNC0303.01
Double w/Sidelites	3/10	Glazed Sidelites			6.00 psf <sup>2</sup>	Sidelites-No	Maximum Panel Size: 3'0" x 6'8"
Bouble w/ Sidentes		Giazea Sidenies			7.05 psf <sup>3</sup>	Sidentes-140	Anchor Detail-MA-FL0182

<sup>1</sup>Bumper Threshold <sup>2</sup>Z-Series Threshold <sup>3</sup>Denotes High Dam Threshold Design

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23077 Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: