

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
 1955 Powis Road
 West Chicago, IL 60185

Certification No.: NI012729.02
Certification Date: 07/16/2015
Expiration Date: 12/31/2019

Product: Fiberglass Integral Glazed Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame unless noted)
Specification: TAS 202/ASTM E330
Glazing: IG-3mm Tempered Glass

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure(psf)	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 8'0"	+45/-47 +55/-55*	0.0 psf	No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
X Single	O/S	Glazed	3'0" x 8'0"	+47/-47	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XX Double	I/S	Glazed	6'0" x 8'0"	+45/-47 +55/-55*	0.0 psf	No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XX Double	O/S	Glazed	6'0" x 8'0"	+47/-47	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XO/OX Single w/Sidelite	I/S	Glazed Door Glazed Sidelite	6'0" x 8'0"	+45/-47 +55/-55*	0.0 psf	Door-No Sidelite-No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
XO/OX Single w/Sidelites	O/S	Glazed Door Glazed Sidelite	6'0" x 8'0"	+47/-47	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	Door-No Sidelite-No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXO Single w/Sidelites	I/S	Glazed Door Glazed Sidelites	9'0" x 8'0"	+45/-47 +55/-55*	0.0 psf	Door-No Sidelites-No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXO Single w/Sidelites	O/S	Glazed Door Glazed Sidelites	9'0" x 8'0"	+47/-47	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	Door-No Sidelites-No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXXO Double w/Sidelites	I/S	Glazed Doors Glazed Sidelites	12'6" x 8'0"	+45/-47 +55/-55*	0.0 psf	Doors-No Sidelites-No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1
OXXO Double w/Sidelites	O/S	Glazed Doors Glazed Sidelites	12'6" x 8'0"	+47/-47	5.25 psf ¹ 6.00 psf ² 7.05 psf ³	Doors-No Sidelites-No	ATLNC0427.01 Maximum Panel Size: 3'0" x 8'0" Anchor Detail-MA-FL0183-1

*Requires Surface Bolts ¹Bumper Threshold ²Z-Series Threshold ³Denotes High Dam Threshold Design

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____