

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
1955 Powis Road
West Chicago, IL 60185

Certification No.: NI013717.05-R1
Certification Date: 05/12/2017
Expiration Date: 05/31/2021
Revision Date: 11/20/2017

Product: Fiberglass Impact Glazed Inswing or Outswing Door w/ and w/o Impact Rated Sidelites
(w/Wood Frame or Worldwide Composite Frame⁴ unless noted)

Specification: TAS 202-94/ASTM E330-02/ASTM E1886-05/ASTM E1996-09

Impact: Wind Zone 4-Missile Level D (Glazing: IG-1/8" Tempered/Laminate-1/8" HS/0.090" Saflex Interlayer/1/8" HS)

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 6'8"	+50/-50	0.0 psf	Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17
X Single	O/S	Glazed	3'0" x 6'8"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁵	Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 /W-1843 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17/W-1813
XX Double	I/S	Glazed	6'0" x 6'8"	+50/-50	0 psf	Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17
XX Double	O/S	Glazed	6'0" x 6'8"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 8.25 psf ⁵	Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 /W-1843 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17/W-1813-1
XO/OX Single w/Sidelite	I/S	Glazed	6'0" x 6'8"	+50/-50	0 psf	Door-Yes Sidelite-Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17
XO/OX Single w/Sidelite	O/S	Glazed	6'0" x 6'8"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁵	Door-Yes Sidelite-Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 /W-1843 Maximum Panel Size: 3'0" x 6'8" Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17/W-1813
OXO Single w/Sidelites	I/S	Glazed	9'0" x 6'8"	+50/-50	0 psf	Door-Yes Sidelites-Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 Maximum Panel Size: 3'0" x 6'8" Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17
OXO Single w/Sidelites	O/S	Glazed	9'0" x 6'8"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁵	Door-Yes Sidelites-Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 /W-1843 Maximum Panel Size: 3'0" x 6'8" Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17/W-1813
OXXO Double w/Sidelites	I/S	Glazed	12'4" x 6'8"	+50/-50	0 psf	Door-Yes Sidelites-Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 Maximum Panel Size: 3'0" x 6'8" Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17
OXXO Double w/Sidelites	O/S	Glazed	12'4" x 6'8"	+50/-50	3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 8.25 psf ⁵	Door-Yes Sidelites-Yes	ATLNC 1222.01-15/0207.01-17/1012.01-16R/0907.01-16 /W-1843 Maximum Panel Size: 3'0" x 6'8" Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0195-17/W-1813

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-W-1815 5-Worldwide Pro T4 Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____