

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
1955 Powis Road
West Chicago, IL 60185

Certification No.: NI013717.07-R1
Certification Date: 05/12/2017
Expiration Date: 05/31/2021
Revision Date: 11/20/2017

Product: Fiberglass Glazed Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame or Worldwide Composite Frame⁴ unless noted)

Specification: TAS 202-94/ASTM E330-02

Glazing: Insulating Glass (Tempered) Full-Lite Doors Require “HPC” Construction Slabs

The “Notice of Product Certification” is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI’s Certified Product Listing at www.Namicertification.com. NAMI’s Certification Program is accredited by The American National Standards Institute (ANSI).

| Configuration | Inswing or Outswing | Glazed or Opaque | Maximum Size | Structural Design Pressure | Water Test Pressure | Missile Impact Rated | Test Report Number Drawing Number & Comments |
|-------------------------|---------------------|------------------|--------------|----------------------------|---|----------------------|--|
| X Single | I/S | Glazed | 3’0” x 8’0” | +47/-47 | 0.0 psf | No | ATLNC 0411.01-17 Maximum Panel Size: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| X Single | O/S | Glazed | 3’0” x 8’0” | +47/-47 | 3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁵ | No | ATLNC 0411.01-17/W-1813/W-1843 Maximum Panel Size: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| XX Double | I/S | Glazed | 6’0” x 8’0” | +47/-47 | 0 psf | No | ATLNC 0411.01-17 Maximum Panel Size: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| XX Double | O/S | Glazed | 6’0” x 8’0” | +47/-47 | 3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 8.25 psf ⁵ | No | ATLNC 0411.01-17/W-1813/W-1843 Maximum Panel Size: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| XO/OX Single w/Sidelite | I/S | Glazed | 6’0” x 8’0” | +47/-47 | 0 psf | Door-No Sidelite-No | ATLNC 0411.01-17 Maximum Panel Size: 3’0” x 8’0”/Sidelite: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| XO/OX Single w/Sidelite | O/S | Glazed | 6’0” x 8’0” | +47/-47 | 3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁵ | Door-No Sidelite-No | ATLNC 0411.01-17/W-1813/W-1843 Maximum Panel Size: 3’0” x 8’0”/Sidelite: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| OXO Single w/Sidelites | I/S | Glazed | 9’0” x 8’0” | +47/-47 | 0 psf | Door-No Sidelites-No | ATLNC 0411.01-17 Maximum Panel Size: 3’0” x 8’0”/Sidelite: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| OXO Single w/Sidelites | O/S | Glazed | 9’0” x 8’0” | +47/-47 | 3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 9.0 psf ⁵ | Door-No Sidelites-No | ATLNC 0411.01-17/W-1813/W-1843 Maximum Panel Size: 3’0” x 8’0”/Sidelite: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| OXXO Double w/Sidelites | I/S | Glazed | 12’4” x 8’0” | +47/-47 | 0 psf | Door-No Sidelites-No | ATLNC 0411.01-17 Maximum Panel Size: 3’0” x 8’0”/Sidelite: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |
| OXXO Double w/Sidelites | O/S | Glazed | 12’4” x 8’0” | +47/-47 | 3.75 psf ¹ 6.0 psf ² 8.25 psf ³ 8.25 psf ⁵ | Door-No Sidelites-No | ATLNC 0411.01-17/W-1813/W-1843 Maximum Panel Size: 3’0” x 8’0”/Sidelite: 3’0” x 8’0” Anchor Details-DWG-MA-FL0192-17 |

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-W-1815 5-Worldwide Pro T4 Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____