

# NOTICE OF PRODUCT CERTIFICATION



**Company:** Masonite International Corporation  
 1955 Powis Road  
 West Chicago, IL 60185

**Certification No.:** NI013717.17-R1  
**Certification Date:** 05/12/2017  
**Expiration Date:** 05/31/2021  
**Revision Date:** 11/20/2017

**Product:** Fiberglass Opaque Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites  
 (w/Wood Frame or Worldwide Composite Frame<sup>4</sup> unless noted)

**Specification:** TAS 202-94/ASTM E330-02/ASTM E1886-05/ASTM E1996-09

**Impact:** Wind Zone 4-Missile Level D Non-Impact Glazing: Insulating Glass (Tempered)

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at [www.Namicertification.com](http://www.Namicertification.com). NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Opaque	3'0" x 6'8"	+60/-65	0.0 psf	Yes	NCTL-210-3835-1/W-1812 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
X Single	O/S	Opaque	3'0" x 6'8"	+60/-60	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> 9.0 psf <sup>5</sup>	Yes	NCTL-210-3835-1/W-1812/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8" Anchor Details-MA-FL0187-17
XX Double	I/S	Opaque	6'0" x 6'8"	+50/-50	0 psf	Yes	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
XX Double	O/S	Opaque	6'0" x 6'8"	+50/-50	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> 9.0 psf <sup>5</sup>	Yes	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
XO/OX Single w/Sidelite	I/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+50/-50	0 psf	Door-Yes Sidelite-No	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
XO/OX Single w/Sidelite	O/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+50/-50	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> 9.0 psf <sup>5</sup>	Door-Yes Sidelite-No	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXO Single w/Sidelites	I/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+50/-50	0 psf	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXO Single w/Sidelites	O/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+50/-50	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> 9.0 psf <sup>5</sup>	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXXO Double w/Sidelites	I/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+50/-50	0 psf	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17
OXXO Double w/Sidelites	O/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+50/-50	3.75 psf <sup>1</sup> 6.0 psf <sup>2</sup> 8.25 psf <sup>3</sup> 9.0 psf <sup>5</sup>	Door-Yes Sidelites-No	ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0187-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-W-1815 5-Worldwide Pro T4 Threshold

**National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072**

**Tel: (804) 684-5124/Fax: (804) 684-5122**

**NAMI AUTHORIZED SIGNATURE:** \_\_\_\_\_

A handwritten signature in black ink, appearing to be 'MID'.