

# NOTICE OF PRODUCT CERTIFICATION



**Company:** Masonite International Corporation  
1955 Powis Road  
West Chicago, IL 60185

**Certification No.:** NI013717.17-R5  
**Certification Date:** 05/12/2017  
**Expiration Date:** 05/31/2027  
**Revision Date:** 12/06/2023

**Product:** Fiberglass Opaque Inswing or Outswing Door w/ and w/o Non-Impact Rated Sidelites (w/Wood Frame or Worldwide Composite Frame<sup>4</sup> unless noted)

**Specification:** TAS 202-94/ASTM E330-02/14/M-14/ASTM E1886-05/13a/ASTM E1996-09/14a

**Impact:** Missile Level D **Non-Impact Glazing:** Insulating Glass (Tempered)

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

| Configuration           | Inswing or Outswing | Glazed or Opaque            | Maximum Size | Structural Design Pressure | Water Test Pressure                                                                                                | Missile Impact Rated  | Test Report Number Drawing Number & Comments                                                                                                              |
|-------------------------|---------------------|-----------------------------|--------------|----------------------------|--------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| X Single                | I/S                 | Opaque                      | 3'0" x 6'8"  | +60/-65                    | 0.0 psf                                                                                                            | Yes                   | NCTL-210-3835-1/W-1812/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17                                                |
| X Single                | O/S                 | Opaque                      | 3'0" x 6'8"  | +60/-60                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup><br>7.5 psf <sup>6</sup> | Yes                   | NCTL-210-3835-1/W-1812/W-1813/W-1843/W-1860/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"<br>Anchor Details-MA-FL0187-17                               |
| XX Double               | I/S                 | Opaque                      | 6'0" x 6'8"  | +50/-50                    | 0 psf                                                                                                              | Yes                   | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17                                     |
| XX Double               | O/S                 | Opaque                      | 6'0" x 6'8"  | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /8.25 psf <sup>5</sup>                        | Yes                   | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843/W-2106<br>Maximum Panel Size: 3'0" x 6'8"/W-1972<br>Anchor Details-DWG-MA-FL0187-17                       |
| XO/OX Single w/Sidelite | I/S                 | Opaque Door Glazed Sidelite | 6'0" x 6'8"  | +50/-50                    | 0 psf                                                                                                              | Door-Yes Sidelite-No  | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17               |
| XO/OX Single w/Sidelite | O/S                 | Opaque Door Glazed Sidelite | 6'0" x 6'8"  | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup>                         | Door-Yes Sidelite-No  | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17 |
| OXO Single w/Sidelites  | I/S                 | Opaque Door Glazed Sidelite | 9'0" x 6'8"  | +50/-50                    | 0 psf                                                                                                              | Door-Yes Sidelites-No | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17               |
| OXO Single w/Sidelites  | O/S                 | Opaque Door Glazed Sidelite | 9'0" x 6'8"  | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /9.0 psf <sup>5</sup>                         | Door-Yes Sidelites-No | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17 |
| OXOX Double w/Sidelites | I/S                 | Opaque Door Glazed Sidelite | 12'4" x 6'8" | +50/-50                    | 0 psf                                                                                                              | Door-Yes Sidelites-No | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17               |
| OXOX Double w/Sidelites | O/S                 | Opaque Door Glazed Sidelite | 12'4" x 6'8" | +50/-50                    | 3.75 psf <sup>1</sup> /6.0 psf <sup>2</sup><br>8.25 psf <sup>3</sup> /8.25 psf <sup>5</sup>                        | Door-Yes Sidelites-No | ATLNC 0831.01-16/ATLNC 0901.02-16/W-1813/W-1843/W-1972/W-2106<br>Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8"<br>Anchor Details-DWG-MA-FL0187-17 |

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-W-1815 5-Worldwide Pro T4 Threshold 6-Denotes HP Outswing Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: \_\_\_\_\_