

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
 1955 Powis Road
 West Chicago, IL 60185

Certification No.: NI007077.04-R5
Certification Date: 04/10/2007
Expiration Date: 12/31/2020
Revision Date: 09/27/2017

Product: Fiberglass Impact Rated Glazed Inswing or Outswing Door w/ and w/o Impact Rated Sidelites
 (w/Wood Frame or Worldwide Composite Frame³ unless noted)

Specification: TAS 201/202/203-94/ASTM E330-02

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 8'0"	+43/-47	0 psf	Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807
X Single	O/S	Glazed	3'0" x 8'0"	+47/-45 +55/-55 w/Surface Bolts	3.75 psf/ 6.0 psf ¹ 8.25 psf ² /9.0 psf ⁴	Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807/W-1835
XX Double	I/S	Glazed	6'0" x 8'0"	+43/-47	0 psf	Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807
XX Double	O/S	Glazed	6'0" x 8'0"	+47/-45 +55/-55 w/Surface Bolts	3.75 psf/ 6.0 psf ¹ 8.25 psf ² /8.25 psf ⁴	Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807/W-1835
XO/OX Single w/Sidelite	I/S	Glazed Door Glazed Sidelite	6'0" x 8'0"	+43/-47	0 psf	Door-Yes Sidelite-Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807
XO/OX Single w/Sidelite	O/S	Glazed Door Glazed Sidelite	6'0" x 8'0"	+47/-45 +55/-55 w/Surface Bolts	3.75 psf/ 6.0 psf ¹ 8.25 psf ² /9.0 psf ⁴	Door-Yes Sidelite-Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807/W-1835
OXO Single w/Sidelites	I/S	Glazed Door Glazed Sidelites	9'0" x 8'0"	+43/-47	0 psf	Door-Yes Sidelite-Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807
OXO Single w/Sidelites	O/S	Glazed Door Glazed Sidelites	9'0" x 8'0"	+47/-45 +55/-55 w/Surface Bolts	3.75 psf/ 6.0 psf ¹ 8.25 psf ² /9.0 psf ⁴	Door-Yes Sidelite-Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807/W-1835
OXXO Double w/Sidelites	I/S	Glazed Doors Glazed Sidelites	12'6" x 8'0"	+43/-47	0 psf	Door-Yes Sidelite-Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807
OXXO Double w/Sidelites	O/S	Glazed Doors Glazed Sidelites	12'6" x 8'0"	+47/-45 +55/-55 w/Surface Bolts	3.75 psf/ 6.0 psf ¹ 8.25 psf ² /8.25 psf ⁴	Door-Yes Sidelite-Yes	NCTL-210-3367-1/ATLNC 1118.01-14/ATLNC 1031.01-16 Maximum Panel Size: 3'0" x 8'0" Anchor Details-MA-FL0173-07/W-1807/W-1835

1 -Denotes Z-Series Threshold Design 2 -Denotes High Dam Threshold Design 3-W-1815 4-Denotes Worldwide Pro T4 Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____