NOTICE OF PRODUCT CERTIFICATION

Company: Masonite International Corporation
1955 Powis Road
West Chicago, IL 60185

Certification No.: NI013747-R2
Certification Date: 06/08/2017
Expiration Date: 06/30/2025
Revision Date: 07/27/2020

Product: Wood-Edge Steel Opaque Inswing or Outswing Door w/Non-Impact Rated Sidelites (w/Wood Frame unless noted)
Specification: TAS 201/202/203-94
Impact: Large Missile Impact Rated Non-Impact Glazing: Insulating Glass (Tempered)

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Opaque	3'0" x 6'8"	+70/-70	0.0 psf	Yes	ATLNC 1001.01-13 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
X Single	O/S	Opaque	3'0" x 6'8"	+70/-70	3.0 psf[1] 4.5 psf [2] 7.50 psf [3,4,5]	Yes	ATLNC 1001.01-13/W-1857 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
XX Double	I/S	Opaque	6'0" x 6'8"	+55/-55	0 psf	Yes	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
XX Double	O/S	Opaque	6'0" x 6'8"	+55/-55	3.0 psf[1] 4.5 psf [2] 7.50 psf [3]	Yes	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
XO/OX Single w/Sidelite	I/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+55/-55	0 psf	Door-Yes Sidelite-No	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
XO/OX Single w/Sidelite	O/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+55/-55	3.0 psf[1] 4.5 psf [2] 7.50 psf [3]	Door-Yes Sidelite-No	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
OXO Single w/Sidelites	I/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+55/-55	0 psf	Door-Yes Sidelites-No	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
OXO Single w/Sidelites	O/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+55/-55	3.0 psf[1] 4.5 psf [2] 7.50 psf [3]	Door-Yes Sidelites-No	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
OXXO Double w/Sidelites	I/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+55/-55	0 psf	Door-Yes Sidelites-No	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17
OXXO Double w/Sidelites	O/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+55/-55	3.0 psf[1] 4.5 psf [2] 7.50 psf [3]	Door-Yes Sidelites-No	NCTL-210-2930-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0211-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-Pro T4 Threshold 5-HP Outswing Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____