

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
 1955 Powis Road
 West Chicago, IL 60185

Certification No.: NI013747.03-R2
Certification Date: 06/08/2017
Expiration Date: 06/30/2025
Revision Date: 07/27/2020

Product: Wood-Edge Steel 3/4-Lite or Less Glazed Inswing or Outswing Door w/Full-Lite or Less Non-Impact Rated Sidelites (w/Wood Frame unless noted)

Specification: TAS 202-94/ASTM E330-02

Glazing: Insulating Glass (Tempered)

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed 3/4-Lite Max	3'0" x 6'8"	+50/-50	0 psf	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
X Single	O/S	Glazed 3/4-Lite Max	3'0" x 6'8"	+50/-50	3.0 psf ¹ 4.5 psf ² 7.50 psf ^{3,4,5}	NCTL-110-19469-1/W-1857 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
X Single	I/S	Glazed Ventlite	3'0" x 6'8"	+50/-50	0 psf	NCTL-210-3461-1/W-1857 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-07
X Single	O/S	Glazed Ventlite	3'0" x 6'8"	+50/-50	0 psf	NCTL-210-3461-1/W-1857 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-07
XX Double	I/S	Glazed 3/4-Lite Max	6'0" x 6'8"	+50/-50	0 psf	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
XX Double	O/S	Glazed 3/4-Lite Max	6'0" x 6'8"	+50/-50	3.0 psf ¹ 4.5 psf ² 7.50 psf ³	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
XO/OX Single w/Sidelite	I/S	Glazed 3/4-Lite Max Door Full-Lite Max S/L	6'0" x 6'8"	+50/-50	0 psf	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
XO/OX Single w/Sidelite	O/S	Glazed 3/4-Lite Max Door Full-Lite Max S/L	6'0" x 6'8"	+50/-50	3.0 psf ¹ 4.5 psf ² 7.50 psf ³	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
OXO Single w/Sidelites	I/S	Glazed 3/4-Lite Max Door Full-Lite Max S/L	9'0" x 6'8"	+50/-50	0 psf	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
OXO Single w/Sidelites	O/S	Glazed 3/4-Lite Max Door Full-Lite Max S/L	9'0" x 6'8"	+50/-50	3.0 psf ¹ 4.5 psf ² 7.50 psf ³	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
OXXO Double w/Sidelites	I/S	Glazed 3/4-Lite Max Door Full-Lite Max S/L	12'4" x 6'8"	+50/-50	0 psf	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17
OXXO Double w/Sidelites	O/S	Glazed 3/4-Lite Max Door Full-Lite Max S/L	12'4" x 6'8"	+50/-50	3.0 psf ¹ 4.5 psf ² 7.50 psf ³	NCTL-110-19469-1 Maximum Panel Size: 3'0" x 6'8" /Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0214-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-Pro T4 Threshold 5-HP Outswing Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072
Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____ *AKO*