

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation

1955 Powis Road
West Chicago, IL 60185

Product: Metal-Edge Steel Glazed Inswing or Outswing Door w/ & w/o Impact Rated Sidelites
(w/Wood Frame unless noted)

Specification: TAS 201/202/203-94

Glazing: Insulating Glass: 1/8" Tempered Glass/1/8" Heat Strengthened Glass/0.090" Saflex PVB
Interlayer/1/8" Heat Strengthened Glass

Certification No.: NI013762.05

Certification Date: 06/26/2017

Expiration Date: 06/30/2021

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Glazed	3'0" x 6'8"	+40/-45	0.0 psf	Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
X Single	O/S	Glazed	3'0" x 6'8"	+45/-40	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XX Double	I/S	Glazed	3'0" x 6'8"	+40/-45	0 psf	Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XX Double	O/S	Glazed	3'0" x 6'8"	+45/-40	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XO/OX Single w/Sidelite	I/S	Glazed Door Glazed Sidelite	6'0" x 6'8"	+40/-45	0 psf	Door-Yes Sidelite-Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
XO/OX Single w/Sidelite	O/S	Glazed Door Glazed Sidelite	6'0" x 6'8"	+45/-40	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Door-Yes Sidelite-Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXO Single w/Sidelites	I/S	Glazed Door Glazed Sidelite	9'0" x 6'8"	+40/-45	0 psf	Door-Yes Sidelite-Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXO Single w/Sidelites	O/S	Glazed Door Glazed Sidelite	9'0" x 6'8"	+45/-40	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Door-Yes Sidelite-Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXXO Double w/Sidelites	I/S	Glazed Door Glazed Sidelite	12'4" x 6'8"	+40/-45	0 psf	Door-Yes Sidelite-Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17
OXXO Double w/Sidelites	O/S	Glazed Door Glazed Sidelite	12'4" x 6'8"	+45/-40	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Door-Yes Sidelite-Yes	ATLNC 0124.01-17 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0222-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3 -Hi-Dam Outswing Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____