

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
 1955 Powis Road
 West Chicago, IL 60185

Certification No.: NI013762.06
Certification Date: 06/26/2017
Expiration Date: 06/30/2021

Product: Metal-Edge Steel Opaque Inswing or Outswing Door w/ & w/o Non-Impact Rated Sidelites
 (w/Wood Frame unless noted)

Specification: TAS 201/202/203-94

Impact: Large Missile Impact Rated (Sidelite Non-Impact Glazing: Insulating Glass (Tempered))

The "Notice of Product Certification" is only valid if the NAMI Certification Label has been applied to the product as described within this document. The certification label represents product conformity to the applicable specification and that all certification criteria has been satisfied. This product has been approved for listing within NAMI's Certified Product Listing at www.Namicertification.com. NAMI's Certification Program is accredited by The American National Standards Institute (ANSI).

| Configuration | Inswing or Outswing | Glazed or Opaque | Maximum Size | Structural Design Pressure | Water Test Pressure | Missile Impact Rated | Test Report Number Drawing Number & Comments |
|-------------------------|---------------------|-----------------------------|--------------|----------------------------|--|----------------------|---|
| X Single | I/S | Opaque | 3'0" x 8'0" | +48/-48 | 0.0 psf | Yes | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| X Single | O/S | Opaque | 3'0" x 8'0" | +48/-48 | 3.75 psf ¹ 6.0 psf ² 6.75 psf ³ | Yes | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| XX Double | I/S | Opaque | 3'0" x 8'0" | +48/-48 | 0 psf | Yes | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| XX Double | O/S | Opaque | 3'0" x 8'0" | +48/-48 | 3.75 psf ¹ 6.0 psf ² 6.75 psf ³ | Yes | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| XO/OX Single w/Sidelite | I/S | Opaque Door Glazed Sidelite | 6'0" x 8'0" | +48/-48 | 0 psf | Door-Yes Sidelite-No | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| XO/OX Single w/Sidelite | O/S | Opaque Door Glazed Sidelite | 6'0" x 8'0" | +48/-48 | 3.75 psf ¹ 6.0 psf ² 6.75 psf ³ | Door-Yes Sidelite-No | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| OXO Single w/Sidelites | I/S | Opaque Door Glazed Sidelite | 9'0" x 8'0" | +48/-48 | 0 psf | Door-Yes Sidelite-No | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| OXO Single w/Sidelites | O/S | Opaque Door Glazed Sidelite | 9'0" x 8'0" | +48/-48 | 3.75 psf ¹ 6.0 psf ² 6.75 psf ³ | Door-Yes Sidelite-No | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| OXXO Double w/Sidelites | I/S | Opaque Door Glazed Sidelite | 12'4" x 8'0" | +48/-48 | 0 psf | Door-Yes Sidelite-No | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |
| OXXO Double w/Sidelites | O/S | Opaque Door Glazed Sidelite | 12'4" x 8'0" | +48/-48 | 3.75 psf ¹ 6.0 psf ² 6.75 psf ³ | Door-Yes Sidelite-No | NCTL 210-1980-1,2,3,4,5,6 Maximum Panel Size: 3'0" x 8'0"/Sidelite: 3'0" x 8'0" Anchor Details-DWG-MA-FL0224-17 |

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/Fax: (804) 684-5122

NAMI AUTHORIZED SIGNATURE: _____