

NOTICE OF PRODUCT CERTIFICATION



Company: Masonite International Corporation
1955 Powis Road
West Chicago, IL 60185

Certification No.: NI013762-R4
Certification Date: 06/26/2017
Expiration Date: 06/30/2027
Revision Date: 11/14/2023

Product: Metal-Edge Steel Opaque Inswing or Outswing Door w/ & w/o Non-Impact Rated Sidelites
(w/Wood Frame unless noted)

Specification: TAS 201/202/203-94

Impact: Large Missile Impact Rated Non-Impact Glazing: Insulating Glass (Tempered)

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit www.namicertification.com. NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

Configuration	Inswing or Outswing	Glazed or Opaque	Maximum Size	Structural Design Pressure	Water Test Pressure	Missile Impact Rated	Test Report Number Drawing Number & Comments
X Single	I/S	Opaque	3'0" x 6'8"	+65/-65	0.0 psf	Yes	NCTL-210-1864-1,2,2,4/W-1961 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
X Single	O/S	Opaque	3'0" x 6'8"	+65/-65	3.75 psf ¹ 6.0 psf ² 7.50 psf ^{3,4,5}	Yes	NCTL-210-1864-1,2,2,4/W-1857/W-1961 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
XX Double	I/S	Opaque	6'0" x 6'8"	+55/-55	0 psf	Yes	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
XX Double	O/S	Opaque	6'0" x 6'8"	+55/-55	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Yes	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
XO/OX Single w/Sidelite	I/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+55/-55	0 psf	Door-Yes Sidelite-No	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
XO/OX Single w/Sidelite	O/S	Opaque Door Glazed Sidelite	6'0" x 6'8"	+55/-55	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Door-Yes Sidelite-No	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
OXO Single w/Sidelites	I/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+55/-55	0 psf	Door-Yes Sidelites-No	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
OXO Single w/Sidelites	O/S	Opaque Door Glazed Sidelite	9'0" x 6'8"	+55/-55	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Door-Yes Sidelites-No	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
OXXO Double w/Sidelites	I/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+55/-55	0 psf	Door-Yes Sidelites-No	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17
OXXO Double w/Sidelites	O/S	Opaque Door Glazed Sidelite	12'4" x 6'8"	+55/-55	3.75 psf ¹ 6.0 psf ² 7.50 psf ³	Door-Yes Sidelites-No	NCTL-210-1905-1,2,3,4,5,6/W-1961 Maximum Panel Size: 3'0" x 6'8"/Sidelite: 3'0" x 6'8" Anchor Details-DWG-MA-FL0218-17

1 -Denotes Bumper Outswing Threshold 2 -Denotes Z-Series Outswing Threshold 3-Hi-Dam Outswing Threshold 4-Pro T4 Threshold 5-HP Outswing Threshold

National Accreditation & Management Institute, Inc./4794 George Washington Memorial Highway/Hayes, VA 23072

Tel: (804) 684-5124/nami@namiinc.com

NAMI AUTHORIZED SIGNATURE: _____