

# NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI013954.20-R2  
**DATE:** 04/06/2020  
**CERTIFICATION PROGRAM:** Structural  
**COMPANY:** Eastern Arch  
**CODE:** 1783-1  
**REVISION DATE:** 10/16/2023

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<b>Eastern Architectural Systems</b> <b>16341 Domestic Avenue</b> <b>Ft. Myers, FL 33912</b>	<b>Series "650 Multi-Slide/Pocket Door"</b> <b>Vinyl Sliding Glass Door</b>  Configuration: OXXO Glazing: Insulating Glass (Tempered) Frame: W-5023mm(197.75") H-2438mm(96") Panel: W-1276mm(50.25") H-2357mm(92.81") DLO: W-1099mm(43.25") H-2180mm(85.81")

SPECIFICATION	PRODUCT RATING
<b>AAMA/WDMA/CSA 101/I.S.2/A440-11</b> <b>AAMA/WDMA/CSA 101/I.S.2/A440-08</b>	<b>Class CW-PG45 5023 x 2438 (198 x 96)-SD</b> <b>Design Pressure: ±2160 Pa (45 psf)</b> <small>No Sill Riser Water Penetration Resistance Test Pressure: 324 Pa (6.75 psf) 0.522" Sill Riser Water Penetration Resistance Test Pressure: 432 Pa (9.0 psf) 1.44" Sill Riser Water Penetration Resistance Test Pressure: 576 Pa (12.0 psf) 1.94" Sill Riser Water Penetration Resistance Test Pressure: 720 Pa (15.0 psf)</small>

Product Tested By: National Certified Testing Laboratories  
Report No: NCTL-210-4143-03A (Spec 2)  
Expiration Date: April 30, 2027

Administrator's Signature: \_\_\_\_\_

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway  
Hayes, VA 23072

Tel: (804) 684-5124

Email: [nami@namiinc.com](mailto:nami@namiinc.com)

NOPC-03/30/2023