

# NOTICE OF PRODUCT CERTIFICATION



<b>CERTIFICATION NO:</b>	<u>NI013954.21-R3</u>
	<b>DATE:</b> <u>04/06/2020</u>
<b>CERTIFICATION PROGRAM:</b>	<u>Structural</u>
<b>COMPANY:</b>	<u>Eastern Arch</u>
<b>CODE:</b>	<u>1783-1</u>
<b>REVISION DATE:</b>	<u>10/16/2023</u>

This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. To affirm the certification status, please visit [www.namicertification.com](http://www.namicertification.com). NAMI is accredited to the ISO/IEC 17065 by the ANSI National Accreditation Board (ANAB) and the Standards Council of Canada (SCC).

COMPANY NAME AND ADDRESS	PRODUCT DESCRIPTION
<p><b>Eastern Architectural Systems</b></p> <p><b>16341 Domestic Avenue</b></p> <p><b>Ft. Myers, FL 33912</b></p>	<p><b>Series "650 Multi-Slide/Pocket Door"</b></p> <p><b>Impact Vinyl Sliding Glass Door</b></p> <p style="text-align: center;">Configuration: OXO</p> <p style="text-align: center;">Glazing: IG-3/16" Tempered Glass/3/16" Annealed Glass/0.090" Kuraray America Trosifol PVB Interlayer/3/16" Annealed Glass</p> <p>Frame: W-3824mm(150.56") H-2438mm(96")</p> <p>Panel: W-1276mm(50.25") H-2357mm(92.81")</p> <p>DLO: W-1099mm(43.25") H-2180mm(85.81")</p>

SPECIFICATION	PRODUCT RATING
<p><b>AAMA/WDMA/CSA 101/I.S.2/A440-11</b></p> <p><b>AAMA/WDMA/CSA 101/I.S.2/A440-08</b></p> <p><b>ASTM E1886-05/12/E1996-05/09/12</b></p>	<p><b>Class CW-PG45 3824 x 2438 (151 x 96)-SD</b></p> <p><b>Design Pressure: ±2160 Pa (45 psf)</b></p> <p style="font-size: small;">No Sill Riser Water Penetration Resistance Test Pressure: 324 Pa (6.75 psf)</p> <p style="font-size: small;">0.522" Sill Riser Water Penetration Resistance Test Pressure: 432 Pa (9.0 psf)</p> <p style="font-size: small;">1.44" Sill Riser Water Penetration Resistance Test Pressure: 576 Pa (12.0 psf)</p> <p style="font-size: small;">1.94" Sill Riser Water Penetration Resistance Test Pressure: 720 Pa (15.0 psf)</p> <p><b>ASTM E1886/E1996 Impact Rating</b></p> <p><b>Design Pressure: ±2640 Pa (55 psf)</b></p> <p><b>Wind Zone 3 - Missile Level D</b></p>

Product Tested By: National Certified Testing Laboratories  
 Report No: NCTL-210-4143-03A (Spec3)/W-1959  
 Expiration Date: **April 30, 2027**

Administrator's Signature: \_\_\_\_\_

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway  
 Hayes, VA 23072  
 Tel: (804) 684-5124

Email: [nami@namiinc.com](mailto:nami@namiinc.com)

NOPC-03/30/2023