

# NOTICE OF PRODUCT CERTIFICATION



**CERTIFICATION NO:** NI014137.07-R2  
**DATE:** 06/19/2019  
**CERTIFICATION PROGRAM:** Structural  
**COMPANY:** Nan Ya  
**CODE:** 661-1  
**REVISION DATE:** 11/08/2021

To verify that the "Notice of Product Certification" is valid, please visit [www.NAMICertification.com](http://www.NAMICertification.com) to assure that the product is active and currently listed. This certification represents product conformity to the applicable specification and that certification criteria has been satisfied. A NAMI approved certification label must be applied to the product to claim certification status. Please review and advise NAMI if any corrections are required to this document.

| COMPANY NAME AND ADDRESS   | PRODUCT DESCRIPTION   |
|--|---|
| <b>Nan Ya Plastics Corporation USA</b><br><b>8989 North Loop East, Suite 800</b><br><b>Houston, TX 77029</b> | <b>Series "SLPS" Glazed Fiberglass</b><br><b>Outswing Side-Hinged Door Assembly</b><br><b>w/Sidelites &amp; Sandwich Glazed</b><br><br>Configuration: OXX/O<br>Glazing: IG-1/8" Tempered Glass/1/8" Tempered Glass/Dupont<br>Butacite PVB Interlayer/1/8" Tempered Glass<br><br>Frame: W-3720mm(146.44") H-2469mm(97.19")<br>Panel: W-908mm(35.75") H-2419mm(95.25")<br>DLO: W-635mm(25") H-2007mm(79") |

| SPECIFICATION   | PRODUCT RATING   |
|---|--|
| <b>AAMA/WDMA/CSA 101/I.S.2/A440-11</b><br><b>CSA A440S1-09</b><br><b>ASTM E1886-05</b><br><b>ASTM E1996-05/09</b> | <b>Class LC-PG50 3720 x 2469 (146 x 97)-SHD</b><br><b>Design Pressure: ±2400 Pa (50 psf)</b><br><b>Water Penetration Resistance Test Pressure: 360 Pa (7.5 psf)</b><br><b>Canadian Air Infiltration/Exfiltration Level: A3</b><br><b>Wind Zone 4 - Missile Level D</b> |

Product Tested By: National Certified Testing Laboratories  
Report No: NCTL-210-4103-07 (Revision 2)(Specimens 6 & 8)/NCTL-210-4103-08  
Expiration Date: April 30, 2026

Administrator's Signature: \_\_\_\_\_

## NATIONAL ACCREDITATION AND MANAGEMENT INSTITUTE, INC.

4794 George Washington Memorial Highway  
Hayes, VA 23072  
Tel: (804) 684-5124  
Fax: (804) 684-5122