

ZHDL.R27576 - Door Frames

Door Frames

[See General Information for Door Frames](#)

CECO DOOR PRODUCTS, DIV OF ASSA ABLOY DOOR GROUP L L C
9159 TELECOM DR
MILAN, TN 38358-3425 USA

R27576

Model	Configuration	Wall Type	Max	Design	Impact	
			Opening Size	Load (psf)	Energy (ft-lbs)	Speed (ft/sec)
Hollow Metal	Single Swing Three sided - KD or Welded Four sided - Welded	Drywall wood or metal stud, Masonry, Precast, Steel building structure	4-0, 8-0	70	350	50
Hollow Metal	Standard Swing Pair, With or Without Hardware or Hollow Metal Mullion Three sided - KD or Welded Four sided - Welded	Drywall wood or metal stud, Masonry, Precast, Steel building structure	8-0, 8-0	70	350	50
Hollow Metal	Standard Swing Pair with Transoms and Sidelights	Drywall wood or metal stud, Masonry, Precast, Steel building structure	12-8, 10-0	60	350	50
Hollow Metal	Single Swing with Transoms and Sidelights	Drywall wood or metal stud, Masonry, Precast, Steel building structure	12-8, 10-0	60	350	50
Hollow Metal	Window Frame	Drywall wood or metal stud, Masonry, Precast, Steel building structure	12-8, 10-0	60	350	50
Hollow Metal	Single swing with Readysset Fame	Drywall wood stud, Steel Buck	3-0, 7-0	70	350	50
Hollow Metal	Single Swing, KD or Welded Four sided - Welded	Drywall wood or metal stud, Masonry, Precast, Steel building structure	3-0, 7-0	100	350	50
Hollow Metal	Standard Swing Single, KD or Welded Four sided - Welded	Drywall wood or metal stud, Masonry, Precast, Steel building structure	4-0, 8-0	150	350	50
Hollow Metal	Standard Swing Pair, With or Without Hardware or Hollow Metal Mullion Three sided - KD or Welded Four sided - Welded	Drywall wood or metal stud, Masonry, Precast, Steel building structure	8-0, 8-0	150	350	50
Hollow Metal	Single Swing, Three sided - KD or Welded Four sided - Welded - Water Infiltration	Drywall wood or metal stud, Masonry, Precast, Steel building structure	4-0, 8-0	+/- 50	—	—
Hollow Metal	Standard Swing Pair, with Hardware Mullion Three sided - KD or Welded Four sided - Welded Water Infiltration	Drywall wood or metal stud, Masonry, Precast, Steel building structure	8-0, 8-0	+/- 60	—	—
Hollow Metal	Single Swing, Three sided - KD or Welded Four sided - Welded	Drywall wood or metal stud, Masonry, Precast, Steel building structure	4'0" x 8'0"	±150	895	80
Hollow Metal	Standard Swing Pair with or without Hardware Mullion Three sided - KD or Welded Four sided - Welded	Drywall wood or metal stud, Masonry, Precast, Steel building structure	8'0" x 8'0"	±150	895	80

Products also tested to TAS 201, TAS 202 (Structural only), TAS 203, ASTM E330, ASTM E1886, ANSI/SDI A250.13 and ASTM E1996.

* See [ZHCH](#) for ratings and construction details.

[Last Updated](#) on 2020-04-09