



**ZHLL.R38772**

**Products for Use in Windstorm-rated Assemblies**

[Page Bottom](#)

**Products for Use in Windstorm-rated Assemblies**

[See General Information for Products for Use in Windstorm-rated Assemblies](#)

**ACTIVE VENTILATION PRODUCTS INC**

R38772

311 1ST ST  
NEWBURGH, NY 12550 USA

Product	Assembly No.	Test Method	Ratings
Keapa Vent Series: Models KV 04, KV 06, KV 08, KV 10, KV 12	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — ± 68 psf Static Test Pressure — ± 136 psf
		ASTM E330	Design Pressure — ± 68 psf Static Test Pressure — ± 136 psf
Round Back Vent Series: Models RBV 3 C2, RBV 3 C4, RBV 4 C2, RBV 4 C4, RBV 5 C2, RBV 5 C4, RBV 6 C2, RBV 6 C4, RBV 8 C2, RBV 8 C4, RBV 10 C2, RBV 10 C4	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — ± 68 psf Static Test Pressure — ± 136 psf
		ASTM E330	Design Pressure — ± 68 psf Static Test Pressure — ± 136 psf
Universal Vent Series: Model UV 15	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — ± 68 psf Static Test Pressure — ± 136 psf

		ASTM E330	Design Pressure — ± 68 psf Static Test Pressure — ± 136 psf
Universal Vent Series: Models UV 30, UV 45, UV 60, UV 75, UV 90, UV 105, UV 120, UV 135	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — ± 51 psf Static Test Pressure — ± 102 psf
		ASTM E330	Design Pressure — ± 51 psf Static Test Pressure — ± 102 psf
Aura Vent Series: Model AV-04-C12	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — ±112.5 psf Static Test Pressure — ±225 psf
		ASTM E330	Design Pressure — ±112.5 psf Static Test Pressure — ±225 ps
Aura Vent Series: Models AV-04-C02, AV-04-C04, AV-04-C06, AV-04-C08, AV-06-C02, AV-06-C04, AV-06-C06, AV-06-C08, AV-06-C10, AV-08-C02, AV-08-C04, AV-08-C06, AV-08-C08, AV-08-C12, AV-10-C02, AV-10-C04, AV-10-C06, AV-10-C08, AV-10-C12, AV-12-C02, AV-12-C04, AV-12-C06, AV-12-C08, AV-12-C12, AV-14-C02, AV-14-C04, AV-14-C06, AV-14-C08, AV-14-C12, AV-16-C02, AV-16-C04, AV-16-C06, AV-16-C08, AV-16-C12, AV-18-C02, AV-18-C04, AV-18-C06, AV-18-C08, AV-18-C12, AV-20-C02, AV-20-C04, AV-20-C06, AV-20-C08, AV-20-C12, AV-24-C02, AV-24-C04, AV-24-C06, AV-24-C08, AV-24-C12	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — +60 psf - 112.5 psf Static Test Pressure - +120 psf -225 psf
		ASTM E330	Design Pressure - +60 psf - 112.5 psf Static Test Pressure

			— +120 psf -225 psf
Pop Vent Series: Model PV-04-C12	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — ±112.5 psf Static Test Pressure — ±225 psf
		ASTM E330	Design Pressure — ±112.5 psf Static Test Pressure — ±225 psf
Pop Vent Series: Models PV-04-C01, PV-04-C02, PV-04-C04, PV-04-C06, PV-04-C08, PV-06-C01, PV-06-C02, PV-06-C04, PV-06-C06, PV-06-C08, PV-06-C10, PV-08-C01, PV-08-C02, PV-08-C04, PV-08-C06, PV-08-C08, PV-08-C12, PV-10-C01, PV-10-C02, PV-10-C04, PV-10-C06, PV-10-C08, PV-10-C12, PV-12-C01, PV-12-C02, PV-12-C04, PV-12-C06, PV-12-C08, PV-12-C12, PV-14-C01, PV-14-C02, PV-14-C04, PV-14-C06, PV-14-C08, PV-14-C12, PV-16-C02, PV-16-C04, PV-16-C06, PV-16-C08, PV-16-C12, PV-18-C02, PV-18-C04, PV-18-C06, PV-18-C08, PV-18-C12, PV-20-C02, PV-20-C04, PV-20-C06, PV-20-C08, PV-20-C12, PV-24-C02, PV-24-C04, PV-24-C06, PV-24-C08, PV-24-C12	<a href="#">48</a>	TAS 202 (Structural Load Only)	Design Pressure — +60 psf - 112.5 psf Static Test Pressure — +120 psf -225 psf
		ASTM E330	Design Pressure — +60 psf - 112.5 psf Static Test Pressure — +120 psf -225 psf

[Last Updated](#) on 2017-11-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".

