



LISTING INFORMATION OF
Curries 30 x 70 Doors (Windstorm) 115 psf
SPEC ID: 22381

Curries Company
1502 12th Street NW
PO Box 1648
Mason City, IA 50401
United States

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

LISTING INFORMATION

Product Description:

Door Models : 707, 727, 747				Stiffness Class: 1			
Design Pressure (psf)	Max Size	Door Face Type	Swing Configuration	Latching Hardware	Impact Rating (ft-lbs)	Min. Latch Throw	Min Latch Strength
115	3' x 7'	Flush	Single In-swing or Out-swing	Mortise Lock with Latch Bolt and Dead Bolt	350	Latch Bolt: 3/4" Dead Bolt: 1"	1207.5
115	3' x 7'	Flush	Single Out-swing	Rim Exit	350	3/4"	N/A

Thresholds: Pemko 2005
Weather-strip: Pemko S88

Product not qualified for water infiltration.

See manufacturer's installation instructions for more information.

Design pressure ratings (in PSF) and the impact energy involved included above - 9 lb 2x4 @ 50 ft/sec, 350 ft-lbs.

Attribute	Value
Criteria	ASTM E330 (2002)
Criteria	ASTM E1886 (2002)

Criteria	ASTM E1996 (2003)
Criteria	ANSI A250.13 (2003)
Criteria	TAS 203
Criteria	TAS 201
Criteria	ASTM E1886 (2005)
Criteria	TAS 202 - Structural
Criteria	TAS 202 - Air Infiltration
Criteria	ANSI A250.13 (2005)
Criteria	ASTM E1996 (2008)
CSI Code	08 11 00 Metal Doors and Frames
DP Rating (psf)	115
Hardware	Mortise Latching
Hardware	Rim Exit Latching
Hurricane Impact Load Rating ft-lb	350
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	WIND LOAD RESISTANT DOORS
Report Number	3060066, 3085345, 3144406MID-009, 100099459, 100099459MID-001, 102441385MID-001
Spec ID	22381
Stiffness Class	I
Swing	In swing
Swing	Out swing
Verification Testing	No