

CERTIFICATE OF COMPLIANCE

Certificate Number R21803
Report Reference R21803-2004-08-07
Date 2021-April-12

Issued to: Fyre-Tec
701 Centennial Rd
Wayne NE, 68787 US

**This is to certify that
representative samples of**

PRODUCTS FOR USE IN WINDSTORM-RATED
ASSEMBLIES

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

AAMA/WDMA/CSA 101/I.S.2/A440-17 "North America
Fenestration Standard/Specification for Windows, Doors
and Skylights"


Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R21803
Report Reference R21803-2004-08-07
Date 2021-April-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Series 925P wind resistant window assemblies meeting the requirements for windows tested in accordance with ANSI/AAMA/NWWDA 101/I.S.2-97, AAMA/WDMA/CSA 101/I.S.2/A440-11, or AAMA/WDMA/CSA 101/I.S.2/A440-17. Product is able to bear a as H-R55 (48 x72) based on the 97 edition of ANSI/AAMA/NWWDA 101/I.S.2 or Class R-PG55 – Size Tested 48 x 72 in - Hung (DP = +/- 55 psf) rating based 2011 edition of AAMA/WDMA/CSA 101/I.S.2/A440 or Class R-PG55 – Mulled Single Hung - Size Tested 72 x 72 in (DP = +/- 75 psf) rating based 2017 edition of AAMA/WDMA/CSA 101/I.S.2/A440.



Bruce Mahrenholz, Director North American Certification Program



UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>