



1 1/2" MIN. EMBEDMENT

MIN. DISTANCE FROM EDGE: 3/4"-

-1/4" MAX SHIM SPACE

NAIL FIN INSTALLATION

## Max OPERATING 48 Frame 48 AWNING -50 WINDOW MPACT N 0

FRAME JAMB SECTION (TYP) NOTE: Caulk between Nailing Flange & Wood Opening HORIZONTAL SECTION

## Installed Fastener Schedule:

N → Seal flange/frame to substrate.

ယ္

- Use #8 PH or greater fasteners through nail fin with sufficient length to penetrate a minimum of 1 1/2" into the wood framing. For 2X wood frame substrate (min. S.G. = 0.42).
- project of installation. Host structure (wood buck, stud framing and opening) to be designed and anchored to properly transfer all loads to the structure. The host structure is the responsibility of the architect or engineer of record for the

www.jeld-wen.com/resources/installation packaged with the window or go to conditions. For the complete installation procedure, see the instructions not address the sealing consideration that may arise in different wall noted. It is not intended as a guide to the installation process and does window to achieve the rated design pressure up to the size limitations This schedule addresses only the fasteners required to anchor the

## DISCLAIMER:

except as authorized by JELD-WEN Inc. reproduced or copied in whole or in part or used or disclosed to others This drawing and its contents are confidential and are not to be

## General Notes:

- Building Code (FBC) and the industry standard requirement for the stated conditions. the adopted International Building Code (IBC), the International Residential Code (IRC), the Florida The product shown herein is designed, tested and manufactured to comply with the wind load criteria of
- Buck, framing and masonry by others and is responsibility of architect or engineer of record.
- ωΝ All glazing shall conform to ASTM E1300
- At minimum, glazing shall be double strength annealed insulating glass.
- 4 0 Maximum sizes are buck sizes and do not include fin or flange.

REV: 00 SHEET	CAD DWG. No.: REV: CustCLAwnOperInstall	TION:	Bend, Oregon	IDENTIFIER No.
		<u>.</u>		D009286
ָּבְּיָבְּאָ 	Nail Fin Installation (48" x 48":	N		1 1000
	Custom Clad Awning Operator	Cust		APPROVED BY:
			חוורב:	CHECKED BY: D. Stokes
Phone: (541) 882-3451	•	J J	NTS	D Vezo
Klamath Falls, OR. 97601				DDAWNI RV:
3250 Lakeport Blvd			DATE: 7/30/13	PROJECT ENGINEER: