


NAIL FIN INSTALLATION



52 1/8" × 75"	Max Frame	BRICKMOULD '
+/-50	DP RATING	D VINYL SH WINDOV
O	IMPACT	MODUL

Installation Notes:

Seal flange/frame to substrate

ယ

- into the wood framing. For 2X wood frame substrate (min. S.G. = 0.42). Use #8 PH or greater fastener though the nail fin with sufficient length to penetrate a minimum of 1 1/2"
- project of installation. Host structure (wood buck, masonry, steel) to be designed and anchored to properly transfer all loads to the structure. The host structure is the responsibility of the architect or engineer of record for the

not address he sealing consideration that may arise in different wall noted. It is not intended as a guide to the installation process and does window to achieve the rated design pressure up to the size limitations This schedule addresses only the fasteners required to anchor the

packaged with the window or go to www.jeld-wen.com/resources/installation.

conditions. For the complete installation procedure, see the instructions

DISCLAIMER:

except as authorized by JELD-WEN Inc. reproduced or copied in whole or in part or used or disclosed to others This drawing and its contents are confidential and are not to be

General Notes:

- of the adopted International Building Code(IBC), the International Residential Code(IRC), the Florida Building Code(FBC) and the industry requirement for the stated conditions. The product shown herein is designed, tested and manufactured to comply with the wind load criteria
- ं स्याप All glazing shall conform to ASTM E1300.
 - At minimum, glazing shall be single strength annealed insulating glass
 - Use structural or composite shims where required.
 - Installation methods can be interchanged within the same opening.
- building code. An impact protective system is required where wind bourne debris protection is mandated by local
- Maximum sizes are buck sizes and do not include fin or flange

_							
DENTIFIER W. 270-FBC	D008897	99.99	APPROVED BY:	CHECKED BY: J. Kantola	D. Vezo	•	PROJECT ENGINEER:
PLANT NAME AND LOCATION:			5 1	NTS	01/10/2013	DATE:	
		Nail Fin I	Brickmould vinyi Till Single Hung willidow	JEL			
CAD DWG. No.:		Nail Fin Installation (52 1/8" x 75")	ELD WEN				
REV: 01	,	3" x 75	M Sun		•		
REV: 00 SHEET		ָּבָי. ביי	ALICOM	Phone: (541) 882-3451	Klamath Falls, OR, 97601	3050 Lakenort Rive	