WINDOW HEIGHT: 84 TYPICAL ELEVATION WITH FASTENER SPACING WINDOW WIDTH: 84' FROM CORNERS _8" O.C. MAX TYP. THRU NAILFIN

WOOD FRAME SECTION (TYP) VERTICAL SECTION NOTE: Caulk between Nailing Flange & Wood Opening —1 1/2" MIN. EMBEDMENT -1 1/2" MIN. EMBEDMENT (G) (G) -1/4" MAX SHIM SPACE -1/4" MAX SHIM SPACE 3/4" MINIMUM EDGE DISTANCE 3/4" MINIMU EDGE DISTANI

1 1/2" MIN. EMBEDMENT

3/4" MINIMUM EDGE DISTANCE

-1/4" MAX SHIM SPACE

NAILFIN INSTALLATION

General Notes:

90 **M**a×

+

165

MPACT N O

rame 90

FRAME JAMB SECTION (TYP) NOTE: Caulk between Nailing Flange & Wood Opening

HORIZONTAL SECTION

- Building Code (FBC) and the industry requirement for the stated conditions. of the adopted International Building Code (IBC), the International Residential Code (IRC), the Florida The product shown herein is designed tested and manufactured to comply with the wind load criteria
- All glazing shall conform to ASTM E1300.

αω4

- At minimum, glazing shall be double strength annealed insulating glass
- Use structural or composite shims where required

Installation Notes:

- Seal flange/frame to substrate.
- ယ minimum of 1 1/2" into the wood framing. For 2x wood frame substrate (min. S.G. = 0.42) Use #8 PH or greater fastener through the nailfin on all sides with sufficient length to penetrate a
- project of installation. to the structure. The host structure is the responsibility of the architect or engineer of record for the Host structure (wood buck, masonry, steel) to be designed and anchored to properly transfer all loads

| C | NIC | J.HAWKINS |
|---|------------|-------------------|
| , | SCALE: | DRAWN BY: |
| | 06/30/2017 | |
| | DATE: | PROJECT ENGINEER: |

Ë

ELIWEN KLAMATH FALLS OR, 97601 PHONE: (800) 535-3936 3737 LAKEPORT BLVD.

Custom Clad Direct Set Window

PART/PROJECT No. D006942 IDENTIFIER No.

PLANT NAME AND LOCATION: Bend-OR

CustCLDset Cert CAD DWG No

REV

SHEET

 \triangleright

APPROVED BY: CHECKED BY: K.CAMPBEL **D.STOKES**

complete installation procedure, see the instructions packaged with the a guide to the installation process and does not address he sealing (where applicable) up to the size limitations noted. It is not intended as window to achieve the rated design pressure and impact performance This schedule addresses only the fasteners required to anchor the

except as authorized by JELD-WEN Inc. reproduced or copied in whole or in part or used or disclosed to others This drawing and its contents are confidential and are not to be