



1 1/2" MIN. EMBEDMENT

3/4" MINIMUM EDGE DISTANCE

-1/4" MAX SHIM SPACE

NAIL FIN INSTALLATION

## General Notes:

Building Code (FBC) and the industry standard requirement for the stated conditions. the adopted International Building Code (IBC), the International Residential Code (IRC), the Florida The product shown herein is designed, tested and manufactured to comply with the wind load criteria of

Z Q X

rame

MPACT Z

FRAME JAMB SECTION (TYP) NOTE: Caulk between Brickmould & Wood Opening HORIZONTAL SECTION

96

×

**4**∞

1 95

- Buck, framing and masonry by others and is responsibility of architect or engineer of record
- 0 2 4 0 All glazing shall conform to ASTM E1300.
  - At minimum, glazing shall be double strength annealed insulating glass.
- Maximum sizes are buck sizes and do not include fin or flange

## Installed Fastener Schedule:

Seal flange/frame to substrate.

2 -

- Use #8 PH or greater fasteners through nail fin with sufficient length to penetrate a minimum of 1 1/2" into the wood framing. For 2X wood frame substrate (min. S.G. = 0.42).
- ယ project of installation. loads to the structure. The host structure is the responsibility of the architect or engineer of record for the Host structure (wood buck, stud framing and opening) to be designed and anchored to properly transfer all

www.jeld-wen.com/resources/installation packaged with the window or go to conditions. For the complete installation procedure, see the instructions not address the sealing consideration that may arise in different wall noted. It is not intended as a guide to the installation process and does window to achieve the rated design pressure up to the size limitations This schedule addresses only the fasteners required to anchor the

## DISCLAIMER:

except as authorized by JELD-WEN Inc. reproduced or copied in whole or in part or used or disclosed to others This drawing and its contents are confidential and are not to be

IDENTIFIER No.	D004507	APPROVED BY: D.STOKES	CHECKED BY:	J HAWKINS	PROJECT ENGINEER:
Bend, Oregon	TITLE:  Custom Clad InSash FIxed Window			SCALE: NTS	DATE: 06/30/2017
Cad Dwg. No.: CustCLInsashGeo Cert					NHWZ IHI
REV:				_	
>				Phon	
SHEET				Phone: (541) 882-3451	3250 Lakeport Blvd