

WOOD FRAME SECTION (TYP) VERTICAL SECTION NOTE: Caulk between Brickmould & Wood Opening. EDGE DISTANCE 1 1/2" MIN. EMBEDMENT 1/4" MAX SHIM SPACE 1/4" MAX SHIM SPACE 3/4" MINIMUM EDGE DISTANCE 1 1/2" MIN. EMBEDMENT

THRU JAMB INSTALLATION

-1/4" MAX SHIM SPACE

Max 96 Frame 48 /-65 MPACT NO

FRAME JAMB SECTION (TYP) HORIZONTAL SECTION
NOTE: Caulk between Brickmould & Wood Opening

Installed Fastener Schedule:

- \sim \rightarrow Seal flange/frame to substrate.
- the wood framing. For 2X wood frame substrate (min. S.G. = 0.42). Use #8 PH or greater fasteners through jamb with sufficient length to penetrate a minimum of 1 1/2" into
- ယ loads to the structure. The host structure is the responsibility of the architect or engineer of record for the Host structure (wood buck, stud framing and opening) to be designed and anchored to properly transfer all project of installation.

not address the sealing consideration that may arise in different wall window to achieve the rated design pressure up to the size limitations noted. It is not intended as a guide to the installation process and does This schedule addresses only the fasteners required to anchor the

packaged with the window or go to www.jeld-wen.com/resources/installation.

conditions. For the complete installation procedure, see the instructions

DISCLAIMER:

except as authorized by JELD-WEN Inc. reproduced or copied in whole or in part or used or disclosed to others This drawing and its contents are confidential and are not to be

General Notes:

_ 3/4" MINIMUM EDGE DISTANCE

1 1/2" MIN. EMBEDMENT

- Building Code (FBC) and the industry standard requirement for the stated conditions. the adopted International Building Code (IBC), the International Residential Code (IRC), the Florida The product shown herein is designed, tested and manufactured to comply with the wind load criteria of
- Buck, framing and masonry by others and is responsibility of architect or engineer of record
- ωΝ All glazing shall conform to ASTM E1300
- At minimum, glazing shall be double strength annealed insulating glass
- Maximum sizes are buck sizes and do not include fin or flange.

PART/PROJECT NO.: D004805	D.STOKES	CHECKED BY: K.CAMPBELL	J HAWKINS	PROJECT ENGINEER:
		TITLE:	SCALE: NTS	06/30/2017
Custor				
	n Wood Insash			
	Txea		_	•
			none: (541) 882-3451	3250 Lakeport Blvd
	D004805	Gi:		SCALE: NTS