



TYPICAL HORIZONTAL

ווי

MULLION SECTION

副網

EMBEDMENT

MIN. EDGE DISTANCE FOR EDGE: 3/4'--

TYPICAL HORIZONTAL
FRAME SECTION
OTE: Caulk between unit and openin

-1/4" MAX SHIM SPACE

NAIL FIN INSTALLATION

## General Notes:

- Building Code (FBC) and the industry requirement for the stated conditions. the adopted International Building Code (IBC), the International Residential Code (IRC), the Florida The product shown herein is designed, tested and manufactured to comply with the wind load criteria of
- All glazing shall conform to ASTM E1300.
- At minimum, glazing is single strength annealed insulated glass
- Use structural or composite shims where required.
- 9 2 4 5 0 Installation methods can be interchanged within the same opening.
- building code. An impact protective system is required where wind borne debris protection is mandated by local
- Maximum sizes are buck sizes and do not include fin or flange

process and to the size limitations noted. It is not intended as a guide to the installation achieve the rated design pressure and impact performance (where applicable) up This schedule addresses only the fasteners required to anchor the product to

with the window or go to www.jeld-wen.com/resources/installation. conditions. For the complete installation procedure, see the instructions packaged does not address the sealing consideration that may arise in different wal

expressed use of determining anchor requirements for this product only This drawing and its contents are the property of JELD-WEN, Inc. and are for the

## Installation Notes:

M Q X 84"×

Frame

P

MPACT Z

57″

/-50

Seal flange/frame to substrate.

ယ

- minimum of 1" into the wood framing. For two (2X) wood frame substrate (min. S.G. = 0.42). Use #8 X 1 1/4" PH or greater fastener throught the nail fin with sufficient length to penetrate a
- project of installation. to the structure. The host structure is the responsibility of the architect or engineer of record for the Host structure (wood buck, masonry, steel) to be designed and anchored to properly transfer all loads

IDENTIFIER No. PLANT NAME AND LOCATION:	D007207	APPROVED BY:	CHECKED BY: TITLE:	D. Vezo SCALE: NTS	
ATION: CAD DWG. No.:  BM CHS Twin Muled DH Install		Bullders vinyl CHS I win Double Hung			
REV: 00 SHEET 1 of 1		Double Hung		(800) 535-3936	