



SHIM SPACE 1/4" MAX NAIL

FIN INSTALLATION

NOTE: Caulk between Nailing Flange & Wood Opening HORIZONTAL SECTION JAMB SECTION (TYP)

DP RATING IMPACT

+50/-55

8

- Seal flange/frame to substrate
- 2 into the wood framing. For 2X wood frame substrate (min. S.G. = 0.42). Use #8 PH or greater fastener though the nail fin with sufficient length to penetrate a minimum of 1 1/2'
- ယ to the structure. The host structure is the responsibility of the architect or engineer of record for the Host structure (wood buck, masonry, steel) to be designed and anchored to properly transfer all loads project of installation.

conditions. For the complete installation procedure, see the instructions not address the sealing consideration that may arise in different wall noted. It is not intended as a guide to the installation process and does window to achieve the rated design pressure up to the size limitations packaged with the window or go to www.jeld-wen.com. This schedule addresses only the fasteners required to anchor the

## DISCLAIMER

except as authorized by JELD-WEN Inc reproduced or copied in whole or in part or used or disclosed to others This drawing and its contents are confidential and are not to be

AS TESTED

## General Notes:

- of the adopted International Building Code(IBC), the International Residential Code(IRC), the Florida Building Code(FBC) and the industry requirement for the stated conditions. The product shown herein is designed, tested and manufactured to comply with the wind load criteria
- All glazing shall conform to ASTM E1300.
- At minimum, glazing shall be single strength annealed insulating glass
- Use structural or composite shims where required

9 2 3

- building code. An impact protective system is required where wind borne debris protection is mandated by local
- Maximum sizes are buck sizes and do not include fin or flange

0 SHEET 10F1	REV: 00	CAD DWG. No.:	TION:	PLANT NAME AND LOCATION	SJW2013-233-FBC
	,				PART/PROJECT No.: D010587
	" x 72")	Nail Fin Installation (36" x 72")	Nail Fi		1
Window	ement	Premium Vinyi Stationary Casement Window	mium viny	Pre	APPROVED BY:
				шпе	CHECKED BY:  J. Kantola
Phone: (800) 535-3936	_		عند ل	SCALE: NTS	D. Vezo
3737 Lakeport Blvd	_,	NEW ZIE		04/08/2015	PROJECT ENGINEER: