SECTION

I - I/2" MAX. FROM CORNERS EACH SIDE.

MAX. O.C. TYP

D -

MAX. EXPOSED WINDOW WIDTH 48"

(A) TYPICAL OUTSIDE ELEVATION

## NOTE:

FOR SUNROOM WALL INFO SEE APPROPRIATE FLORIDA PRODUCT APPROVAL REPORT

. THIS WINDOW IS APPROVED ONLY FOR INSTALLATION INTO SEPARATELY ENGINEERED FOUR SEASONS ALUMINUM SUNROOM, INSTALLATION INTO ANY OTHER SUBSTRATE SHALL REQUIRE A SEPARATE, SITE SPECIFIC DESIGN TO BE PREPARED BY A FL-REGISTERED PROFESSIONAL ENGINEER, AND SUBMITTED TO THE AUTHORITY HAVING JURISDICTION FOR APPROVAL 2. ALL FASTENERS SHALL PENETRATE SHEET METAL WITH THREE FULL THREAD

REFER TO MFR. INFORMATION **# TEST DATA FOR MORE** INFORMATION ON EXTRUSIONS

NATER PENETRATION PER ASTM E547: 12 PSF AIR INFILTRATION PER ASTM E283

# (AI) ALUMINUM

BUILDING CODE SEVENTH EDITION (2020)

5/32" TEMPERED

(G1) GLASS DETAIL (NON IMPACT)

## VISIT ECALC.IO/39520

SUNROOM COLUMN MAY VARY

DEPENDING ON WALL

2 1/4" TYP

AT JAMBS REF

I - I/2" O.C.

1-1/2"

TYP. MAX.

MAX FXPOSED

WINDOW

HEIGHT 82"

½" ALUMINUM I.G. SPACER. TYP.

SILICONE SEALANT, TYP

1/8"x/2"x1" 85 +/- 5 SHORE A

(2) I WEEP HOLES

I.GLASS THICKNESS COMPLIES WITH ASTM E1300 REQUIREMENTS

2.SETTING BLOCK SHALL COMPLY WITH 24 | 1.3.3.1 OF THE FLORIDA

CLOSED CELL FOAM FRAME

DUROMETER SETTING.

BLOCKS @ 1/4 POINTS

FOR HELPFUL RESOURCES. SITE SPECIFIC JOB ORDERING & MORE NFORMATION ABOUT THIS PRODUCT & RELATED SERVICES



SMS @ 12" O/C MIN.

CORNERS EACH SIDE.

VINYL GLAZING BEAD, TYP

\*#8 SMS @ 12" O/C MIN 1-1/2" MAX. FROM

CORNERS EACH SIDE

## (NON IMPACT APPROVED) MAXIMUM ALLOWABLE DESIGN PRESSURES

+75 PSF / -75 PSF

## **DESIGN NOTES:**

REQUIREMENTS AS DETERMINED IN ACCORDANCE WITH ASCE 7-16 AND CHAPTER

ONLY & AS PER FBC 2002.6

## **GENERAL NOTES:**

DESIGN OF THIS SYSTEM.

3. THE ARCHITECT/ENGINEER OF RECORD FOR THE PROJECT SUPERSTRUCTURE WITH WHICH THIS DESIGN IS USED SHALL BE RESPONSIBLE FOR THE INTEGRITY OF ALL SUPPORTING SURFACES TO THIS DESIGN WHICH SHALL BE COORDINATED BY THE PERMITTING CONTRACTOR.

THE CONDITIONS DETAILED HEREIN, A LICENSED ENGINEER OR REGISTERED ARCHITECT SHALL PREPARE SITE SPECIFIC DOCUMENTS FOR USE IN CONJUNCTION WITH THIS DOCUMENT.

THE MINIMUM ALLOYS AND TEMPERS AS SPECIFIED IN THE BILL OF MATERIALS.

6. ALL FASTENERS TO BE 1/4"Ø SAE GRADE 5 CARBON STEEL UNLESS NOTED OTHERWISE. FASTENERS SHALL BE CADMIUM-PLATED OR OTHERWISE CORROSION-RESISTANT MATERIAL AND SHALL COMPLY WITH THE ALUMINUM

THE CONTRACTOR IS RESPONSIBLE TO INSULATE ALL MEMBERS FROM DISSIMILAR MATERIALS TO PREVENT ELECTROLYSIS.

ENGINEER SEAL AFFIXED HERE TO VALIDATES STRUCTURAL DESIGN AS SHOWN ONLY. USE OF THIS SPECIFICATION BY CONTRACTOR, et. al. INDEMNIFIES & SAVES HARMLESS THIS ENGINEER FOR ALL COST & DAMAGES INCLUDING LEGAL FEES & APPELLATE FEES RESULTING FROM MATERIAL FABRICATION, SYSTEM ERECTION, & CONSTRUCTION PRACTICES BEYOND THAT WHICH IS CALLED FOR BY LOCAL, STATE, & FEDERAL CODES & FROM DEVIATIONS

11. PRODUCT SHALL BE PERMANENTLY LABELED WITH A MINIMUM OF ONE

ALL UNSPECIFIED INFORMATION SHALL BE PER TEST REPORTS Nos. 10-FS-006B AND #10-FS-001 BY MATERIALS TESTING LAB. INC., WHICH IS ATTACHED TO THIS CERTIFICATION.

# (A.S.D.):

1. POSITIVE AND NEGATIVE DESIGN PRESSURES CALCULATED FOR USE WITH THIS SYSTEM SHALL BE DETERMINED BY OTHERS ON A JOB-SPECIFIC BASIS IN ACCORDANCE WITH THE GOVERNING CODE. SITE-SPECIFIC PRESSURE REQUIREMENTS AS DETERMINED IN ACCORDANCE WITH ASCE 7-16 AND CHAPTER 1609 OF THE FLORIDA BUILDING CODE SEVENTH EDITION (2020) SHALL BE LESS THAN OR EQUAL TO THE POSITIVE OR NEGATIVE DESIGN PRESSURE CAPACITY VALUES LISTED HEREIN FOR ANY ASSEMBLY AS SHOWN.

2. FOR USE IN SUNROOMS, SYSTEM TO BE USED AS AN AAMA 2100 CATEGORY I-I

3. THE HOST STRUCTURE IS NOT TO BE MODIFIED WITH THE ADDITION OF THIS

THIS SYSTEM DESCRIBED HEREIN HAS BEEN DESIGNED AND TESTED IN ACCORDANCE WITH THE FLORIDA BUILDING CODE SEVENTH EDITION (2020) PER AAMA/WDMA/CSA 101/I.S.2/A440-08 AND TAS 202 STANDARDS FOR USE WITHIN AND OUTSIDE THE HIGH VELOCITY HURRICANE ZONE (HVHZ).

NO 33-1/3% INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE

4. THE SYSTEM DETAILED HEREIN IS GENERIC AND DOES NOT PROVIDE INFORMATION FOR A SPECIFIC SITE. FOR SITE CONDITIONS DIFFERENT FROM

ALL ALUMINUM EXTRUSIONS SHALL BE EQUIVALENT TO OR GREATER THAN

ASSOCIATION, INC., & ANY APPLICABLE FEDERAL, STATE, AND/OR LOCAL CODES.

OF THIS PLAN.

9. EXCEPT AS EXPRESSLY PROVIDED HEREIN, NO ADDITIONAL CERTIFICATIONS OR AFFIRMATIONS ARE INTENDED.

10. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE THIS CERTIFICATION.

WINDOW CONTAINING THE FOLLOWING: FOUR SEASONS SOLAR PRODUCTS LLC HOLBROOK, NY AAMA/WDMA/CSA 101/I.S.2/A440-08

> APPROVED BY FLORIDA BUILDING COMMISSION FLORIDA PRODUCT APPROVAL NUMBER

THE SYSTEM DETAILED HEREIN HAS BEEN TESTED PER THE TEST STANDARD(S) LISTED ABOVE AS REFERENCED IN TEST REPORTS #10-FS-006B AND #10-FS-001 BY MATERIALS TESTING LAB, INC.

RANK BENNARDO, P.E

FL#15202.1

PRODUCTS, I

SOLAR PRO

SEASONS S

FOUR

FIXED WINDOW (48"x82") FOR SUNROOM FLORIDA PRODUCT APPROVAL

21-39520

CALE: NTS UNLESS NOTED

