

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.

NOTES:


1. THE PRODUCT SHOWN HEREIN IS DESIGNED AND MANUFACTURED TO COMPLY WITH REQUIREMENTS OF THE FLORIDA BUILDING CODE INCLUDING THE HVHZ.
2. WOOD FRAMING AND MASONRY OPENING TO BE DESIGNED AND ANCHORED TO PROPERLY TRANSFER ALL LOADS TO STRUCTURE. FRAMING AND MASONRY OPENING IS THE RESPONSIBILITY OF THE ARCHITECT OR ENGINEER OF RECORD.
3. 1X BUCK OVER MASONRY/CONCRETE IS OPTIONAL. WHERE 1X BUCK IS NOT USED DISSIMILAR MATERIALS MUST BE SEPARATED WITH APPROVED COATING OR MEMBRANE. SELECTION OF COATING OR MEMBRANE IS THE RESPONSIBILITY OF THE ARCHITECT OR ENGINEER OF RECORD.
4. ALLOWABLE STRESS INCREASE OF 1/3 WAS NOT USED IN THE DESIGN OF THE PRODUCT SHOWN HEREIN. WIND LOAD DURATION FACTOR Cd=1.6 WAS USED FOR WOOD ANCHOR CALCULATIONS.
5. FRAME MATERIAL: ALUMINUM 6063-T6
6. UNITS MUST BE GLAZED PER ASTM E1300, WITH SAFETY GLAZING.
7. APPROVED IMPACT PROTECTIVE SYSTEM IS REQUIRED FOR THIS PRODUCT IN WIND BORNE DEBRIS REGIONS.
8. SHIM AS REQUIRED AT EACH INSTALLATION ANCHOR WITH LOAD BEARING SHIM. SHIM WHERE SPACE OF 1/16" OR GREATER OCCURS. MAXIMUM ALLOWABLE SHIM STACK TO BE 1/4".
9. FOR ANCHORING INTO WOOD FRAMING OR 2X BUCK USE #10 WOOD SCREWS WITH SUFFICIENT LENGTH TO ACHIEVE A 1 1/4" MINIMUM EMBEDMENT INTO SUBSTRATE. LOCATE ANCHORS AS SHOWN IN ELEVATIONS AND INSTALLATION DETAILS.

10. FOR ANCHORING INTO MASONRY/CONCRETE USE 3/16" ELCO ULTRACON OR 1/4" TAPCONS WITH SUFFICIENT LENGTH TO ACHIEVE A 1 3/4" MINIMUM EMBEDMENT INTO SUBSTRATE WITH 2" MINIMUM EDGE DISTANCE. LOCATE ANCHORS AS SHOWN IN ELEVATIONS AND INSTALLATION DETAILS.
11. FOR ANCHORING INTO METAL STRUCTURE USE #10 SMS OR SELF DRILLING SCREWS WITH SUFFICIENT LENGTH TO ACHIEVE 3 THREADS MINIMUM BEYOND STRUCTURE INTERIOR WALL. LOCATE ANCHORS AS SHOWN IN ELEVATIONS AND INSTALLATION DETAILS.
12. ALL FASTENERS TO BE CORROSION RESISTANT.
13. INSTALLATION ANCHORS SHALL BE INSTALLED IN ACCORDANCE WITH ANCHOR MANUFACTURER'S INSTALLATION INSTRUCTIONS AND ANCHORS SHALL NOT BE USED IN SUBSTRATES WITH STRENGTHS LESS THAN THE MINIMUM STRENGTH SPECIFIED BELOW:
  - A. WOOD – MINIMUM SPECIFIC GRAVITY OF G=0.42
  - B. CONCRETE – MINIMUM COMPRESSIVE STRENGTH OF 3,000 PSI.
  - C. GROUT FILLED MASONRY – STRENGTH CONFORMANCE TO ASTM C-90, GRADE N, TYPE 1 (OR GREATER).
  - D. METAL STRUCTURE: STEEL 18GA, 33KSI OR ALUMINUM 6063-T5 .125" THICK MINIMUM

TABLE OF CONTENTS	
SHEET NO.	DESCRIPTION
1	NOTES
2	ELEVATIONS
3 – 4	CROSS SECTIONS
5 – 7	INSTALLATION DETAILS
8	COMPONENTS


SOLAR INNOVATIONS, INC. 31 ROBERTS RD PINE GROVE, PA 17963		
SERIES SI8100 SLIDING GLASS DOOR 5x8 PANEL NON-IMPACT HVHZ NOTES		
DRAWN: A.R.	DWG NO. 08-03418	REV A
SCALE NTS	DATE 04/15/19	SHEET 1 OF 8
L. ROBERTO LOMAS P.E. 1432 WOODFORD RD LEWISVILLE, NC 27023 434-688-0609 rllomas@lrlomaspe.com		

SIGNED: 11/19/2020



Luis R. Lomas P.E.  
FL No.: 62514

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.



**NOTES:**  
 1. PANEL SIZE: 60 1/2" x 99"  
 2. D.L.O.: 55 1/2" x 92 5/16"

(2) ANCHORS PER LOCATION AT HEAD AND JAMBS

(1) ANCHOR PER LOCATION AT SILL

**SERIES SI8100 SLIDING GLASS DOOR 5x8 PANEL**  
 EXTERIOR VIEW

FOR OTHER PANEL SIZE RATINGS SEE CHART #1 THIS SHEET

DESIGN PRESSURE RATING	IMPACT RATING
±65.0PSF	NONE

UNITS WITH 4 PANELS MAXIMUM IN UNLIMITED CONFIGURATIONS ARE APPROVED AS LONG AS INDIVIDUAL PANEL AREA DOES NOT EXCEED 41.59 FT<sup>2</sup> AND FRAME AREA DOES NOT EXCEED 254.48 FT<sup>2</sup> AND USES VERTICAL CONDITIONS AS SHOWN.

**Chart #1**

Panel Height (in)	Maximum Design pressure (psf)															
	Single Panel Width (in)															
	24.0		30.0		36.0		42.0		48.0		54.0		60.5		66.0	
	Pos	Neg	Pos	Neg	Pos	Neg	Pos	Neg	Pos	Neg	Pos	Neg	Pos	Neg	Pos	Neg
78.0	80.0	97.5	80.0	97.5	80.0	97.5	80.0	97.5	80.0	97.5	80.0	92.4	80.0	82.5	75.6	75.6
84.0	80.0	97.5	80.0	97.5	80.0	97.5	80.0	97.5	80.0	93.9	80.0	85.8	76.6	76.6	70.2	70.2
90.0	80.0	97.5	80.0	97.5	80.0	97.5	80.0	93.3	80.0	85.3	79.5	79.5	71.5	71.5	65.5	65.5
96.0	80.0	97.5	80.0	97.5	80.0	96.3	80.0	85.8	78.2	78.2	72.6	72.6	67.0	67.0	-	-
99.0	80.0	97.5	80.0	97.5	80.0	92.7	80.0	82.5	75.1	75.1	69.5	69.5	65.0	65.0	-	-
102.0	80.0	97.5	80.0	97.5	80.0	89.4	78.5	78.5	70.2	70.2	64.0	64.0	-	-	-	-
108.0	80.0	97.5	80.0	89.2	75.4	75.4	65.7	65.7	58.6	58.6	53.2	53.2	-	-	-	-
114.0	80.0	93.5	75.6	75.6	63.8	63.8	55.5	55.5	49.4	49.4	-	-	-	-	-	-
120.0	80.0	80.1	64.6	64.6	54.5	54.5	47.3	47.3	42.0	42.0	-	-	-	-	-	-
126.0	69.0	69.0	55.7	55.7	46.9	46.9	40.7	40.7	-	-	-	-	-	-	-	-
132.0	60.0	60.0	48.3	48.3	40.7	40.7	35.2	35.2	-	-	-	-	-	-	-	-
138.0	52.4	52.4	42.2	42.2	35.5	35.5	30.7	30.7	-	-	-	-	-	-	-	-
144.0	46.1	46.1	37.1	37.1	31.2	31.2	-	-	-	-	-	-	-	-	-	-
150.0	40.7	40.7	32.8	32.8	27.5	27.5	-	-	-	-	-	-	-	-	-	-
156.0	36.2	36.2	29.1	29.1	24.4	24.4	-	-	-	-	-	-	-	-	-	-

**HARDWARE SCHEDULE**

A.	(2) POINT METAL LOCK WITH KEEPERS, 42" FROM BOTTOM OF LOCK STILE
B.	DUAL STAINLESS STEEL ROLLERS AT EACH END OF BOTTOM RAILS
C.	ALUMINUM REINFORCEMENT PANEL ADAPTER AT MEETING STILE IN PANELS 1 & 2

SIGNED: 11/19/2020

SOLAR INNOVATIONS, INC.  
 31 ROBERTS RD  
 PINE GROVE, PA 17963

SERIES SI8100 SLIDING GLASS DOOR  
 5x8 PANEL NON-IMPACT HVHZ  
 ELEVATIONS

DRAWN: A.R. DWG NO. 08-03418 REV A


SCALE NTS DATE 04/15/19 SHEET 2 OF 8

L. ROBERTO LOMAS P.E.  
 1432 WOODFORD RD LEWISVILLE, NC 27023  
 434-688-0609 rllomas@rlomaspe.com




Luis R. Lomas P.E.  
 FL No.: 62514

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.



**EXTERIOR**



**VERTICAL CROSS SECTION**


SOLAR INNOVATIONS, INC.  
31 ROBERTS RD  
PINE GROVE, PA 17963

SERIES SI8100 SLIDING GLASS DOOR  
5x8 PANEL NON-IMPACT HVHZ  
CROSS SECTIONS

DRAWN: A.R.	DWG NO. 08-03418	REV A
SCALE NTS	DATE 04/15/19	SHEET 3 OF 8

L. ROBERTO LOMAS P.E.  
1432 WOODFORD RD LEWISVILLE, NC 27023  
434-688-0609 rllomas@rlomaspe.com



SIGNED: 11/19/2020



Luis R. Lomas P.E.  
FL No.: 62514

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.

**HORIZONTAL CROSS SECTION**



**SOLAR INNOVATIONS, INC.**  
 31 ROBERTS RD  
 PINE GROVE, PA 17963

**SERIES SI8100 SLIDING GLASS DOOR**  
 5x8 PANEL NON-IMPACT HVHZ  
 CROSS SECTIONS


DRAWN: A.R.	DWG NO. 08-03418	REV A
SCALE NTS	DATE 04/15/19	SHEET 4 OF 8

L. ROBERTO LOMAS P.E.  
 1432 WOODFORD RD LEWISVILLE, NC 27023  
 434-688-0609 rllomas@rlomaspe.com

SIGNED: 11/19/2020


Luis R. Lomas P.E.  
 FL No.: 62514

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.



**VERTICAL CROSS SECTION**  
WOOD FRAMING OR 2X BUCK INSTALLATION

- NOTES:**
1. INTERIOR AND EXTERIOR FINISHES, BY OTHERS, NOT SHOWN FOR CLARITY.
  2. PERIMETER AND JOINT SEALANT BY OTHERS TO BE DESIGNED IN ACCORDANCE WITH ASTM E2112



**JAMB INSTALLATION DETAIL**  
WOOD FRAMING OR 2X BUCK INSTALLATION


SOLAR INNOVATIONS, INC.  
31 ROBERTS RD  
PINE GROVE, PA 17963

SERIES SI8100 SLIDING GLASS DOOR  
5x8 PANEL NON-IMPACT HVHZ  
INSTALLATION DETAILS

DRAWN: A.R.	DWG NO. 08-03418	REV A
SCALE NTS	DATE 04/15/19	SHEET 5 OF 8


L. ROBERTO LOMAS P.E.  
1432 WOODFORD RD LEWISVILLE, NC 27023  
434-688-0609 rllomas@rlomaspe.com

SIGNED: 11/19/2020




Luis R. Lomas P.E.  
FL No.: 62514

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.



**VERTICAL CROSS SECTION**  
METAL STRUCTURE INSTALLATION

- NOTES:
1. INTERIOR AND EXTERIOR FINISHES, BY OTHERS, NOT SHOWN FOR CLARITY.
  2. PERIMETER AND JOINT SEALANT BY OTHERS TO BE DESIGNED IN ACCORDANCE WITH ASTM E2112



**JAMB INSTALLATION DETAIL**  
METAL STRUCTURE INSTALLATION

SEE SHEET 9 FOR ADDITIONAL TRESHOLDS


SOLAR INNOVATIONS, INC.  
31 ROBERTS RD  
PINE GROVE, PA 17963

SERIES SI8100 SLIDING GLASS DOOR  
5x8 PANEL NON-IMPACT HVHZ  
INSTALLATION DETAILS

DRAWN: A.R.	DWG NO. 08-03418	REV A
SCALE NTS	DATE 04/15/19	SHEET 6 OF 8


L. ROBERTO LOMAS P.E.  
1432 WOODFORD RD LEWISVILLE, NC 27023  
434-688-0609 rllomas@rlomaspe.com

SIGNED: 11/19/2020




Luis R. Lomas P.E.  
FL No.: 62514

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.



**VERTICAL CROSS SECTION**  
CONCRETE/MASONRY INSTALLATION



**JAMB INSTALLATION DETAIL**  
CONCRETE/MASONRY INSTALLATION

- NOTES:**
1. INTERIOR AND EXTERIOR FINISHES, BY OTHERS, NOT SHOWN FOR CLARITY.
  2. PERIMETER AND JOINT SEALANT BY OTHERS TO BE DESIGNED IN ACCORDANCE WITH ASTM E2112

3/16" ELCO ULTRACON OR  
1/4" TAPCON

SEE SHEET 9  
FOR ADDITIONAL  
THRESHOLDS


SOLAR INNOVATIONS, INC.  
31 ROBERTS RD  
PINE GROVE, PA 17963

SERIES SI8100 SLIDING GLASS DOOR  
5x8 PANEL NON-IMPACT HVHZ  
INSTALLATION DETAILS

DRAWN: A.R.	DWG NO. 08-03418	REV A
SCALE NTS	DATE 04/15/19	SHEET 7 OF 8














L. ROBERTO LOMAS P.E.  
1432 WOODFORD RD LEWISVILLE, NC 27023  
434-688-0609 rllomas@lrlomaspe.com

SIGNED: 11/19/2020



Luis R. Lomas P.E.  
FL No.: 62514

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	REVISED PER NEW REQUIREMENTS	11/03/2020	R.L.



**SOLAR INNOVATIONS, INC.**  
 31 ROBERTS RD  
 PINE GROVE, PA 17963

SERIES SI8100 SLIDING GLASS DOOR  
 5x8 PANEL NON-IMPACT HVHZ  
 COMPONENTS

DRAWN: A.R.	DWG NO. 08-03418	REV A
SCALE NTS	DATE 04/15/19	SHEET 8 OF 8

L. ROBERTO LOMAS P.E.  
 1432 WOODFORD RD LEWISVILLE, NC 27023  
 434-688-0609 rllomas@rlomaspe.com

SIGNED: 11/19/2020

Luis R. Lomas P.E.  
 FL No.: 62514