


## THROUGH FRAME INSTALLATION



NO	+50/-50	80.1250"	73.8125" x
IMPACT	DP	FRAME	MAXIMUM

## Installation Notes:

- silicone caulk (typ.). Seal flange/frame to substrate. Sill shall be set on a continuous serpentine bead of structural grade
- 2 substrate (min. S.G. = 0.42) minimum of 1 1/2" into the wood framing with a 3/4" min. from edge distance. For 2x wood frame Use #8 SFH or greater fastener through the head & side jambs with sufficient length to penetrate a
- Use (1) #8 TFH or greater fastener through each Hinge with sufficient length to penetrate a minimum of 1 1/2" into the wood framing
- project of installation. to the structure. The host structure is the responsibility of the architect or engineer of record for the Host structure (wood buck, masonry, steel) to be designed and anchored to properly transfer all loads

## General Notes:

- of the adopted International Building Code (IBC), the International Residential Code (IRC), the Florida Building Code (FBC) and the industry requirement for the stated conditions. The product shown herein is designed, tested and manufactured to comply with the wind load criteria
- All glazing shall conform to ASTM E1300

 $\omega N$ 

Use structural or composite shims where required

1 OF 1		ī	7	K5516.01-301-47	"AS TESTED"
SHEET . OI	REV:	CAD DWG No.		IDENTIFIER No.	
				PART/PROJECT No.: D015785	
VING	OD ISW	ARCHITECTURAL FIBERGLASS OUTSWING	AX	APPROVED BY: D. VEZO	
			TITLE:	CHECKED BY D. VEZO	
PHONE: (800) 535-3936	PHON	ITE W SERVE	SCALE: NTS	T BROOKS	
3737 LAKEPORT BLVD.	373 KI AMAT	3737 LAKEPORT BLVD	DATE: 03/17/20		

unit or go to www.jeld-wen.com

complete installation procedure, see the instructions packaged with the consideration that may arise in different wall conditions. For the to the installation process and does not address the sealing to achieve the rated design pressure and impact performance (where applicable) up to the size limitations noted. It is not intended as a guide This schedule addresses only the fasteners required to anchor the unit

except as authorized by JELD-WEN Inc. reproduced or copied in whole or in part or used or disclosed to others This drawing and its contents are confidential and are not to be